



IBM 000-114

Exam Name: *Storage Implementation Entry/Mid Range DS Series*

Q & A : 130 Q&As

Pdf Demo

Quality and Value for the 000-114 Exam

[Just4Exams Practice Exams](#) for IBM IBM certifications III 000-114 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

100% Guarantee to Pass Your 000-114 Exam

If you do not pass the IBM certifications III 000-114 exam on your first attempt using our Just4Exams **000-114 testing engine and pdf study guide**, we will give you a FULL REFUND of your purchasing fee.

Downloadable, Interactive 000-114 Testing engines and PDF Version

Our Exam Preparation Material provides you everything you will need to take a [IBM certifications III certification](#) examination. Details are researched and produced by [IBM Certification](#) Experts who are constantly using industry experience to produce precise, and logical.

Free 000-114 Exams:

This is demo only, this pdf do not include the questions and answers picture

Exam : IBM 000-114

Title : Storage Implementation Entry/Mid Range DS Series

1. How would you cable 2 EXP5000 to a DS5300 on one drive channel? Cable from each controller to the _____.

- A. 1A port of the first ESM and then cable from 1B port to the 1A port of the second ESM
- B. 1B port of the first ESM and then cable from 1A port to the 1B port of the second ESM
- C. 2A port of the first ESM and then cable from 2B port to the 2A port of the second ESM
- D. 2B port of the first ESM and then cable from 2A port to the 2B port of the second ESM

Answer: B

2. A customer is using FlashCopy to backup a 350GB logical drive. During the backup process, the data will change by 68%. What should the minimum repository logical drive size be?

- A. 70GB
- B. 220GB
- C. 245GB
- D. 350GB

Answer: C

3. If a customer wants to increase the capacity of a logical drive to 700 GB without adding drives to the array, what must be available on the storage subsystem?

- A. Sufficient, unconfigured capacity in the array.
- B. Sufficient free capacity in the array.
- C. Sufficient unconfigured capacity in the subsystem.
- D. Sufficient free capacity in the subsystem.

Answer: B

4. When examining a profile you see the following:

Drive at Enclosure 5, Slot 8 [mirrored pair with drive at enclosure 5, slot 9]

Drive at Enclosure 5, Slot 9 [mirrored pair with drive at enclosure 5, slot 8]

How should this be configured for enclosure loss protection?

- A. Drive at Enclosure 5, Slot 9 [mirrored pair with drive at enclosure 5, slot 9]
- B. Drive at Enclosure 3, Slot 1 [mirrored pair with drive at enclosure 5, slot 9]
- Drive at Enclosure 5, Slot 9 [mirrored pair with drive at enclosure 3, slot 1]
- C. Drive at Enclosure 5, Slot 7 [mirrored pair with drive at enclosure 5, slot 9]
- Drive at Enclosure 5, Slot 9 [mirrored pair with drive at enclosure 5, slot 7]
- D. Drive at Enclosure 5, Slot 9 [mirrored pair with drive at enclosure 15, slot 18]

Drive at Enclosure 15, Slot 18 [mirrored pair with drive at enclosure 5, slot 9]

Answer: B

5. A new LUN has been created and mapped to a Windows host, but on the host system the LUN does not appear. Which action should be taken to see the LUN from the host?

- A. run SMDDevices
- B. run hot_add
- C. run SMRepassist
- D. run SMSScanLUNs

Answer: D

6. Even though some host operating systems may impose limitations, how many LUNs can be mapped to a host or host group using the storage manager?

- A. 32
- B. 128
- C. 256
- D. 512

Answer: C

7. You see an amber light flashing on an EXP810 ESM. Where should you start to find information on how to handle the flashing amber light?

- A. Recovery Guru
- B. Major Event Log (MEL)
- C. Storage Manager online help
- D. Read Link Status counters related to the specific ESM

Answer: A

8. The automatic discovery function of Storage Manager 10.10 allows the discovery of any DS3000, DS4000 and DS5000 connected in the customer environment:

- A. If the DS3000/DS4000/DS5000 are in the IP subnet
- B. If they have the latest firmware release installed
- C. If they can be discovered on other IP subnets
- D. The DS4000 and DS5000 can only be automatically discovered

Answer: A

9. What is a possible outcome when Media Scan detects an unrecovered media error on controller code revision 6.60.xx?

- A. Unrecovered media errors are not fixable. A critical event will be logged in the Major Event Log (MEL) and subsequent manual intervention will be required.
- B. If the RAID type is 0, then the data from the mirrored drive will be used to restore the data.
- C. A counter is kept of the number of unrecovered media errors and when a user defined threshold is met, an audible alarm will sound and the LED on the suspect drive will turn amber.
- D. If redundancy exists, the data will be reconstructed, written to disk, and verified.

Answer: D

10. What is a suggested purpose of the Storage Manager command line interface (SMcli)?

- A. to change parameters on multiple storage subsystems
- B. to save the subsystem configuration
- C. to script repeatable operations on a storage subsystem
- D. All of the above

Answer: D

11. What is the minimum firmware level required for an upgrade to firmware 7.10.xx?

- A. 6.12.xx.xx
- B. 6.16.xx.xx
- C. 6.23.xx.xx
- D. 6.60.xx.xx

Answer: B

12. A customer who has been using Metro Mirror with an Enhanced Remote Mirroring (ERM) configuration to mirror the company inventory database from headquarters to a data warehouse at a remote site has asked for some assistance. Due to bandwidth concerns they need to change the mirroring mode to Global Mirroring. What must be done to help the customer make the change?

- A. Advise the customer to purchase two new licenses.
- B. Break and re-establish the mirror relationship.
- C. Backup the inventory data to tape.
- D. Make the mode change in Storage Manager.

Answer: D

13. What is the minimum number of disks needed for RAID 6 on a DS4000 or DS5000 system?

- A. 3
- B. 4
- C. 5
- D. 6

Answer: C

14. A customer has a DS4800 with five EXP810. They plan to upgrade to a DS5300, the maximum power consumption will be ____.

- A. equal
- B. lower
- C. higher
- D. no difference

Answer: C

15. On a DS5000 there are several LUNs hosting small-block, write intensive databases. What is the smallest cache block-size that can be configured?

- A. 1K
- B. 2K
- C. 4K
- D. 8K

Answer: C

16. How often will a Windows operating system without multi-pathing software detect a target LUN?

- A. once per controller
- B. once per bus
- C. once per path
- D. once per port

Answer: C

17. What are features and benefits of RSM?

- a. Built in firewall
- b. Runs on Linux and Windows servers
- c. Collect support data d. Allow remote maintenance
- e. Can support up to 50 DS5000/DS4000/DS3000 storage servers
- f. Minimum annual fee

- A. a, b and e
- B. a, e and f
- C. b, c and f
- D. a, d and e

Answer: D

18. A customer asks you for a reference(s) to help him when troubleshooting problems with the company DS4800. Which official publication has walkthroughs for common fixes on the DS4800?

- A. Installation, User, and Maintenance Guide
- B. Techline / Partner Line
- C. DS4000 Problem Determination Guide
- D. A, B, and C

Answer: D

19. A customer observes higher response times for running transactions, they see spikes in disk activity. What should be checked first?

- A. Backend channel for failed SFPs
- B. Cache flush control settings
- C. ReadLinkStatus diagnostics
- D. Error log for a failed drive in that array

Answer: B

20. What is the correct command syntax to connect the Command Line Interface (CLI) to the storage subsystem?

- A. smcli -n
- B. smcli -h
- C. smcli -L
- D. smcli -e

Answer: A

More [000-114 Braindumps](#) Information

Related 000-114 Exams

000-101	000-100	000-330	000-418	000-962
COG-480	000-136	000-960	000-210	000-433
000-432	COG-300	000-314	000-019	000-R18
000-233	000-071	000-209	000-M22	000-M15

Other IBM Exams

000-926	000-850	000-568	000-285	000-M30
000-025	000-294	COG-145	000-834	000-081
000-815	LOT-956	000-238	000-915	000-867
000-078	000-417	LOT-755	000-373	000-923