



IBM 000-735

Exam Name: DB2 9.5 SQL Procedure Developer

Q & A : 99 Q&As

Pdf Demo

Quality and Value for the 000-735 Exam

[Just4Exams Practice Exams](#) for IBM DB2 000-735 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

100% Guarantee to Pass Your 000-735 Exam

If you do not pass the DB2 000-735 exam on your first attempt using our Just4Exams **000-735 testing engine and pdf study guide**, we will give you a FULL REFUND of your purchasing fee.

Downloadable, Interactive 000-735 Testing engines and PDF Version

Our Exam Preparation Material provides you everything you will need to take a [DB2 certification](#) examination. Details are researched and produced by [IBM Certification](#) Experts who are constantly using industry experience to produce precise, and logical.

Free 000-735 Exams:

This is demo only, this pdf do not include the questions and answers picture

Exam : IBM 000-735

Title : DB2 9.5 SQL Procedure Developer

1. What demonstrates the correct syntax for assigning three rows to the EMPNO, FIRSTNAME, and LASTNAME columns of a table named EMPLOYEE?

- A. INSERT INTO employee (empno, firstname, lastname)
VALUES (100, 200, 300, 'John', 'Jane', 'Paul', 'Doe', 'Smith', 'Jones')
- B. INSERT INTO employee (empno, firstname, lastname)
VALUES (100, 'John', 'Doe'), (200, 'Jane', 'Smith'), (300, 'Paul', 'Jones')
- C. SET (empno, firstname, lastname)
VALUES (100, 200, 300, 'John', 'Jane', 'Paul', 'Doe', 'Smith', 'Jones')
FOR employee

D. SET (empno, firstname, lastname)
VALUES (100, 'John', 'Doe'), (200, 'Jane', 'Smith'), (300, 'Paul', 'Jones')
FOR employee
Answer: B

2. Click the Exhibit button.

Given the following SQL procedure:

```
CREATE PROCEDURE test1 (IN someid CHAR(3), OUT status INT)
BEGIN
DECLARE SQLCODE INTEGER DEFAULT 0;
DECLARE count INTEGER DEFAULT 0;
SET status = 0;
IF (LENGTH(someid) < 3) THEN
RETURN -3;
GOTO exit;
ELSE
SELECT COUNT(deptno) INTO count FROM dept WHERE admrdept=someid;
IF(SQLCODE<>0) THEN
RETURN -1;
ELSE
SET status = COUNT;
RETURN 0;
END IF;
END IF;
exit:
RETURN -2;
END
```

Where the DEPT table consists of:

```
DEPTNO DEPTNAME
MGRNO ADMRDEPT
```

```
-----
-----
A00 SPIFFY COMPUTER SERVICE DIV. 000010 A00
B01 PLANNING 000020 A00
C01 INFORMATION CENTER 000030 A00
D01 DEVELOPMENT CENTER - A00
D11 MANUFACTURING SYSTEMS 000060 D01
D21 ADMINISTRATION SYSTEMS 000070 D01
```

If the procedure TEST1 shown in the exhibit is called with the value 'A00' specified for the SOMEID parameter, what is the expected return code?

- A. 0
- B. -1
- C. -2
- D. -3

Answer: A

3. Given the variable declaration shown below:

```
DECLARE v_mytime TIME;
```

Which statement will assign a value to the variable named V_MYTIME?

- A. SET v_mytime = TIME;
- B. VALUES CURRENT TIME INTO v_mytime;
- C. VALUES CURRENT TIMESTAMP INTO v_mytime;
- D. SET v_mytime = DATE;

Answer: B

4. Which steps must be followed to return a result set from an SQL procedure?

- A. 1. Create the procedure using the DYNAMIC RESULT SETS clause.
- 2. Declare the cursor.
- 3. Open the cursor in the SQL procedure.
- 4. Close the cursor.
- 5. Return to the application.

- B. 1. Create the procedure using the DYNAMIC RESULT SETS clause.
- 2. Declare the cursor using the WITH RETURN clause.
- 3. Open the cursor in the SQL procedure.
- 4. Return to the application.
- C. 1. Create the procedure using the WITH RETURN clause.
- 2. Declare the cursor using the DYNAMIC RESULT SETS clause.
- 3. Open the cursor in the SQL procedure.
- 4. Return to the application.
- D. 1. Create the procedure using the WITH RETURN clause.
- 2. Declare the cursor using the DYNAMIC RESULT SETS clause.
- 3. Open the cursor in the SQL procedure.
- 4. Close the cursor.

Answer: B

- 5. Click the Exhibit button.

```
CREATE PROCEDURE testproc( IN i1 INT, INOUT i3 INT)
SPECIFIC testproc
BEGIN
SET i3 = i1;
END
CREATE PROCEDURE testproc( IN i1 INT, INOUT i2 INT, INOUT i3 INT)
SPECIFIC testp
BEGIN
SET i3 = i1 * i2;
END
```

Given that the statements in the exhibits have executed successfully, which solution contains the complete set of commands that could be used to drop both procedures in the order presented?

- A. DROP PROCEDURE testp;
- DROP PROCEDURE testproc;
- B. DROP PROCEDURE testp;
- DROP PROCEDURE testproc;
- C. DROP SPECIFIC PROCEDURE testproc;
- DROP PROCEDURE testproc;
- D. DROP PROCEDURE testproc(INT);
- DROP PROCEDURE testproc(INT);

Answer: C

- 6. What are two valid DECLARE statements in an SQL procedure? (Choose two.)

- A. DECLARE var1 INTEGER;
- B. DECLARE var1 DECIMAL [9];
- C. DECLARE var1 XML;
- D. DECLARE var1 CURRENT DATE;
- E. DECLARE var1[10] INTEGER;

Answer: AC

- 7. Which CREATE PROCEDURE statement option should be used if you plan on issuing a DECLARE GLOBAL TEMPORARY TABLE statement from within the SQL procedure body?

- A. CONTAINS SQL
- B. READS SQL DATA
- C. MODIFIES SQL DATA
- D. LANGUAGE SQL

Answer: C

- 8. Which statement will change the value of a special register?

- A. UPDATE SPECIAL REGISTER TIME = 12:30:00
- B. UPDATE SPECIAL REGISTER SCHEMA = 'DB2ADMIN'
- C. SET CURRENT TIME = 12:30:00
- D. SET CURRENT SCHEMA = 'DB2ADMIN'

Answer: D

- 9. Click the Exhibit button.

```

CREATE FUNCTION sum(a INT, b INT)
RETURNS INTEGER
SPECIFIC sum_of_2
RETURN a + b;
CREATE FUNCTION sum(a INT, b INT, c INT)
RETURNS INTEGER
SPECIFIC sum_of_3
RETURN a + b + c;

```

Given the two functions in the exhibit, what is the correct command to invoke the function which calculates the sum of two numbers from an SQL procedure?

- A. SELECT sum_of_2 FROM table1;
- B. SELECT sum(2,4,?);
- C. SET res_sum = sum(2,6);
- D. CALL sum(?, ?, ?);

Answer: C

10. Which statement will assign the schema names "SYSIBM", "SYSFUN", "SYSPROC", and "SYSIBMADM" to the CURRENT_PATH special register?

- A. SET PATH = SYSTEM PATH
- B. SET CURRENT_PATH = DEFAULT
- C. SET PATH = SYSTEM DEFAULT
- D. RESET CURRENT PATH

Answer: A

11. Given the variable declaration shown below:

```
DECLARE v_mydate DATE;
```

Which statement will assign a value to the variable V_MYDATE?

- A. VALUES CURRENT TIME INTO v_mydate;
- B. VALUES CURRENT TIMESTAMP INTO v_mydate;
- C. SELECT CURRENT TIMESTAMP INTO v_mydate FROM SYSIBM.SYSDUMMY1;
- D. SELECT CURRENT DATE INTO v_mydate FROM SYSIBM.SYSDUMMY1;

Answer: D

12. What are two valid special registers? (Choose two.)

- A. CURRENT_CLIENT_ACCT
- B. CURRENT_SCHEMA
- C. CURRENT_PATH
- D. CURRENT_DATETIME
- E. CURRENT_PARTITION

Answer: BC

13. Which statement can be used to define an array of 30 names that have a maximum size of 25 characters each?

- A. CREATE TYPE names AS VARCHAR(25) ARRAY[30];
- B. CREATE ARRAY names[30] VARCHAR(25);
- C. CREATE TYPE names[30] VARCHAR(25);
- D. CREATE ARRAY names AS VARCHAR(25);

Answer: A

14. Given the statement shown below:

```

SELECT ROW CHANGE TOKEN FOR dept, RID_BIT (dept)
FROM dept WHERE deptno = 'A00' WITH UR

```

Which two statements are true? (Choose two.)

- A. The statement is selecting two columns from DEPT table.
- B. The statement will allow the latest ROW CHANGE TOKEN value to be returned.
- C. The statement will allow the earliest ROW CHANGE TOKEN value to be returned.
- D. The statement will return a TIMESTAMP value.
- E. The statement uses optimistic locking.

Answer: BE

15. Given the SQL statement shown below:

```
DECLARE test CURSOR FOR
```

```
SELECT hiredate
FROM employee
FOR UPDATE;
```

Which statement correctly describes the cursor that is created?

- A. The cursor will be considered a read-only cursor.
- B. The cursor can only be used to perform positioned updates.
- C. The cursor can only be used to perform positioned deletes.
- D. The cursor can be used to perform positioned updates and deletes.

Answer: D

16. What will be the initial value of V_MAX in the declaration statement shown below?

```
DECLARE v_max DECIMAL(9,2);
```

- A. 0.0
- B. 2
- C. 9
- D. NULL

Answer: D

17. Which statement will successfully create an SQL procedure that returns the name of the current month?

```
A. CREATE PROCEDURE proc.current_month(OUT month VARCHAR(20))
```

```
BEGIN
```

```
DECLARE today DATE;
```

```
SET (today = CURRENT_DATE);
```

```
SET month = MONTHNAME(today);
```

```
END
```

```
B. CREATE PROCEDURE proc.current_month(OUT month VARCHAR(20))
```

```
BEGIN
```

```
DECLARE today DATE;
```

```
SELECT (CURRENT_DATE) INTO today;
```

```
SET month = MONTHNAME(today);
```

```
END
```

```
C. CREATE PROCEDURE proc.current_month(OUT month VARCHAR(20))
```

```
BEGIN
```

```
DECLARE today DATE;
```

```
VALUES (CURRENT_DATE) INTO today;
```

```
SET month = MONTHNAME(today);
```

```
END
```

```
D. CREATE PROCEDURE proc.current_month(OUT month VARCHAR(20))
```

```
BEGIN
```

```
SET month = MONTHNAME(SELECT (CURRENT_DATE))
```

```
END
```

Answer: C

18. Which statement can be used to declare a variable inside an SQL procedure that can be used to represent a monetary value?

```
A. DECLARE v_money MONEY;
```

```
B. DECLARE v_money DOUBLE;
```

```
C. DECLARE v_money DECIMAL(9,2);
```

```
D. DECLARE v_money CURRENCY;
```

Answer: C

19. Which statement should be used to declare an array with at most 10 elements of type INTEGER?

```
A. DECLARE sub_total INTEGER[10];
```

```
B. DECLARE sub_total[10] INTEGER;
```

```
C. CREATE TYPE sub_total AS INTEGER[10];
```

```
D. CREATE TYPE sub_total[10] AS INTEGER;
```

Answer: C

20. Given the statements shown below:

```
DECLARE c_dept CURSOR WITH HOLD FOR
```

```
SELECT * FROM dept;
```

OPEN c_dept;

Which two conditions are true? (Choose two.)

- A. C_DEPT will remain open after a ROLLBACK.
- B. C_DEPT will remain open after a COMMIT.
- C. C_DEPT will be returned to the caller of the routine.
- D. C_DEPT will be positioned before the next logical row.
- E. All locks held by C_DEPT will be released after a COMMIT.

Answer: BD

More [000-735 Braindumps](#) Information

Related 000-735 Exams

000-730	000-355	000-731	000-732	000-700
000-735	000-702	000-442	000-513	000-703
000-701	000-516	000-704	000-514	000-706
000-541	000-543			

Other IBM Exams

000-888	000-013	000-792	000-793	000-389
000-550	000-743	LOT-722	000-m27	LOT-841
000-962	000-S02	000-851	000-M07	COG-185
000-741	000-M03	000-466	000-912	000-995