



[Lpi 117-201](#)

Exam Name: Lpi Level 2 Exam 201

Q & A : 118 Q&As

Pdf Demo

Quality and Value for the 117-201 Exam

[Just4Exams Practice Exams](#) for Lpi LPIC Level 2 117-201 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

100% Guarantee to Pass Your 117-201 Exam

If you do not pass the LPIC Level 2 117-201 exam on your first attempt using our Just4Exams **117-201 testing engine and pdf study guide**, we will give you a FULL REFUND of your purchasing fee.

Downloadable, Interactive 117-201 Testing engines and PDF Version

Our Exam Preparation Material provides you everything you will need to take a [LPIC Level 2 certification](#) examination. Details are researched and produced by [Lpi Certification](#) Experts who are constantly using industry experience to produce precise, and logical.

Free 117-201 Exams:

This is demo only, this pdf do not include the questions and answers picture

Exam : Lpi 117-201

Title : LPI Level 2 Exam 201

1. After changing the default runlevel in the init configuration file, the system boots in a different than the intended runlevel. Where else could be this different runlevel be defined?

- A. Nowhere. The init configuration file wasn't properly modified.
- B. In the boot loader configuration file.
- C. In /etc/runlevel under default.
- D. In the initrd image file.
- E. In the /etc/rc.d/rc.local file.

Answer: B

2. One of the IDE hard drives in a server is transferring data very slowly. What command must be run to enable DMA on it?

- A. `hdparm d /dev/hda`
- B. `hdparm dma /dev/hda`
- C. `hdparm dma /dev/hda1`
- D. `hdparm d /dev/hda1`
- E. `hdparm d 1 /dev/hda`

Answer: E

3. Which single parameter, when passed to `nmap`, will instruct `nmap` to perform a fast scan? (Provide only the option)

Answer: -F

4. What information does the file `modules.dep` provide?

- A. A list of all modules available to the kernel.
- B. A list of modules required by each module.
- C. A list of devices and their module name.
- D. A list of all modules compiled for this kernel.
- E. A list of modules the kernel needs to run.

Answer: B

5. To remove the patch `patch2.4.28.tar.bz2` from a kernel source tree, the command that must be used is:

- A. `bunzip2 ../patch2.4.28.tar.bz2 | patch rp1`
- B. `bunzip2 ../patch2.4.28.tar.bz2 | patch Rp1`
- C. `bunzip2 c ../patch2.4.28.tar.bz2 | patch Rp1`
- D. `bunzip2 c ../patch2.4.28.tar.bz2 | patch rp1`
- E. `bunzip2 ../patch2.4.28.tar.bz2 | unpatch p1`

Answer: C

6. What is the command to add another IP address to an interface that already has (at least) one IP address?

- A. `ifconfig eth0:1 192.168.1.2`
- B. `ifconfig eth0 192.168.1.2`
- C. `ipconfig eth0:1 192.168.1.2`
- D. `ipconfig eth0 192.168.1.2`

Answer: A

7. You have configured a workstation to boot in runlevel 4, but you now find that the X server will not start correctly and the machine will not allow local access. What would be the most effective command to run at the LILO prompt to regain local access to the machine, when the last known working kernel image was `linux`?

Answer: `linux 3 linux 1 linux single linux S linux 2`

8. A DNS server has the IP address `192.168.0.1`. Which TWO of the following need to be done on a client machine to use this DNS server?

- A. Add `nameserver 192.168.0.1` to `/etc/resolv.conf`.
- B. Run `route add nameserver 192.168.0.1`.
- C. Run `ifconfig eth0 nameserver 192.168.0.1`.
- D. Ensure that the `dns` service is listed in the hosts entry in the `/etc/nsswitch.conf` file.
- E. Run `bind add nameserver 192.168.0.1`.

Answer: AD

9. What is the minimum number of disks required in a RAID5 array?

- A. 1
- B. 2
- C. 3
- D. 4
- E. 5

Answer: C

10. You are compiling some software from source. After running `./configure` with the appropriate arguments and no errors, what is the next command to run?

Answer: `make make all`

11. Performing a DNS lookup with `dig` results in this answer:

:: QUESTION SECTION:

;5.123.168.192.inaddr.arpa. IN PTR

:: ANSWER SECTION:

5.123.168.192.inaddr.arpa. 600 IN PTR linuxerv.example.net.123.168.192.inaddr.arpa.

:: AUTHORITY SECTION:

123.168.192.inaddr.arpa. 600 IN NS linuxerv.example.net.

:: ADDITIONAL SECTION:

linuxerv.example.net. 600 IN A 192.168.123.5

What might be wrong in the zone definition?

- A. Nothing. All seems to be good.
- B. There's no "." after linuxerv.example.net in the PTR record in the forward lookup zone file.
- C. There's no "." after linuxerv in the PTR record in the forward lookup zone file.
- D. There's no "." after linuxerv.example.net in the PTR record in the reverse lookup zone file.
- E. The "." in the NS definition in reverse lookup zone has to be removed.

Answer: D

12. Your routing configuration relies on eth0 being a 3com card that requires the 3c59x module. What line must be added to modules configuration file, to ensure that eth0 always uses this module?

- A. eth0=3c59x
- B. alias eth0=3c59x
- C. alias eth0 3c59x
- D. set eth0 3c59x
- E. set eth0=3c59x

Answer: C

13. After a crash, the system needs to be booted into runlevel 1. Which option(s) must be typed at the LILO prompt to achieve this, assuming that the working kernel image is called 'linux'?

Answer: linux 1 linux single

14. A zone file on the DNS server has been updated. Which of the following commands will tell named to reload its zone files? (Please select TWO correct answers)

- A. killall HUP named
- B. killall named
- C. rndc reload
- D. rndc flush
- E. namedcheckzone r

Answer: AC

15. Which TWO of the following commands could be used to add a second IP address to eth0?

- A. ifconfig eth0 addip 192.168.123.10
- B. ifconfig eth0:1 192.168.123.10
- C. ifconfig eth01 192.168.123.10
- D. ifconfig eth0 +192.168.123.10
- E. ifconfig eth0:sub1 192.168.123.10

Answer: BE

16. Using only commands included with named, what is the command, with options or parameters, to make named reread its zone files?

Answer: ndc reload /usr/sbin/ndc reload rndc reload /usr/sbin/rndc reload

17. A 2.6.9ac1 kernel would be

- A. an alpha kernel.
- B. someone's patch to a stable kernel.
- C. a stable kernel.
- D. an unstable kernel.
- E. someone's patch to an unstable kernel.

Answer: B

18. If the command arp f is run, which file will be read by default?

- A. /etc/hosts
- B. /etc/ethers
- C. /etc/arp.conf

- D. /etc/networks
- E. /var/cache/arp

Answer: B

19. Your newlycompiled kernel can not find any modules it needs to load. What command was missed when compiling and installing the kernel?

Answer: make modules_install

20. How can the label root be added to the ext2 filesystem on /dev/sda1? Please enter the command with all parameter(s) and/or option(s) below.

Answer: /sbin/tune2fs -L root /dev/sda1 tune2fs -L root /dev/sda1

More [117-201 Braindumps](#) Information

Related 117-201 Exams

117-202 117-201

Other Lpi Exams

117-101 117-201 117-102 117-302 117-202
117-151 117-303 117-301 117-199