



[Oracle 1z0-001](#)

Exam Name: *9i Internet Application Developer Introduction to Oracle: SQL and PL/SQL*

Q & A : 171 Q&As

Pdf Demo

Quality and Value for the 1z0-001 Exam

[Just4Exams Practice Exams](#) for Oracle 9i Internet Application Developer 1z0-001 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

100% Guarantee to Pass Your 1z0-001 Exam

If you do not pass the 9i Internet Application Developer 1z0-001 exam on your first attempt using our Just4Exams **1z0-001 testing engine and pdf study guide**, we will give you a FULL REFUND of your purchasing fee.

Downloadable, Interactive 1z0-001 Testing engines and PDF Version

Our Exam Preparation Material provides you everything you will need to take a [9i Internet Application Developer certification](#) examination. Details are researched and produced by [Oracle Certification](#) Experts who are constantly using industry experience to produce precise, and logical.

Free 1z0-001 Exams:

This is demo only, this pdf do not include the questions and answers picture

Exam : Oracle 1Z0-001

Title : INTRODUCTION TO ORACLE: SQL AND PL/SQL

1. Click on the EXHIBIT button and examine the table instance chart for the patient table.

You need to create the patient_id_seq sequence to be used with the patient table's primary key column. The sequence should begin at 1000, have a maximum value of 999999999, never reuse any numbers, and increment by 1.

Which statement would you use to complete this task?

A. CREATE SEQUENCE patient_id_seq

START WITH 1000

MAXVALUE 999999999

NOCYCLE;

B. CREATE SEQUENCE patient_id_seq
START WITH 1000
MAXVALUE 999999999
STEP BY 1;
C. CREATE SEQUENCE patient_id_seq
ON patient (patient_id)
MINVALUE 1000
MAXVALUE 999999999
INCREMENT BY 1
NOCYCLE;
D. This task cannot be accomplished.

Answer: A

2. Your company wants to give each employee a \$100 salary increment. You need to evaluate the results from the EMP table prior to the actual modification. If you do not want to store the results in the database, which statement is valid?

- A. You need to add a column to the EMP table.
- B. You need to give the arithmetic expression that involves the salary increment in the SET clause of the UPDATE statement.
- C. You need to give the arithmetic expression that involves the salary increment in the SELECT clause of the SELECT statement.
- D. You need to give the arithmetic expression that involves the salary increment in the UPDATE clause of the SELECT statement.
- E. You need to give the arithmetic expression that involves the salary increment in the DISPLAY clause of the SELECT statement.

Answer: C

3. Evaluate this IF statement:

```
IF v_value > 100 THEN  
v_new_value := 2 * v_value;  
ELSIF v_value > 200 THEN  
v_new_value := 3 * v_value;  
ELSIF v_value < 300 THEN  
v_new_value := 4 * v_value;  
ELSE  
v_new_value := 5 * v_value;  
END IF;
```

What would be assigned to V_NEW_VALUE if V_VALUE is 250?

- A. 250
- B. 500
- C. 750
- D. 1000
- E. 1250

Answer: B

4. Which should you do after each FETCH statement in a PL/SQL block?

- A. Open the cursor.
- B. Close the cursor.
- C. Initialize the loop.
- D. Test for rows using a cursor attribute.

Answer: D

5. Examine the declaration section:

```
DECLARE  
CURSOR emp_cursor(p_deptno NUMBER, p_job VARCHAR2)  
IS  
SELECT empno, ename  
FROM emp  
WHERE deptno = p_deptno  
AND job = p_job;  
BEGIN
```

...

Which statement opens this cursor successfully?

- A. OPEN emp_cursor;
- B. OPEN emp_cursor('Clerk', 10);
- C. OPEN emp_cursor(10,'Analyst');

D. OPEN emp_cursor(p_deptno, p_job);

Answer: C

6. The PRODUCT table contains these columns:

ID NUMBER(9) PK

COST NUMBER(7,2)

SALE_PRICE NUMBER(7,2)

Management has asked you to calculate the net revenue per unit for each product if the cost of each product is increased by 10% and the sale price of each product is increased by 25%.

You issue this SQL statement:

```
SELECT id, sale_price * 1.25 - cost * 1.10
```

```
FROM product;
```

Which conclusion can you draw from the results?

A. Only the required results are displayed.

B. The results provide more information than management requested.

C. A function needs to be included in the SELECT statement to achieve the desired results.

D. The order of the operations in the calculation needs to be changed to achieve the required results.

Answer: A

7. Which ALTER command would you use to reinstate a disabled primary key constraint?

A. ALTER TABLE cars

```
ENABLE PRIMARY KEY (id);
```

B. ALTER TABLE cars

```
ENABLE CONSTRAINT cars_id_pk;
```

C. ALTER TABLE cars

```
ENABLE PRIMARY KEY (id) CASCADE;
```

D. ALTER TABLE cars

```
ADD CONSTRAINT cars_id_pk PRIMARY KEY (id);
```

Answer: B

8. Click on the EXHIBIT button and examine the structure of the DEPARTMENT and EMPLOYEE tables.

Evaluate this SQL statement:

```
CREATE INDEX emp_dept_id_idx
```

```
ON employee(dept_id);
```

Which result will the statement provide?

A. Store an index in the EMPLOYEE table.

B. Increase the chance of full table scans.

C. May reduce the amount of disk I/O for SELECT statements.

D. May reduce the amount of disk I/O for INSERT statements.

E. Override the unique index created when the FK relationship was defined.

Answer: C

9. Examine this block of code:

```
SET SERVEROUTPUT ON
```

```
DECLARE
```

```
x NUMBER;
```

```
v_sal NUMBER;
```

```
v_found VARCHAR2(10) := 'TRUE';
```

```
BEGIN
```

```
x := 1;
```

```
v_sal := 1000;
```

```
DECLARE
```

```
v_found VARCHAR2(10);
```

```
y NUMBER;
```

```
BEGIN
```

```
IF (v_sal > 500) THEN
```

```
v_found := 'YES';
```

```
END IF;
```

```
DBMS_OUTPUT.PUT_LINE ('Value of v_found is '|| v_found);
```

```
DBMS_OUTPUT.PUT_LINE ('Value of v_sal is '|| v_sal);
```

```
y := 20;
```

```
END;
DBMS_OUTPUT.PUT_LINE ('Value of v_found is '|| v_found);
DBMS_OUTPUT.PUT_LINE ('Value of Y is '|| TO_CHAR(y));
END;
SET SERVEROUTPUT OFF
```

What is the result of executing this block of code?

A. PLS-00201: identifier 'Y' must be declared

B. Value of v_found is YES

Value of v_sal is 1000

Value of v_found is TRUE

C. Value of v_found is YES

Value of v_sal is 1000

Value of v_found is YES

Value of Y is 20

D. PLS-00201: identifier 'v_sal' must be declared

PLS-00201: identifier 'Y' must be declared

E. Value of v_found is YES

Value of v_sal is 1000

Value of v_found is TRUE

Value of Y is 20

Answer: A

10. You need to perform a major update on the EMPLOYEE table. You have decided to disable the PRIMARY KEY constraint on the empid column and the CHECK constraint on the job column.

What happens when you try to enable the constraints after the update is completed?

A. You need to recreate the constraints once they are disabled.

B. Any existing rows that do not confirm with the constraints are automatically deleted.

C. Only the future values are verified to confirm with the constraints, leaving the existing values unchecked.

D. The indexes on both the columns with the PRIMARY KEY constraint and the CHECK constraint are automatically re-created.

E. All the existing column values are verified to confirm with the constraints and an error message is generated if any existing values do not confirm.

Answer: E

11. Which statement is valid within the executable section of a PL/SQL block?

A. BEGIN

```
emp_rec emp%ROWTYPE;
```

```
END;
```

B. WHEN NO_DATA_FOUND THEN

```
DBMS_OUTPUT.PUT_LINE ('No records found');
```

C. SELECT ename, sal

```
INTO v_ename, v_sal
```

```
FROM emp
```

```
WHERE empno = 101;
```

D. PROCEDURE calc_max (n1 NUMBER, n2 NUMBER, p_max OUT NUMBER) IS

```
BEGIN
```

```
IF n1 > n2 THEN
```

```
p_max := n1;
```

```
ELSE
```

```
p_max := n2;
```

```
END;
```

Answer: C

12. You want to display the average salary for departments 20 and 50, but only if those departments have an average salary of at least 2000. Which statement will produce the required results?

A. SELECT deptno, AVG(sal)

```
FROM emp
```

```
WHERE deptno IN (20, 50)
```

```
GROUP BY deptno
```

```
HAVING AVG(sal) >= 2000;
```

B. SELECT deptno, AVG(sal)

```
FROM emp
```

```

GROUP BY deptno
HAVING AVG(sal) >= 2000
AND deptno IN (20, 50);
C. SELECT deptno, AVG(sal)
FROM emp
WHERE deptno IN (20, 50)
AND AVG(sal) >= 2000
GROUP BY deptno;
D. SELECT deptno, AVG(sal)
FROM emp
WHERE deptno IN (20, 50)
GROUP BY AVG(sal)
HAVING AVG(sal) >= 2000;
Answer: A

```

13. The structure of the DEPT table is as follows:

Name Null? Type

```

-----
DEPTNO NOT NULL NUMBER(2)
DNAME VARCHAR2(14)
LOC VARCHAR2(13)

```

Examine the code:

```

DECLARE
TYPE dept_record_type IS RECORD
(dno NUMBER,
name VARCHAR2(20));
dept_rec dept_record_type;
BEGIN
SELECT deptno, dname
INTO dept_rec
FROM dept
WHERE deptno = 10;
END;

```

Which statement displays the name of the selected department?

- A. DBMS_OUTPUT.PUT_LINE(name);
- B. DBMS_OUTPUT.PUT_LINE(dname);
- C. DBMS_OUTPUT.PUT_LINE(dept_rec.name);
- D. DBMS_OUTPUT.PUT_LINE(dept_rec.dname);
- E. DBMS_OUTPUT.PUT_LINE(dept_rec(name));

Answer: C

14. Examine this block of code:

```

SET SERVEROUTPUT ON
DECLARE
x NUMBER;
v_sal NUMBER;
v_found VARCHAR2(10) := 'TRUE';
BEGIN
x := 1;
v_sal := 1000;
DECLARE
v_found VARCHAR2(10);
y NUMBER;
BEGIN
IF (v_sal > 500) THEN
v_found := 'YES';
END IF;
DBMS_OUTPUT.PUT_LINE ('Value of v_found is '|| v_found);
DBMS_OUTPUT.PUT_LINE ('Value of v_sal is '|| v_sal);
y := 20;
END;

```

```
DBMS_OUTPUT.PUT_LINE ('Value of v_found is '|| v_found);
DBMS_OUTPUT.PUT_LINE ('Value of Y is '|| TO_CHAR(y));
END;
SET SERVEROUTPUT OFF
```

Why does this code produce an error when executed?

- A. The value of V_FOUND cannot be 'YES'.
- B. Variable V_FOUND is declared at more than one location.
- C. Variable Y is declared in the inner block and referenced in the outer block.
- D. Variable V_SAL is declared in the outer block and referenced in the inner block.

Answer: C

15. Click on the EXHIBIT button and examine the table instance chart for the cars table.

You query the database with this command:

```
SELECT lot_no "Lot Number", COUNT(*) "Number of Cars Available"
FROM cars
WHERE model = 'Fire'
GROUP BY lot_no
HAVING COUNT(*) > 10
ORDER BY COUNT(*);
```

Which clause restricts which groups are displayed?

- A. SELECT lot_no "Lot Number", COUNT(*) "Number of Cars Available"
- B. WHERE model = 'Fire'
- C. HAVING COUNT(*) > 10
- D. GROUP BY lot_no
- E. ORDER BY COUNT(*)

Answer: C

16. Click on the EXHIBIT button and examine the table instance chart for the cars table.

Which SELECT statement will display style, color, and lot number for all cars based on the model entered at the prompt, regardless of case?

- A. SELECT style, color, lot_no
FROM cars
WHERE model = UPPER('&model');
- B. SELECT style, color, lot_no
FROM cars
WHERE model = '&model';
- C. SELECT style, color, lot_no
FROM cars
WHERE UPPER(model) = UPPER('&model');
- D. SELECT style, color, lot_no
FROM cars
WHERE UPPER(model) = '&model';

Answer: C

17. Given this executable section of a PL/SQL block:

```
BEGIN
FOR employee_record IN salary_cursor LOOP
employee_id_table(employee_id) :=
employee_record.last_name;
END LOOP;
CLOSE salary_cursor;
END;
```

Why does this section cause an error?

- A. The cursor needs to be opened.
- B. No FETCH statements were issued.
- C. Terminating conditions are missing.
- D. The cursor does not need to be closed.

Answer: D

18. The EMPLOYEE table contains these columns:

```
BONUSNUMBER(7,2)
```

DEPT_ID NUMBER(9)

There are 10 departments and each department has at least 1 employee. Bonus values are greater than 500; not all employees receive a bonus.

Evaluate this PL/SQL block:

DECLARE

v_bonusemployee.bonus%TYPE := 300;

BEGIN

UPDATE employee

SET bonus = bonus + v_bonus

WHERE dept_id IN (10, 20, 30);

COMMIT;

END;

What will be the result?

- A. All employees will be given a 300 bonus.
- B. A subset of employees will be given a 300 bonus.
- C. All employees will be given a 300 increase in bonus.
- D. A subset of employees will be given a 300 increase in bonus.

Answer: D

19. You need to execute a script file named QUERYEMP.SQL from your SQL*Plus environment. Which command do you use?

- A. RUN QUERYEMP
- B. GET QUERYEMP
- C. START QUERYEMP
- D. EXECUTE QUERYEMP

Answer: C

20. You issue this command:

CREATE SYNONYM emp

FOR ed.employee;

Which task has been accomplished?

- A. The need to qualify an object name with its schema was eliminated for user Ed.
- B. The need to qualify an object name with its schema was eliminated for only you.
- C. The need to qualify an object name with its schema was eliminated for all users.
- D. The need to qualify an object name with its schema was eliminated for users with access.

Answer: B

More [1z0-001 Braindumps](#) Information

Related 1z0-001 Exams

1z0-147	1z0-001	1z0-141	1z0-101	1z0-132
1z0-140	1z0-131			

Other Oracle Exams

1z0-271	1Z0-200	1Z1-225	1Z0-043	1z0-235
1Z0-517	1z0-213	1z1-051	1z0-141	1z0-263
1Z1-241	1Z0-207	1z0-257	1z0-054	1z0-032
1Z0-146	1Z0-520	1z0-238	1z0-120	1z0-630