



SUN 310-220

Exam Name: Sun Certified Developer for Java Web Services

Q & A : 250 Q&As

Pdf Demo

Quality and Value for the 310-220 Exam

[Just4Exams Practice Exams](#) for SUN SCDJWS 310-220 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

100% Guarantee to Pass Your 310-220 Exam

If you do not pass the SCDJWS 310-220 exam on your first attempt using our Just4Exams **310-220 testing engine and pdf study guide**, we will give you a FULL REFUND of your purchasing fee.

Downloadable, Interactive 310-220 Testing engines and PDF Version

Our Exam Preparation Material provides you everything you will need to take a [SCDJWS certification](#) examination. Details are researched and produced by [SUN Certification](#) Experts who are constantly using industry experience to produce precise, and logical.

Free 310-220 Exams:

This is demo only, this pdf do not include the questions and answers picture

Exam : SUN 310-220

Title : Sun Certified Developer for Java Web Services

1. Given:

```
<Schema targetNamespace="http://sun.cert/types"
xmlns:ns0="http://www.w3.org/2001/XMLSchema"
xmlns="http://www.w3.org/2001/XMLSchema"
xmlns:xsd="http://sun.cert/xsdTypes"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
<complexType name="Foo">
<sequence>
<!-- insert code here -->
```

```
</sequence>
</complexType>
</schema>
```

Assuming that no other namespace declarations exist, which two elements use the long type that is defined in the <http://www.w3.org/2001/XMLSchema> namespace? (Choose two.)

- A. <element name="length" type="long"/>
- B. <element name="length" type="xsi:long"/>
- C. <element name="length" type="xsd:long"/>
- D. <element name="length" type="ns0:long"/>

Answer: AD

2. In addition to SAX2 and DOM Level 2, which is supported by JAXP 1.2?

- A. XSLT
- B. JAXB
- C. SAAJ
- D. JDBC

Answer: A

3. Given:

```
11: public BulkResponse findCallerAssociations(
12: Collection findQualifiers,
13: Boolean confirmedByCaller,
14: Boolean confirmedByOtherParty,
15: Collection associationTypes);
...
36: BusinessQueryManager queryMngr =
37: registry.getBusinessQueryManager();
38: BulkResponse response =
39: queryMngr.findCallerAssociations(null,
40: Boolean.TRUE, Boolean.FALSE, null);
```

A developer has established a JAXR connection to a UDDI registry. The developer executes the findCallerAssociations method that is defined in lines 11-15. The context for the method invocation is shown in lines 36-40. The invocation on line 39-40 will return a BulkResponse object.

Which is true about the BulkResponse object?

- A. It contains a Collection of Association objects that the other party has confirmed with the caller.
- B. It contains a Collection of Organization objects that have confirmed the associations with the caller.
- C. It contains a Collection of Association objects that the other party has NOT yet confirmed with the caller.
- D. It contains a Collection of Key objects representing UUID keys for organizations that have confirmed the associations with the caller.

Answer: C

4. Given:

```
<xsd:schema targetNamespace="http://sun.cert/types"
xmlns:suncert="http://sun.cert/types">
<xsd:element name="fooElement" type="suncert:Foo"/>
<xsd:complexType name="Foo">
<xsd:sequence>
<xsd:element name="age" type="xsd:long"/>
<xsd:element name="last" type="xsd:string"/>
<xsd:element name="first" type="xsd:string"
nillable="true"/>
</xsd:sequence>
</xsd:complexType>
</xsd:schema>
```

Which two instances of a fooElement are valid? (Choose two.)

- A. <fooElement>
<last>Duke</last>
<first xsi:nil="1"/>
</fooElement>
- B. <fooElement>
<age>33</age>
<last>Duke</last>

```
<first>Monty</first>
</fooElement>
```

C. <fooElement>
<age>33</age>
<last>Duke</last>
<first xsi:nil="1"/>
</fooElement>

D. <fooElement>
<age>33</age>
<last xsi:nil="1"/>
<first>Monty</first>
</fooElement>

E. <fooElement>
<age>33</age>
<last>Duke</last>
<first xsi:nil="1">Monty</first>
</fooElement>

Answer: BC

5. A developer in a business-to-business environment is required to build a Web service client that can be strongly authenticated by a Web service.

What must the developer do to create the client?

- A. use role-based security
- B. implement form-based security
- C. implement basic authentication
- D. provide a digital certificate that is signed by a Certificate Authority

Answer: D

6. Given:

```
<schema targetNamespace="http://sun.cert/types"
xmlns:sun="http://sun.cert/types"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
elementFormDefault="qualified">
<xsd:element name="Person" type="sun:PersonType"/>
<xsd:complexType name="PersonType">
<xsd:sequence>
<xsd:element name="first" type="xsd:string"/>
<xsd:element name="last" type="xsd:string"/>
</xsd:sequence>
</xsd:complexType>
</schema>
```

Assume all XML fragments are well-formed.

Which two instances of Person are correct? (Choose two.)

A. <Person>
<first>Monty</first>
<last>Duke</last>
</Person>

B. <t:Person xmlns:t="http://sun.cert/types">
<first>Monty</first>
<last>Duke</last>
</t:Person>

C. <t:Person xmlns:t="http://sun.cert/types">
<t:first>Monty</t:first>
<t:last>Duke</t:last>
</t:Person>

D. <p:Person xmlns:p="http://sun.cert/types">
<f:first xmlns:f="http://sun.cert/types">Monty</f:first>
<f:last>Duke</f:last>
</p:Person>

Answer: CD

7. A stateful Web service is implemented as an EJB based endpoint.

What are two ways to maintain that state? (Choose two.)

- A. by using URL re-writing
- B. by adding a session cookie to the HTTP headers
- C. by adding a conversation id to the SOAP headers
- D. by requiring clients to send a client id parameter to all methods

Answer: CD

8. Which two are commonly used as SOAP headers? (Choose two.)

- A. security information
- B. transaction information
- C. postal address information
- D. stock quote request information

Answer: AB

9. According to the WS-I Basic Profile 1.0a, a conformant WSDL 1.1 portType definition is allowed to use two type operations (that is, Message-Exchange Patterns).

Which two are allowed? (Choose two.)

- A. one-way
- B. notification
- C. solicit-response
- D. request-response

Answer: AD

10. Given:

```
<types>
<schema targetNamespace="http://sun.cert/types"
xmlns:tns="http://sun.cert/types"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
<xsd:complexType name="Person">
<xsd:all>
<!-- insert code here -->
</xsd:all>
</xsd:complexType>
</schema>
</types>
```

Which two element definitions, when inserted into the given schema fragment, result in a correct schema type definition? (Choose two.)

- A. <xsd:element name="first" type="xsd:string"/>
- B. <xsd:element name="items" type="xsd:long" maxOccurs="5"/>
- C. <xsd:element name="last" type="xsd:string" minOccurs="1" maxOccurs="1"/>
- D. <xsd:element name="first" type="xsd:string" minOccurs="0" maxOccurs="5"/>

Answer: AC

11. Given the type declaration in a WSDL description for a Web service:

```
<element name="PurchaseOrder">
<complexType>
<sequence>
<any maxOccurs="1"/>
</sequence>
</complexType>
</element>
```

The Java code generated by a JAX-RPC service endpoint interface consists of a PurchaseOrder JavaBean.

Which property should the PurchaseOrder JavaBean contain?

- A. _any of type java.lang.String
- B. PurchaseOrder of type java.lang.Object
- C. complexType of type java.lang.Object[]
- D. _any of type javax.xml.soap.SOAPElement

Answer: D

12. Given:

```
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/"
```

```

xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:ns1="http://sun.cert/">
<s:Header>
<ns1:transaction>
<user>root</user>
<transid>9b3e64e326537b4e8c0ff19e953f9673</transid>
</ns1:transaction>
</s:Header>
<s:Body>
<m:StockQuote xmlns:m="http://sun.cert/bar/">
<Quote>
<ns1:symbol>SUNW</ns1:symbol>
<ns1:companyname name="Sun"/>
</Quote>
</s:Body>
</s:Envelope>

```

Which describes this SOAP message?

- A. It is NOT well-formed.
- B. It contains a mandatory header block.
- C. It is WS-I Basic Profile 1.0a compliant.
- D. It does NOT contain the correct namespace declarations.

Answer: A

13. Which SAAJ 1.2 type is used to represent SOAP message header blocks?

- A. org.omg.dom.Document
- B. javax.xml.soap.SOAPPart
- C. javax.xml.soap.DetailEntry
- D. javax.xml.soap.SOAPHeaderElement

Answer: D

14. Where is the Kerberos ticket embedded in a SOAP header processed?

- A. Web service interaction layer
- B. Web service processing layer
- C. Web service interaction and processing layers
- D. It is an HTML issue and it is NOT related to Web services.

Answer: A

15. Given:

```

<service name="InventoryServices">
<port name="PurchaseOrder" binding="tns:POBinding">
<soap:address location="http://192.168.0.2:8080/inventory"/>
</port>
<port name="Invoice" binding="tns:InvoiceBinding">
<soap:address location="http://192.168.0.2:8080/inventory"/>
</port>
</service>

```

Which describes this WSDL extract?

- A. The extract is WS-I Basic Profile 1.0a compliant because both port element names are different.
- B. The extract is NOT WS-I Basic Profile 1.0a compliant because both port elements point to the same location.
- C. The extract is WS-I Basic Profile 1.0a compliant because both port elements point to different binding elements.
- D. The extract is NOT WS-I Basic Profile 1.0a compliant because it contains two port elements in the same service.

Answer: B

16. A developer uses the delete_tModel function to delete five tModels. Which two describe the behavior of the system after the delete_tModel is executed? (Choose two.)

- A. The delete_tModel logically deletes the tModels .
- B. The tModels cannot be accessed since they are permanently deleted.
- C. The deleted tModels still appear in the results returned by find_tModel.
- D. The deleted tModels are omitted from any results returned by find_tModel.

Answer: AD

17. A developer is writing a request-response Web service. An error occurs when the service executes.

Which is true about the Body element of the SOAP reply message?

- A. It must NOT contain any fault elements.
- B. It must contain zero or one fault element.
- C. It must contain an array of fault elements.
- D. It can contain as many fault elements as it needs.

Answer: B

18. Given:

```
<schema targetNamespace="http://sun.cert/types"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
xmlns:wSDL="http://schemas.xmlsoap.org/wSDL">
<!-- insert code here -->
</schema>
```

Assume all XML fragments are well-formed.

According to the WS-I Basic Profile 1.0a, which type definition can be used to define an array of longs?

- A. `<xsd:complexType name="longArray">`
`<xsd:array>`
`<xsd:element name="item" type="xsd:long"/>`
`</xsd:array>`
`</xsd:complexType>`
- B. `<xsd:complexType name="longArray">`
`<xsd:sequence>`
`<element name="item" type="xsd:long"/>`
`</xsd:sequence>`
`</xsd:complexType>`
- C. `<xsd:complexType name="longArray">`
`<xsd:array>`
`<xsd:element name="item" type="xsd:long" minOccurs="0"`
`maxOccurs="unbounded"/>`
`</xsd:array>`
`</xsd:complexType>`
- D. `<xsd:complexType name="longArray">`
`<xsd:sequence>`
`<xsd:element name="item" minOccurs="0" maxOccurs="5"`
`type="xsd:long"/>`
`</xsd:sequence>`
`</xsd:complexType>`

Answer: D

19. According to the JAX-RPC 1.1 XML-to-Java mappings, which three elements or attribute declarations are mapped to a Java primitive wrapper class (for example, java.lang.Short)? (Choose three.)

- A. `<xsd:element name="age" type="xsd:short" minOccurs="0"/>`
- B. `<xsd:element name="age" type="xsd:short" nillable="true"/>`
- C. `<xsd:element name="age" type="xsd:short" nillable="false"/>`
- D. `<xsd:attribute name="required" type="xsd:boolean" use="optional"/>`
- E. `<xsd:attribute name="required" type="xsd:boolean" use="required"/>`

Answer: ABD

20. Which Java type can be used to represent arbitrary XML data in a JAX-RPC service endpoint interface?

- A. org.w3c.dom.Document
- B. javax.xml.soap.SOAPPart
- C. javax.xml.soap.SOAPElement
- D. javax.xml.soap.SOAPException

Answer: C

More [310-220 Braindumps](#) Information

310-220

310-600	310-	310-065	310-812	212-302
	055Big5	310-014	310-092	310-878
310-019	310-082	310-110	310-015	412-600
310-540	310-231	310-011	310-630	310-056
310-084	212-083			