



Cisco 350-027

Exam Name: CCIE Written: Metro Ethernet

Q & A : 400 Q&As

Pdf Demo

Quality and Value for the 350-027 Exam

[Just4Exams Practice Exams](#) for Cisco CCIE 350-027 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

100% Guarantee to Pass Your 350-027 Exam

If you do not pass the CCIE 350-027 exam on your first attempt using our Just4Exams **350-027 testing engine and pdf study guide**, we will give you a FULL REFUND of your purchasing fee.

Downloadable, Interactive 350-027 Testing engines and PDF Version

Our Exam Preparation Material provides you everything you will need to take a [CCIE certification](#) examination. Details are researched and produced by [Cisco Certification](#) Experts who are constantly using industry experience to produce precise, and logical.

Free 350-027 Exams:

This is demo only, this pdf do not include the questions and answers picture

Exam : Cisco 350-027

Title : CCIE Written: Metro Ethernet

1. What technology allows transporting Layer2 attachment circuits over IP-only backbones?

- A. GRE
- B. AToM
- C. L2TPv3
- D. DLSW+

Answer: C

2. What protocol is not disabled by the 'no service tcp-small-servers' command?

- A. Echo

- B. Finger
- C. Chargen
- D. Discard
- E. Daytime

Answer: B

3. Click the Exhibit button. PE1 and PE2 are connected to the MPLS cloud. All MPLS labels from PE1 and PE2 are working. Observing the shown topology, will this scenario work?

- A. This scenario will not work because Gigabit Ethernet can't be connected to FastEthernet over MPLS.
- B. This scenario will work because the issues concerning Gigabit and FastEthernet over MPLS with default behavior should not make any difference.
- C. This scenario will not work because Gigabit usually has MTU over 9000 and FastEthernet 1500.
- D. This scenario will not work because one side has dot1q header and another side is in port mode.
- E. This scenario will work by configuring PWE Class using the Interworking feature. By default, the MTU on each side is 1500, so this is an acceptable solution.

Answer: E

4. What Q.931 message cannot be received in response to sending a Q.931 SETUP message?

- A. Alerting
- B. Call Proceeding
- C. Connect
- D. USER Information
- E. Progress

Answer: D

5. How many bits does TCI contain?

- A. 1
- B. 3
- C. 6
- D. 12
- E. 16
- F. 20

Answer: E

6. EIGRP applies the principle of Feasible Successor (FS) in resolving a new path to a lost route. What statement regarding the FS is correct?

- A. Information is stored for the FS as part of the Link-State Routing updates forwarded for EIGRP.
- B. EIGRP estimates the FS from each neighbor for each network after an exchange of database information during the normal update process. It uses this information for path selection when a route is lost.
- C. When EIGRP is notified that a route is lost, it will always send requests to each neighbor for ways to reach the lost route. The neighbor that returns the best path will qualify as the FS.
- D. EIGRP nominates a central router as the FS for all lost routes during configuration.

Answer: B

7. Which commands are valid in ethernet or ethernet VLAN attachment circuits?

- A. match cos
- B. match ethernet cos
- C. match source-mac
- D. match vlan
- E. match ethernet multicast

Answer: AD

8. What specification defines LACP?

- A. IEEE 802.11
- B. IEEE 802.1q and IEEE 802.1p
- C. IEEE 802.3ad
- D. ITU Q.922
- E. RFC2547

Answer: C

9. The Hold-Down Timer used in Distance Vector protocols:

- A. Sets the time limit of how long a router may keep a packet in its buffer, if the routing protocol is in the process of converging
- B. Determines the number of seconds a router will wait before sending another update to neighbor routers
- C. Sets a specific period for routers to neither accept nor advertise a route from a destination where an original route was recently lost
- D. Sets a duration where routes are not accepted from the neighbor router that caused a routing loop

Answer: C

10. What command is used for Interworking configuration?

- A. `interworking {etherner | ip} in interface config mode.
- B. `interworking {etherner | ip} in pseudowire-class config mode.
- C. `Interworking {bridged | routed} in l2tp-class mode.
- D. `{ip | ethernet}Interworking in pseudowire-class config mode.

Answer: B

11. A router is set to boot from flash, but cannot find boot commands in the configuration. Also, valid files do not exist in the default flash device. The router will:

- A. Boot from ROM, since there are no valid sources
- B. Try to boot from the network, using a default filename
- C. Terminate the boot process with an error message
- D. Try to boot from the network, then boot from ROM as a backup

Answer: D

12. Which statements are true regarding VPLS?

- A. There is a full mesh of pseudowires.
- B. There is a partial mesh of pseudowires.
- C. Only L2TPv3 can be used for pseudowire establishment.
- D. STP runs in the core.
- E. There is split-horizon to avoid loops.

Answer: AE

13. Which are components of VPLS?

- A. BGP extensions
- B. Pseudowire technology
- C. LDP extensions
- D. Etherchannel technology
- E. MAC Address learning and forwarding on a virtual port

Answer: ABE

14. What IE is not mandatory in a Q.931 Service msg?

- A. Bearer capability
- B. Channel ID
- C. Message Type
- D. Change Status
- E. Call Reference

Answer: A

15. OSPF is defined on a Frame Relay interface providing point-to-multipoint connections. The remote neighbors can reach this central site, but are complaining of routing failures between each of the remote sites. The central router has all the routes for each remote site. Based on this information, what can be diagnosed as the biggest potential problem?

- A. An over-subscribed Frame Relay switch will cause some packet loss.
- B. There are problems in the use of OSPF Authentication.
- C. There is an incorrect selection of the Designated Router.
- D. There is an incorrect DLCI assigned on a point-to-point sub-interface.

Answer: C

16. Which are supported ways of transporting ATM over MPLS?

- A. AAL5 SDU VC Mode
- B. AAL5 SDU VP Mode
- C. Packet Cell Relay AAL5 Trunk Mode
- D. Packed Cell Relay Trunk mode
- E. AAL2oMPLS

Answer: AC

17. What kind of packet is being decoded, using the captured debug mpls l2transport packet data command, below?

- A. HDLC
- B. PPP
- C. Ethernet
- D. RFC 2427/RFC1490

Answer: D

18. Which do NOT exist?

- A. Per VLAN Spanning Tree (PVST).
- B. Per VLAN Spanning Tree Plus (PVST+).
- C. Per VLAN Spanning Tree Plus Plus (PVST++).
- D. Rapid STP (RSTP).
- E. Resilient STP (RSTP).

Answer: CE

19. Click the Exhibit button to view the topology. According to the diagram, what attribute is initiated by AS200 (IBGP) to give preference to the path A or D traffic will take when going from AS200 to AS100? What attribute is initiated by AS200 (EBGP) to give preference to the path B or C traffic will take when going from AS100 to AS200?

- A. MED; Origin
- B. MED; Local Preference
- C. Community; Origin
- D. Local Preference; MED
- E. Origin; Community

Answer: D

20. Estimating the MTU for EoMPLS Packets Edge MTU of 1500, Transport header, AToM header present, MPLS label, and stack MPLS Label, calculate the core MTU requirements to handle EoMPLS port mode packets.

- A. 1518
- B. 1520
- C. 1524
- D. 1526

Answer: D

More [350-027 Braindumps](#) Information

Related 350-027 Exams

350-001	350-018	350-030	350-001- LAB	350-029 351-001
350-018- LAB	350-040	350-022	350-024	350-050
350-021	350-020	350-027	350-025	351-018
	350-026	350-023	350- 001GB2312- LAB	

Other Cisco Exams

646-229	642-181	640-863	646-362	642-145
642-066	646-361	642-356	640-553	646-222
646-561	642-342	642-415	642-831	642-873
350-029	642-524	642-587	642-112	642-591