



[Cisco 640-863](#)

Exam Name: *Designing for Cisco Internetwork Solutions*

Q & A : 128 Q&As

Pdf Demo

Quality and Value for the 640-863 Exam

[Just4Exams Practice Exams](#) for Cisco CCDA 640-863 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

100% Guarantee to Pass Your 640-863 Exam

If you do not pass the CCDA 640-863 exam on your first attempt using our Just4Exams **640-863 testing engine and pdf study guide**, we will give you a FULL REFUND of your purchasing fee.

Downloadable, Interactive 640-863 Testing engines and PDF Version

Our Exam Preparation Material provides you everything you will need to take a [CCDA certification](#) examination. Details are researched and produced by [Cisco Certification](#) Experts who are constantly using industry experience to produce precise, and logical.

Free 640-863 Exams:

This is demo only, this pdf do not include the questions and answers picture

Exam : Cisco 640-863

Title : Designing for Cisco Internetwork Solutions

1. Which two statements about designing the Enterprise Data Center Access submodule are correct? (Choose two.)

- A. Multiport NIC servers should each have their own IP address.
- B. Layer 3 connectivity should never be used in the access layer.
- C. Layer 2 connectivity is primarily implemented in the access layer.
- D. Multiport NIC servers should never be used in the access layer.
- E. Layer 2 clustering implementation requires servers to be Layer 2 adjacent.

Answer: CE

2. Which three of these are components of the North American Numbering Plan? (Choose three.)

- A. Numbering Plan Area
 - B. country code
 - C. prefix
 - D. zone
 - E. line number
 - F. trunk channel
- Answer: ACE

3. Which two implementation plan principles best describe how to deal with potential failures?(Choose two.)

- A. A good implementation plan.
- B. A successful test network test.
- C. A test should be included at every step.
- D. A detailed rollback procedure for each implementation step.
- E. A table of failure points, rollback steps, and estimated rollback times.

Answer: CD

4. Which three of these describe the best practice for Cisco wireless outdoor Mesh network deployment? (Choose three.)

- A. RAP implemented with 20 to 32 MAP nodes
- B. RAP implemented with 20 or fewer MAP nodes
- C. mesh hop counts of 8 to 4
- D. mesh hop counts of 4 or fewer
- E. client access via 802.11b/g and backhaul with 802.11a
- F. client access via 802.11a and backhaul with 802.11b/g

Answer: BDE

5. Which statement can a network designer use to describe route summarization to an IT manager?

- A. It is the grouping of multiple contiguous subnets into one Class A, B, or C IP address to minimize routing table size.
- B. It is the grouping of multiple discontinuous subnets to increase routing performance.
- C. It is the grouping of multiple contiguous networks and advertising as one large network.
- D. It is the grouping of ISP network addresses to minimize the number of routes to the Internet.

Answer: C

6. Refer to the exhibit.

A standard, Layer 2 campus network design is pictured. Which numbered box represents the distribution layer?

- A. #1
- B. #2
- C. #3
- D. #4

Answer: B

7. Which two of the following statements represent a preferred wireless LWAPP implementation?(Choose two.)

- A. verify open ports for:
Layer 2 LWAPP on ethertype OxABAB
Layer 3 LWAPP on TCP 12222 and TCP 12223
- B. verify open ports for:
Layer 2 LWAPP on ethertype OxBBBB
Layer 3 LWAPP on UDP 12222 and UDP 12223
- C. verify open ports for:
Layer 2 LWAPP on ethertype OxBABA
Layer 3 LWAPP on UDP 12222 and TCP 12223
- D. use of Layer 3 LWAPP is preferred over Layer 2 LWAPP
- E. use of Layer 2 LWAPP is preferred over Layer 3 LWAPP

Answer: BD

8. Which statement identifies a benefit obtained when using a top-down network design plan?

- A. allows quick responses to design requests
- B. facilitates design based on previous experience
- C. incorporates customer organizational requirements
- D. is less time-consuming than using a bottom-up approach
- E. provides a more detailed picture of the desired network

Answer: C

9. Lightweight access points are being deployed in remote locations where others are already operational.

The new access points are in a separate IP subnet from the wireless controller. OTAP has not been enabled at any locations.

Which two methods can the AP use to locate a wireless controller? (Choose two.)

- A. local subnet broadcast
- B. NV-RAM IP address
- C. DHCP
- D. primary, secondary, tertiary
- E. DNS
- F. master

Answer: CE

10. A lightweight access point is added to a working network. Which sequence will it use to associate itself with a wireless LAN controller?

- A. master, primary, secondary, tertiary, greatest AP capacity
- B. greatest AP capacity, primary, secondary, tertiary, master
- C. primary, secondary, tertiary, master, greatest AP capacity
- D. primary, secondary, tertiary, greatest AP capacity, master

Answer: C

11. Which of these is the equation used to derive a 64 Kbps bit rate?

- A. $2 \times 8 \text{ kHz} \times 4\text{-bit code words}$
- B. $8 \text{ kHz} \times 8\text{-bit code words}$
- C. $2 \times 4\text{-bit code words} \times 8 \text{ kHz}$
- D. $2 \times 4 \text{ kHz} \times 8\text{-bit code words}$

Answer: D

12. A very large organization has received its IPv6 address range from its Internet Service Provider and intends to use only IPv6 addresses internally. Employees will access the Internet using port address translation. What is a requirement for their DNS servers?

- A. They no longer need DNS servers.
- B. Their DNS servers need to support both IPv4 and IPv6 addresses.
- C. Their DNS servers need to support only IPv6 addresses.
- D. Their DNS servers need to support only IPv4 addresses.
- E. They need additional DNS servers in their network just for IPv6 addresses.
- F. There are no changes required to their DNS servers.

Answer: B

13. Which two statements best describe intradomain route summarization? (Choose two.)

- A. OSPF and RIP automatically summarize at classful network boundaries.
- B. EIGRP and OSPF automatically summarize at classful network boundaries.
- C. EIGRP and RIP automatically summarize at classful network boundaries.
- D. EIGRP and OSPF must be manually configured to summarize at non-classful boundaries.
- E. EIGRP and OSPF automatically summarize at non-classful boundaries.

Answer: CD

14. Data link switching is typically used in which Enterprise Campus Module layer?

- A. Server Farm
- B. Campus Core
- C. Building Access
- D. Building Distribution
- E. Internet Connectivity

Answer: C

15. Which two of these are functions of an access point in a Split MAC Network Architecture?(Choose two.)

- A. EAP Authentication
- B. MAC layer encryption or decryption
- C. 802.1Q encapsulation
- D. Process probe response

Answer: BD

16. In the Cisco branch office design, what categorizes an office as large?

- A. between 50 and 100 users and a three-tier design
- B. between 50 and 100 users and a single-tier design
- C. between 100 and 200 users and a two-tier design
- D. between 100 and 200 users and a three-tier design
- E. over 200 users and a two-tier design

Answer: D

17. Which transmission medium should you recommend to this customer?

- A. shielded twisted pair
- B. unshielded twisted pair
- C. multimode fiber
- D. single-mode fiber
- E. wireless

Answer: D

18. Which Cisco security solution offers protection against "day zero" attacks?

- A. Cisco Adaptive Security Appliance
- B. Cisco Security Agent
- C. Cisco IOS Firewall
- D. Cisco IOS IPS
- E. Cisco Traffic Anomaly Detector

Answer: B

19. Refer to the exhibit.

Which layer is the distribution layer?

- A. Layer A
- B. Layer B
- C. Layer C
- D. Layers A and B form a consolidated core and distribution layer

Answer: B

20. Which statement accurately describes one difference between a small office and medium office topology?

- A. Small offices commonly use Rapid PVST+ for Layer 3 deployments.
- B. Medium offices commonly use integrated route and switching platforms.
- C. Medium offices use integrated 10/100/1000 interfaces as Layer 2 trunks.
- D. Medium offices use external access switches to support LAN connectivity.

Answer: D

More [640-863 Braindumps](#) Information

Related 640-863 Exams

640-863 640-861

Other Cisco Exams

642-061	642-813	640-861	646-203	642-741
642-521	642-961	640-460	642-736	646-003
350-018-	646-393	642-892	642-062	642-444
LAB	646-011	642-661	646-056	642-162
642-513				