



[Cisco 642-053](#)

Exam Name: Access Routing and LAN Switching Routing and Switching SE/FE Exam

Q & A : 180 Q&As

Pdf Demo

Quality and Value for the 642-053 Exam

[Just4Exams Practice Exams](#) for Cisco Access Routing and LAN Switching 642-053 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

100% Guarantee to Pass Your 642-053 Exam

If you do not pass the Access Routing and LAN Switching 642-053 exam on your first attempt using our Just4Exams **642-053 testing engine and pdf study guide**, we will give you a FULL REFUND of your purchasing fee.

Downloadable, Interactive 642-053 Testing engines and PDF Version

Our Exam Preparation Material provides you everything you will need to take a [Access Routing and LAN Switching certification](#) examination. Details are researched and produced by [Cisco Certification](#) Experts who are constantly using industry experience to produce precise, and logical.

Free 642-053 Exams:

This is demo only, this pdf do not include the questions and answers picture

Exam : Cisco 642-053

Title : Access Routing and LAN Switching Routing and Switching SE/FE Exam

1. LCP is responsible for the negotiation of which function?

- A. IP address
- B. modulo size
- C. error correction
- D. frequency on the link

Answer: C

2. You have used CRWS to set up an auto EZ VPN connection using Client mode with PAT. Which statement is true about the

connection?

- A. The connection uses the IP address of the outside interface to base the PAT address on and uses all other physical interface configurations.
- B. The connection ignores the physical outside address and uses addresses from the server for the both the inside and the outside addresses.
- C. The connection uses the IP address of the outside interface to base the PAT address on and uses server-supplied addresses for the inside interface and workstations.
- D. The connection ignores the outside IP address and uses one supplied by the server, while the inside addresses are used from the physical DHCP configuration of the client router.

Answer: D

3. Which T1 controller command is used to configure the controller for ISDN PRI operation?

- A. framing
- B. linecode
- C. pri-group
- D. isdn switch-type

Answer: C

4. Which three features are provided by the new ASIC in the Cisco Integrated Services Router platform? (Choose three.)

- A. provides a nonblocking high-speed bus to each interface and slot on the router
- B. processes any specific services
- C. allows DSP resources to be shared between all interfaces
- D. optimizes packet flow to and from CPU to improve efficiency
- E. accelerates QoS and ACL processing
- F. provides time of day and calendar used for validating certificates from a certificate authority

Answer: ACD

5. Which parameter will be used to determine when to disconnect an idle established DDR call, when the line is needed to place a DDR call to a different destination?

- A. The time specified by dialer idle-timeout.
- B. The time specified by dialer fast-idle.
- C. The value configured by dialer load-threshold.
- D. The presence of interesting traffic designated for a different destination will force an immediate disconnect.

Answer: B

6. Which technology allows a service provider to support overlapping customer VLAN IDs over transparent LAN services?

- A. 802.1q tunneling
- B. ATM
- C. SDH
- D. IP+Optical

Answer: A

7. What is the purpose of the dialer-list command when configuring a router to initiate a dial-on-demand routing ISDN call?

- A. It defines call destination parameters.
- B. It defines what constitutes interesting traffic.
- C. It provides for optional call parameters.
- D. It assigns a dialer-group to an interface.

Answer: B

8. Which Catalyst switch has modules tailored for VoIP?

- A. 2950
- B. 3550
- C. 4000
- D. 6500

Answer: D

9. Which two commands assign multiple ISDN BRI interfaces to a single hunt group? (Choose two.)

- A. dialer-group
- B. multilink ppp
- C. interface dialer
- D. dialer hunt-group

E. dialer rotary-group

Answer: CE

10. Which three protocols can be used by the NAC solution to implement its functions? (Choose three.)

A. IKE

B. 802.1x

C. RSA

D. EAP

E. RADIUS

F. WEP

Answer: BDE

11. A company has unique dial requirements for each branch site that communicates with a central site router. Which two commands permit multiple physical interfaces on a central router to be shared by multiple remote sites while retaining their unique site requirements? (Choose two.)

A. dialer pool

B. dialer-list

C. dialer-group

D. dialer hunt-group

E. dialer pool-member

Answer: AE

12. Cisco's Long Reach Ethernet (LRE) is based on Ethernet over which type of DSL service?

A. ADSL

B. IDSL

C. HDSL

D. VDSL

Answer: D

13. Which type of IGMP message is sent when a network client wants to join a multicast group?

A. host membership query

B. host membership report

C. host membership status

D. host membership notification

Answer: B

14. The new AIM-VPN module for the Cisco Integrated Services Router provides how many times better performance than the previous AIM-VPN modules?

A. 2

B. 4

C. 10

D. 15

E. 20

Answer: C

15. What is the purpose of a CSU/DSU in a leased T1 WAN configuration?

A. It provides encryption and compression for the security of transmitted data.

B. It multiplexes individual 64K channels into a single circuit.

C. It channelizes the leased T1 line into multiple 64K circuits.

D. It provides signal timing for communications and interfaces to the digital transmission facility.

E. It converts the analog T1 signals into digital signals for the router interface.

Answer: D

16. Which QoS technique avoids the problems that occur when tail drop is used as the congestion avoidance mechanism on the router?

A. RSVP

B. WRED

C. CAR

D. CBWFQ

Answer: B

17. What are the two modes of operation for the EZ VPN Remote? (Choose two.)

- A. Client mode with NAT/PAT
- B. Client mode without NAT/PAT
- C. Network Extension mode with PAT
- D. Network Extension mode without PAT

Answer: AD

18. You have decided to change the IP address of the inside network on a Cisco 800 broadband router using CRWS to 192.168.5.0/24 with an IP address on the router's inside interface of 192.168.5.1/24. You have made NO manual changes to the configuration. What will the IP addressing look like on the router on the inside interface?

- A. There will be one address on the inside interface of 192.168.5.1.
- B. There will be a 10.x.x.x address on the inside interface as a primary and 192.168.5.1 will be secondary.
- C. There will be the 192.168.5.1 address on the inside interface as a primary and a 10.x.x.x address as secondary.
- D. There will be a 10.x.x.x address on the main inside interface and a sub-interface will have been created with the 192.168.5.1 address installed on it.

Answer: B

19. Which statement is true about the STP Path Cost on a particular port?

- A. It is known only to the local switch where the port resides.
- B. It can be modified to help determine Root Bridge selection.
- C. Modifying it can cause TCN BPDU to be sent to the Root Bridge.
- D. When increased, it can provide higher bandwidth to a connecting port.

Answer: A

20. Which two features can SDM 0 configure? (Choose two.)

- A. resource monitoring
- B. PIM
- C. QoS
- D. SRST
- E. MPLS VPNs

Answer: AC

More [642-053 Braindumps](#) Information

Related 642-053 Exams

642-062	642-067	642-061	642-055	642-054
646-003	642-066	646-057	642-053	

Other Cisco Exams

642-541	642-383	640-816	646-272	642-241
642-382	642-961	646-573	642-373	640-822
642-642	640-861	642-902	650-575	642-978
642-975	642-062	646-056	646-393	640-553