



[Cisco 642-354](#)

Exam Name: Cisco Storage Networking Support Specialist(CSNSS)

Q & A : 140 Q&As

Pdf Demo

Quality and Value for the 642-354 Exam

[Just4Exams Practice Exams](#) for Cisco Storage Networking 642-354 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

100% Guarantee to Pass Your 642-354 Exam

If you do not pass the Storage Networking 642-354 exam on your first attempt using our Just4Exams **642-354 testing engine and pdf study guide**, we will give you a FULL REFUND of your purchasing fee.

Downloadable, Interactive 642-354 Testing engines and PDF Version

Our Exam Preparation Material provides you everything you will need to take a [Storage Networking certification](#) examination. Details are researched and produced by [Cisco Certification](#) Experts who are constantly using industry experience to produce precise, and logical.

Free 642-354 Exams:

This is demo only, this pdf do not include the questions and answers picture

Exam : Cisco 642-354

Title : Cisco Storage Network Support Specialist Exam

1. Reference the exhibit.

Given the output from the show command in the exhibit, what does the error message indicate is wrong with the configuration?

- A. Trunk mode has been administratively set to E instead of TE.
- B. The port needs a shut/noshut to become active.
- C. The port has been incorrectly left in VSAN 1.
- D. The trunk needs configured VSANs allowed on both sides.

Answer: D

2. You have been asked to install a Cisco MDS switch for your company. If you accept all installation defaults, which of these will occur?

- A. default port state: shut default zone policy: deny
- B. default port state: no shut default zone policy: deny
- C. default port state: shut default zone policy: permit
- D. default port state: no shut default zone policy: permit

Answer: A

- 3. deny config fspf
- 3. permit debug zone
- 4. permit exec fcping

Which of the following two functions can a user with role Manage undertake? (Choose two.)

- A. change fspf parameters
- B. configure FC port parameters for VSAN 3
- C. issue a debug command for a port
- D. configure zoning for all VSANs
- E. check connectivity for VSAN 2

Answer: BE

4. Your company has a multiswitch fabric including Switch A and Switch B. An administrator of Switch A creates the following zoneset and successfully activates it:

```
zoneset name ZoneSet1 vsan 1
```

```
zone name Zone1 vsan 1
```

```
pwwn 21:01:00:e0:8b:3c:03:b6
```

```
pwwn 21:01:00:e0:8b:3c:55:bb
```

Later in the day a second administrator creates the following zone set on Switch B:

```
zoneset name ZoneSet2 vsan 1
```

```
zone name Zone1 vsan 1
```

```
pwwn 21:01:00:e0:8b:3c:03:b6
```

```
pwwn 21:01:00:e0:8b:3c:55:aa
```

What happens when the administrator of Switch B attempts to activate ZoneSet2?

- A. ZoneSet2 becomes the active zoneset for both Switches A and B.
- B. The fabric segments and ZoneSet2 become the active zoneset for Switch B only.
- C. The fabric segments and ZoneSet 2 become the active zoneset for Switch A only.
- D. The fabric segments and ZoneSet 1 remain the active zone set for Switch B, while ZoneSet 2 becomes the active zoneset for Switch A.

Answer: A

5. The Cisco Traffic Analyzer is required to gather historical data for what type of information?

- A. Class F traffic
- B. SCSI session data
- C. Class 2 errors
- D. FC framing errors

Answer: B

- 6. permit debug zone
- 4. permit exec fcping

Which of the following two functions can a user with role Manage undertake? (Choose two.)

- A. change fspf parameters
- B. configure FC port parameters for VSAN 3
- C. issue a debug command for a port
- D. configure zoning for all VSANs
- E. check connectivity for VSAN 2

Answer: BE

7. You are looking at the LEDs on an MDS 9500 Supervisor module. If the Status LED is orange, which statement is true?

- A. The module cannot boot because of a corrupted image on the flash.
- B. The diagnostic test failed. The module is not operational because a fault occurred.
- C. The module is booting or running diagnostics.
- D. Incompatible power supplies are installed.

Answer: C

8. Which two of these items are advantages of configuring static domain IDs? (Choose two.)

- A. facilitates troubleshooting

- B. reduces FSPF link-state updates
- C. increases switch throughput
- D. ensures that persistent FCIDs will not change
- E. enables LUN masking

Answer: AD

9. What are four valid protocols for copying software to the MDS 9000 family switches? (Choose four.)

- A. Remote Copy Service
- B. Secure Copy Protocol
- C. Trivial File Transfer Protocol
- D. File Transfer Protocol
- E. Secure Trivial File Transfer Protocol
- F. Secure File Transfer Protocol

Answer: BCDF

10. An administrator reviews the running configuration of a switch that a junior administrator has prepared to be placed in a heterogeneous SAN environment. This environment includes three different brands of Fibre Channel switches. In this particular environment, only VSAN 1 is being used.

Which of these attributes suggests that the switch has not been properly configured?

- A. A static domain ID has been set to 0x21.
- B. src-dst-ox load balancing has been selected.
- C. Interop mode 3 has been selected.
- D. FCC has been enabled.

Answer: A

11. Which three of these upper-level protocols are supported by FC-4? (Choose three.)

- A. HIPPI
- B. SBCCS
- C. OSPF
- D. SCSI
- E. PPTP
- F. CDP

Answer: ABD

12. Consider the ACL applied to a GigE 2/3 on a Cisco MDS switch. What happens to traffic that does not match any of the rules?

- A. The traffic is allowed to pass through the interface because there is an implicit permit applied.
- B. The traffic is not allowed to pass through the interface because there is an implicit deny applied.
- C. The ACL is invalid and will not be accepted, and as a result the traffic will be allowed to pass.

Answer: B

13. An administrator finds these lines in the running configuration file:

```
interface vsan1
ip address 10.10.10.3 255.255.255.0
no shut
```

What is the impact of this entry?

- A. The entry sets the IP address on the management port and places it in VSAN 1.
- B. The entry creates an interface for IPFC.
- C. The entry sets up a common IP address to be shared by all GigE ports in VSAN 1.
- D. The entry sets up a default gateway for VSAN 1.

Answer: B

14. permit exec fcping

Which of the following two functions can a user with role Manage undertake? (Choose two.)

- A. change fspf parameters
- B. configure FC port parameters for VSAN 3
- C. issue a debug command for a port
- D. configure zoning for all VSANs
- E. check connectivity for VSAN 2

Answer: BE

15. Which three of these statements are attributes of the Cisco SET? (Choose three.)

- A. SET configuration is persistent.
- B. SBCCS and SCSI commands are supported.
- C. SET initiators can only communicate with SET targets.
- D. SET requires SAN-OS 2.0 or higher and the SAN Extension IP license.
- E. Only SCSI read/write commands are supported.

Answer: CDE

16. The Call Home feature provides what type of notification when critical events occur?

- A. SNMP
- B. syslog
- C. PBX
- D. e-mail

Answer: D

17. Which three CLI commands can be used to view remaining buffer-to-buffer credits? (Choose three.)

- A. show interface fc x/y
- B. show interface fc x/y brief
- C. show interface fc x/y counters
- D. show interface fc x/y bbcredit
- E. show interface fc x/y flow-control

Answer: ACD

18. Issuing the show role command to check a defined role in an MDS 9000 Series switch will produce the following output:

Role : Manage

VSAN Description :

vsan policy : deny Permitted vsans : 2-4

Rule Type Command-type Feature

- 1. permit config *
- 2. deny config fspf
- 3. permit debug zone
- 4. permit exec fcping

Which of the following two functions can a user with role Manage undertake? (Choose two.)

- A. change fspf parameters
- B. configure FC port parameters for VSAN 3
- C. issue a debug command for a port
- D. configure zoning for all VSANs
- E. check connectivity for VSAN 2

Answer: BE

19. When installing the Port Analyzer Adapter, how do you connect the Fibre Channel port to the MDS switch?

- A. single-mode fiber and SC to LC connector
- B. multimode fiber and LC to LC connector
- C. single-mode fiber and LC to LC connector
- D. multimode fiber and SC to LC connector

Answer: B

20. Your company is planning a SAN deployment using Fibre Channel connections from a central, highly secure data center to several less secure branch offices. Which of these security features would allow you to disable all branch office switch management ports and yet still maintain the complete suite of TCP/IP-based SAN management utilities?

- A. IPSec
- B. Port Mode Security
- C. Port Security
- D. Overlay VSAN

Answer: D

More [642-354 Braindumps](#) Information

Related 642-354 Exams

642-356	642-353	642-355	646-011	642-354
---------	---------	---------	---------	---------

Other Cisco Exams

646-228	642-432	646-002	646-057	646-653
642-382	642-825	650-621	640-863	642-812

642-642	650-575	642-544	642-062	646-056
650-393	642-144	642-964	642-691	350-021