



Cisco 642-382

Exam Name:

Q & A : 59 Q&As

Pdf Demo

Quality and Value for the 642-382 Exam

[Just4Exams Practice Exams](#) for Cisco Optical 642-382 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

100% Guarantee to Pass Your 642-382 Exam

If you do not pass the Optical 642-382 exam on your first attempt using our Just4Exams **642-382 testing engine and pdf study guide**, we will give you a FULL REFUND of your purchasing fee.

Downloadable, Interactive 642-382 Testing engines and PDF Version

Our Exam Preparation Material provides you everything you will need to take a [Optical certification](#) examination. Details are researched and produced by [Cisco Certification](#) Experts who are constantly using industry experience to produce precise, and logical.

Free 642-382 Exams:

This is demo only, this pdf do not include the questions and answers picture

Exam : Cisco 642-382

Title : Cisco Express Foundation for Field Engineers

1. Refer to the exhibit. A company has just set up an e-commerce webhost on the DMZ. It was designed so that partners can enter their equipment orders via a secure interface on a security appliance. The first time a partner tried to access the e-commerce webhost at `http://172.16.1.2`, the partner could not gain access to the webhost.

After reviewing the network diagram, the Cisco Adaptive Security Device Manager translation table, and Cisco ASDM access list configuration shown in the exhibit, what did the corporate network administrator determine to be the cause of the problem?

- A. The pnet static translation entry is not configured correctly.
- B. The URL that the partner is using is not configured correctly.
- C. The pnet-access access list is not configured correctly.
- D. The pnet global address is not configured correctly.

Answer: B

2. Refer to the exhibit.

R2 is always in the init state. Which two statements are correct? (Choose two.)

- A. R2 is seeing hello packets from R1.
- B. R2 is not seeing hello packets from R1.
- C. The exchanging of data between R1 and R2 is occurring because each is sending hello packets.
- D. Two-way communication has not been established between R1 and R2 because R2 is not seeing its router ID in the hello packets that it is receiving from R1.
- E. R2 has an access list defined for S0 that is blocking an OSPF multicast IP address of 224.0.0.5.

Answer: AD

3. Which command assigns a cost value of "17" to a switch port?

- A. spanning-tree interface fastethernet 5/8 17
- B. spanning-tree portcost 17
- C. spanning-tree port cost 17
- D. spanning-tree vlan 1 cost 17

Answer: D

4. In what location is it recommended that the Cisco Catalyst 6500 Series WLSM be placed?

- A. distribution layer
- B. core layer
- C. access layer
- D. network management functional module

Answer: A

5. Which network management tool is designed to allow businesses to manage up to 40 devices?

- A. CiscoWorks Unrestricted
- B. CiscoWorks SNMS
- C. Campus Manager
- D. Resource Management Essentials

Answer: B

6. Which three are different types of STP inconsistencies in a Layer 2 network? (Choose three.)

- A. MAC inconsistency
- B. root inconsistency
- C. EtherChannel inconsistency
- D. type inconsistency
- E. PVID inconsistency
- F. vendor inconsistency

Answer: BCD

7. You are migrating the network design from using point security products (perimeter router, firewall, VPN router, IPS) to an integrated security solution using Cisco ISR. During the migration process, you determine that you need to improve VPN performance. What can you do?

- A. upgrade the Cisco IOS image on the ISR to the V3PN bundle
- B. increase the RAM on the ISR
- C. install AIM-VPN EP11-PLUS on the ISR
- D. enable transparent tunneling using IPSec over TCP

Answer: C

8. Which two statements are correct about OSPF in a multiarea environment? (Choose two.)

- A. OSPF will by default summarize routing updates between areas.
- B. OSPF requires the use of the area range configuration command only when nondefault summarization is required.
- C. OSPF ABR routers are needed only at the boundary of another OSPF area.
- D. OSPF uses wildcard masks in the network statements but subnet masks in the area range statements.
- E. OSPF requires that all areas have a least one ASBR.

Answer: CD

9. A wireless autonomous 1200 access point running core feature set in root mode has its SSID set to Factory_floor and provides connection to a repeater access point with its SSID set to Factory_floor. If the root-mode access point is using channel 11, which channel

will the repeater access point use?

- A. channel 11
- B. channel 1 or 6
- C. any nonoverlapping channel
- D. The root access point and the repeater will negotiate this setting.

Answer: A

10. Refer to the exhibit. The tables contain information from the Cisco Router and Security Device Manager configurations of Router A and Router B. Traffic between Host 1 and Host 2 is not successfully establishing the site-to-site VPN between Router A and Router B.

What is the mostly likely cause of this fault?

- A. Router A is using a standard IP ACL (100-149) while Router B is using a Turbo ACL (150?99).
- B. The IKE encryption methods on the two routers are different.
- C. The IPSec policy map names on the two routers are different.
- D. The IPSec rules on the two routers are not permitting the correct interesting traffic.

Answer: B

More [642-382 Braindumps](#) Information

Related 642-382 Exams

642-241	642-381	642-564	642-321	642-311
642-382	642-371			

Other Cisco Exams

642-071	642-359	642-873	642-382	642-691
642-072	642-061	646-204	642-373	642-812
646-202	642-342	646-272	642-511	640-811
640-802	642-832	350-029	642-452	646-393