



[Cisco 642-551](#)

Exam Name: *Securing Cisco Network Devices Exam(SND)*

Q & A : 62 Q&As

Pdf Demo

Quality and Value for the 642-551 Exam

[Just4Exams Practice Exams](#) for Cisco CCSP VPN and Security 642-551 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

100% Guarantee to Pass Your 642-551 Exam

If you do not pass the CCSP VPN and Security 642-551 exam on your first attempt using our Just4Exams **642-551 testing engine and pdf study guide**, we will give you a FULL REFUND of your purchasing fee.

Downloadable, Interactive 642-551 Testing engines and PDF Version

Our Exam Preparation Material provides you everything you will need to take a [CCSP certification VPN and Security certification](#) examination. Details are researched and produced by [Cisco Certification](#) Experts who are constantly using industry experience to produce precise, and logical.

Free 642-551 Exams:

This is demo only, this pdf do not include the questions and answers picture

Exam : CISCO 642-551

Title : Securing Cisco Network Devices Exam(SND)

1. Which Cisco IOS command enables the AAA access-control commands and functions on the router, and overrides the older TACACS and extended TACACS commands?

- A. no aaa authentication login default enable
- B. aaa authentication login default local
- C. aaa new-model
- D. login authentication default
- E. no login authentication default

Answer: C

2. Which command would be used on the Cisco PIX Security Appliance to show the pool of addresses to be translated?

- A. show nat
- B. show xlate
- C. show global
- D. show conn

Answer: C

3. Which Cisco IDS/IPS feature enables the appliance to aggregate alarms?

- A. FireOnce
- B. response actions
- C. alarm summarization
- D. threshold configuration

Answer: C

4. What is a set of conditions that, when met, indicates that an intrusion is occurring or has occurred?

- A. rules
- B. state tables
- C. signatures
- D. master parameters

Answer: C

5. Which command is used to reboot the Cisco PIX Security Appliance?

- A. reboot
- B. restart
- C. boot
- D. reload

Answer: D

6. To which router platform can Turbo ACLs be applied?

- A. Cisco 800 Router
- B. Cisco 2600 Series Router
- C. Cisco 3500
- D. Cisco 7200 Router

Answer: D

7. Which communication protocol is used by the administrator workstation to communicate with the CSA MC?

- A. SSH
- B. Telnet
- C. HTTPS
- D. SSL

Answer: D

8. What is a description of a promiscuous PVLAN port?

- A. It has a complete Layer 2 separation from the other ports within the same PVLAN.
- B. It can only communicate with other promiscuous ports.
- C. It can communicate with all interfaces within a PVLAN.
- D. It cannot communicate with any other ports.

Answer: C

9. Which component within the Cisco Network Admission Control architecture acts as the policy server for evaluating the endpoint security information that is relayed from network devices, and for determining the appropriate access policy to apply?

- A. CiscoWorks
- B. CiscoWorks VMS
- C. Cisco Secure ACS
- D. Cisco Trust Agent
- E. Cisco Security Agent

Answer: C

10. What are the three types of private VLAN ports? (Choose three.)

- A. typical

- B. isolated
- C. nonisolated
- D. promiscuous
- E. community
- F. bridging

Answer: BDE

11. If you choose Add from the Allowed Hosts panel in Cisco IDM, which two fields are available for configuration? (Choose two.)

- A. Static Routes
- B. Dynamic Routes
- C. IP Address
- D. Default Route
- E. Netmask

Answer: CE

12. LAB

This is the Answer:

```
pixfirewall(config)#interface eth3 100full
```

```
pixfirewall(config)# nameif eth3 protected security 56
```

```
pixfirewall(config)# ip address protected 192.168.147.1 255.255.255.0
```

5. When port security is enabled on a Cisco Catalyst switch, what is the default action when the configured maximum of allowed MAC addresses value is exceeded?

- A. The port is shut down.
- B. The port is enabled and the maximum number automatically increases.
- C. The MAC address table is cleared and the new MAC address is entered into the table.
- D. The MAC address table is shut down.

Answer: A

13. When port security is enabled on a Cisco Catalyst switch, what is the default action when the configured maximum of allowed MAC addresses value is exceeded?

- A. The port is shut down.
- B. The port is enabled and the maximum number automatically increases.
- C. The MAC address table is cleared and the new MAC address is entered into the table.
- D. The MAC address table is shut down.

Answer: A

14. Which administrative access mode for the Cisco PIX Security Appliance allows you to change the current settings?

- A. unprivileged mode
- B. privileged mode
- C. configuration mode
- D. monitor mode

Answer: B

15. Which method does a Cisco firewall use for packet filtering?

- A. inspection rules
- B. ACLs
- C. security policies
- D. VACLs

Answer: B

16. Which two protocols does Cisco Secure ACS use for AAA services? (Choose two.)

- A. TACACS+
- B. Telnet
- C. SSH
- D. RADIUS
- E. SSL
- F. SNMP

Answer: AD

17. What is the default security-level definition setting for the outside interface for the Cisco PIX Security Appliance?

- A. 0

B. 100

C. 50

D. 25

Answer: A

More [642-551 Braindumps](#) Information

Related 642-551 Exams

642-515	642-545	642-542	642-552	642-513
642-502	642-503	642-523	642-532	642-521
642-551	642-522			

Other Cisco Exams

646-003	646-203	646-362	640-811	642-545
642-582	642-164	646-011	350-022	642-382
646-562	642-181	642-979	642-652	642-973
646-227	351-001	642-736	642-522	642-504