



[Cisco 642-651](#)

Exam Name: Cisco Wide Area Application Services for System Engineers exam

Q & A : 60 Q&As

Pdf Demo

Quality and Value for the 642-651 Exam

[Just4Exams Practice Exams](#) for Cisco WAASSE 642-651 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

100% Guarantee to Pass Your 642-651 Exam

If you do not pass the WAASSE 642-651 exam on your first attempt using our Just4Exams **642-651 testing engine and pdf study guide**, we will give you a FULL REFUND of your purchasing fee.

Downloadable, Interactive 642-651 Testing engines and PDF Version

Our Exam Preparation Material provides you everything you will need to take a [WAASSE certification](#) examination. Details are researched and produced by [Cisco Certification](#) Experts who are constantly using industry experience to produce precise, and logical.

Free 642-651 Exams:

This is demo only, this pdf do not include the questions and answers picture

Exam : Cisco 642-651

Title : Cisco Wide Area Application Services for System Engineers

1. Which LAN traffic management feature is fully supported by Cisco WAAS?

- A. intrusion detection system
- B. QoS
- C. NBAR
- D. MPLS

Answer: B

2. Which two options correctly identify the WAE file services integration modes available in Cisco WAAS? (Choose two.)

- A. transparent, in which the WAE appears as a node on the remote office LAN

- B. transparent, in which the WAE does not appear as a node on the remote office LAN
- C. non-transparent, in which the WAE appears as a node on the remote office LAN
- D. non-transparent, in which the WAE does not appear as a node on the remote office LAN

Answer: BC

3. How can you monitor optimization statistics for a given application across multiple Cisco WAE devices?

- A. Create a device group for all WAE devices on which that application is optimized.
- B. Create a location group for all WAE devices on which that application is optimized.
- C. Create a separate application traffic policy for each application.
- D. Ensure that each application resides on a different subnet.

Answer: A

4. When using PBR, what do you need to configure to enable failover?

- A. QoS
- B. MPLS
- C. IP SLAs
- D. NetFlow

Answer: C

5. In a Cisco WAAS environment, which TCP connection establishment messages should you examine if your customer has sent you a TCP protocol trace and asked for your help in understanding why the WAE appliances are failing to negotiate the correct, optimized policy?

- A. SYN and FIN
- B. SYN and ACK
- C. SYN and SYN ACK
- D. ACK and SYN ACK

Answer: C

6. Your customer is using PBR as the interception method on its routers. Which mechanism would you recommend to ensure WAE availability and failover if a WAE fails?

- A. enable NetFlow to track WAE appliances
- B. enable IP SLAs to track WAE appliances
- C. nothing, PBR automatically tracks WAE appliances
- D. nothing, PBR does not support the tracking of WAE appliances

Answer: B

7. You have configured a Central Manager WAE cluster for your customer. After a technician accidentally unplugs the power cord from the primary Central Manager WAE, the network administrator calls you to complain that the standby Central Manager WAE did not automatically assume the primary role. What should you tell this administrator?

- A. You should verify that the datafeed.pollrate setting is configured properly.
- B. You should make sure the two Central Manager WAE appliances are on the same subnet
- C. You must manually copy the Central Manager database to the standby Central Manager WAE.
- D. You must manually initiate failover and fallback processes on the WAE.

Answer: D

8. What are three benefits of using the Cisco WAE file blocking feature? (Choose three.)

- A. eliminates data redundancy
- B. reduces the use of network resources
- C. minimizes the transfer of unsanctioned data
- D. prevents multiple users from attempting to edit the same file
- E. controls which file types are stored on the data center file server
- F. ensures that files cannot be edited until they are synchronized between the branch and the data center

Answer: BCE

9. Which two functions does the Central Manager provide in a Cisco WAAS environment? (Choose two.)

- A. application acceleration
- B. management of CIFS servers
- C. application statistics monitoring
- D. configuration backup and restore
- E. policy configuration and distribution

Answer: CE

10. When you size a Cisco WAAS solution, you should assume that how many of the total number of concurrent TCP connections per user will be optimized?

- A. 1-2
- B. 4-7
- C. 14-20
- D. 25-40

Answer: B

11. Your customer is using firewalls. What must be permitted to pass through the firewalls in order to allow WAE auto-discovery?

- A. TCP options
- B. TCP port 139
- C. TCP port 445
- D. TCP SYN-ACK with data

Answer: A

12. Your customer has purchased multiple Cisco WAE appliances, but does not want to dedicate one WAE for management purposes only. How would you advise this customer?

- A. There must be at least one Central Manager available for configuration and management tasks.
- B. The data center WAE can be used for both the Central Manager and Application Accelerator roles.
- C. There is no need for a dedicated Central Manager; all configuration tasks can be performed on the application accelerators using the WAE device CLI and GUI.
- D. If one of the WAE appliances is configured as the Central Manager, then later, after all application accelerators are registered and on line, the Central Manager WAE can be reconfigured as an application accelerator.

Answer: A

13. Your customer's Cisco WAAS design calls for the Central Manager to be deployed on the Core WAE, which is a WAE-612 with 2GB of RAM. The customer initially configured the WAE as an application accelerator, and then issued the device mode central-manager command to enable Central Manager service. Now the customer reports that the WAE is no longer accelerating traffic. What is the problem?

- A. The Central Manager and application accelerator cannot be deployed on the same WAE.
- B. At least 4GB of RAM must be installed for the WAE to serve as both Central Manager and application accelerator.
- C. The device mode central-manager command must be issued before the device mode application-accelerator command.
- D. Central Manager is consuming too much CPU time on the WAE. The Central Manager service should be implemented on a less-utilized edge WAE.

Answer: A

14. How does Cisco WAAS advanced compression DRE improve on traditional LZ compression?

- A. by removing the transmission of previously-seen data
- B. by pre-positioning often-used file segments on the edge WAE appliances
- C. by comparing hashes of each file version to avoid unnecessary file synchronization
- D. by implementing a more aggressive, hardware-intensive version of the LZ compression algorithm

Answer: A

15. In a WAAS Application Traffic Policy, what are three valid match conditions for traffic classifiers? (Choose three.)

- A. IP address
- B. routed protocol
- C. routing
- D. subnet
- E. TCP port
- F. UDP port

Answer: ADE

More [642-651 Braindumps](#) Information

Related 642-651 Exams

642-654 642-655 642-651 642-652

Other Cisco Exams

642-973 642-503 642-426 642-731 646-096
642-446 646-272 642-062 642-801 642-845
642-587 642-591 642-371 646-222 642-513
642-274 642-544 642-359 642-321 650-621

