



[Cisco 642-964](#)

Exam Name: Cisco Data Center Networking Infrastructure Solutions Support

Q & A : 60 Q&As

Pdf Demo

Quality and Value for the 642-964 Exam

[Just4Exams Practice Exams](#) for Cisco Others 642-964 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

100% Guarantee to Pass Your 642-964 Exam

If you do not pass the Others 642-964 exam on your first attempt using our Just4Exams **642-964 testing engine and pdf study guide**, we will give you a FULL REFUND of your purchasing fee.

Downloadable, Interactive 642-964 Testing engines and PDF Version

Our Exam Preparation Material provides you everything you will need to take a [Others certification](#) examination. Details are researched and produced by [Cisco Certification](#) Experts who are constantly using industry experience to produce precise, and logical.

Free 642-964 Exams:

This is demo only, this pdf do not include the questions and answers picture

Exam : Cisco 642-964

Title : Cisco Data Center Networking Infrastructure Support

1. What is the effect of executing the command intrusion-detection module 5 management-port access-vlan 10 on an IDSM?

- A. allows the IDSM to be managed by devices in VLAN 10
- B. configures the IDSM to monitor traffic from VLAN 10 in in-line mode
- C. allows the IDSM to perform blocking actions on devices in VLAN 10
- D. configures the IDSM to monitor traffic from VLAN 10 in promiscuous mode

Answer: A

2. How would you configure a NAM to monitor and report the most heavily viewed sections of a website?

- A. Create a separate domain name or virtual server IP address for each section of the site. Add each domain name or IP address to the

NAM application protocol directory.

B. Enable regular-expression pattern matching. Define application protocol filters based on regular expressions that match the desired URLs.

C. Enable URL monitoring. Define each desired URL as an application in the protocol directory.

D. Use SPAN or VACLs to capture upper-layer protocol data from the web servers. Use a third-party application to parse the stored capture files.

Answer: C

3. Refer to the exhibit. Which FWSM command allows routing of TCP traffic from the Internet to network 10.0.3.0/24?

A. `access-list inside permit tcp 192.168.1.0 255.255.255.0 10.0.3.0 255.255.255.0`

B. `route inside 10.0.3.0 255.255.255.0 10.0.1.3`

C. `route outside 10.0.3.0 255.255.255.0 10.0.1.3`

D. `route inside 0 0 10.0.1.3`

Answer: B

4. Which statement is correct regarding Layer 3 EtherChannels?

A. They are STP-aware.

B. They cannot be automatically negotiated.

C. Multiple EtherChannels are used between a pair of switches.

D. Multiple EtherChannels between two switches create an STP loop.

Answer: C

5. On a Cisco Catalyst 6500 Series Switch, how many physical links can be aggregated into an EtherChannel group?

A. 4

B. 8

C. 16

D. 32

Answer: B

6. How can you configure the NAM to view a list of all switches that are sending NDE packets?

A. Enter the command `sh data-source nde`.

B. Configure Cisco Discovery Protocol to detect all switches on the network.

C. Launch NetFlow Listening Mode from the Cisco Traffic Analyzer application.

D. The NAM will automatically detect NDE broadcasts and add each switch to the NetFlow device table.

Answer: C

7. The IDSM management-interface IP address can be configured from which prompt?

A. `IDSM(config)#`

B. `IDSM(config-hos-net)#`

C. `IDSM(config-mgmt)#`

D. `IDSM(config-if)#`

Answer: B

8. What will be upgraded as a result of this command?

`upgrade ftp://ftpuser@10.1.2.3//upgrade/IPS-K9-r-1.1-a-5.1-1-1.pkg`

A. recovery partition

B. application partition

C. both application and recovery partitions immediately

D. both application and recovery partitions at the next scheduled automatic IDSM update

Answer: A

9. Which command must be issued to activate the FWSM firewall context?

A. `allocate-vlan`

B. `config-url`

C. `limit-resource`

D. `map-interface`

Answer: B

10. Refer to the exhibit. Which command would you use on the FWSM to provide a default route from Servers 1 and 2 to the Internet?

A. `route inside 0 0 192.168.100.1`

B. `route inside 10.1.0.0 255.255.0.0 192.168.1.1`

C. route outside 0 0 192.168.100.1

D. route outside 10.1.0.0 255.255.0.0 192.168.1.1

Answer: C

More [642-964 Braindumps](#) Information

Related 642-964 Exams

642-524	642-436	642-972	650-175	646-223
642-504	642-145	642-456	642-741	642-426
640-460	642-383	642-731	650-180	646-230
646-563	642-373	646-363	642-975	646-656

Other Cisco Exams

646-363	642-481	642-054	642-681	642-973
646-058	642-372	642-453	642-892	642-533
646-002	642-972	646-276	646-361	650-178
350-001	642-975	642-801	646-967	642-655