



[Nortel 920-141](#)

Exam Name: *NNCDS-Communication Server(cs)1000 release 4.0*

Q & A : 68 Q&As

Pdf Demo

Quality and Value for the 920-141 Exam

[Just4Exams Practice Exams](#) for Nortel NCDS 920-141 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

100% Guarantee to Pass Your 920-141 Exam

If you do not pass the NCDS 920-141 exam on your first attempt using our Just4Exams **920-141 testing engine and pdf study guide**, we will give you a FULL REFUND of your purchasing fee.

Downloadable, Interactive 920-141 Testing engines and PDF Version

Our Exam Preparation Material provides you everything you will need to take a [NCDS certification](#) examination. Details are researched and produced by [Nortel Certification](#) Experts who are constantly using industry experience to produce precise, and logical.

Free 920-141 Exams:

This is demo only, this pdf do not include the questions and answers picture

Exam : NORTEL 920-141

Title : NNCDS-Communication Server(cs)1000 release 4.0

1. In the process of designing a CS 1000 Rls. 4.0 system per the customer specifications, you need to order two Enterprise Media Gateway 1000T (EMG 1000T) and eight EMG 1000E systems. Each EMG 1000T will have three digital trunk cards (TMDI) and the EMG 1000E systems are provisioned for digital and analog lines. At a minimum, how many Clock Controllers are required?

- A. two
- B. three
- C. six
- D. ten

Answer: A

2. A customer wants to configure the Enterprise Media Gateways (EMG) on their CS 1000 RIs. 4.0 system for survivability. They also need to interpret the network requirements for the system. Which configuration ensures network survivability?

- A. The survivable EMG TLAN IP address must be on the same TLAN subnet as the Call Server.
- B. The survivable EMG ELAN IP address must be on the same ELAN subnet as the Call Server.
- C. The survivable EMG ELAN IP address must be on a different ELAN subnet than the Call Server.
- D. The survivable EMG must be separated from the Call Server by a Layer 3 device networked with the two Call Servers.

Answer: B

3. A customer has a CS 1000M-SG RIs. 4.0 system installed with one Signaling Server with 512 MB of memory. This system networks to multiple sites with VoIP using 200 IP Peer H.323 trunks. Because additional sites have been added, the customer needs to expand this network. To configure an additional 200 IP Peer H.323 trunks, what must be done?

- A. Add one IP Trunk card.
- B. Just configure the additional trunks.
- C. Add one additional Signaling Server.
- D. Just purchase additional virtual trunk licenses.

Answer: D

4. When designing a geographic redundancy scheme for a CS 1000M RIs. 4.0 system, the failsafe Network Routing Service (NRS) must reside on which component in case network communications are lost with the Primary and Alternate NRS?

- A. the Signaling Server designated as the Leader
- B. the Signaling Server designated as the Follower
- C. on both the Follower and the Leader Signaling Server
- D. the CS 1000E Call Server that resides on the secondary system

Answer: A

5. A company is planning the deployment of a new CS 1000 RIs. 4.0 system and requires ultra-high reliability. How would campus redundancy meet their needs?

- A. It provides an optionally redundant Signaling Server.
- B. It moves the Gatekeeper to a standalone Signaling Server.
- C. It duplicates the entire processing core of a CS 1000E fault resilient system.
- D. It provisions an Enterprise Media Gateway 1000E as a CS 1000E Call Server.

Answer: C

6. A company has a geographically dispersed workforce with laptop computers. They connect their PCs to the company intranet via cable modems and/or DSL over VPN using IPSec. They plan to deploy IP Softphone 2050s. A network assessment shows some shared Ethernet hubs between the VPN server and the CS 1000 RIs. 4.0. At a minimum, what is required to enable a deployment of the telephones?

- A. Layer 3 switches with gigabit uplink
- B. Layer 3 switches with VLAN support
- C. Layer 2 switches with 802.1p support
- D. Layer 2 switches with DiffServ capabilities

Answer: C

7. What is a the benefit of networking several CS 1000S RIs 4.0 system Call Servers together through LAN or WAN connections under the control of one Network Redirect Server (NRS)?

- A. Double Virtual Trunk resources are used for intra-system, inter-Call Server calls.
- B. IP Phones with a known community of interest can be registered on the same Call Server.
- C. AMIS and VPIM networking of the voice messaging systems is more efficient using the NRS.
- D. MCDN can be enabled providing Enterprise-wide feature transparency between the systems.

Answer: D

8. A company plans to deploy a CS 1000M-SG RIs. 4.0 system at their headquarters. Some of their call center agents are located in a branch office. They want all applications to be centrally located and managed at the headquarters. Agents are to access services via an IP connection and get local access to the PSTN through PRI connections. What should the company consider as part of their traffic plan? (Choose three.)

- A. the number of PRI cards for ESN access
- B. the creation of private zone for the agents
- C. the engineering requirements for Multimedia Processing Units (MPUs)
- D. the total WAN requirements for data between the branch office and the main office
- E. the total WAN bandwidth required for the remote call center agent telephony needs

Answer: BDE

9. A customer is considering the deployment of the a H.323 Gatekeeper in failsafe mode for a CS 1000 RIs. 4.0 solution. Which statement most accurately describes why you would recommend this configuration?

- A. Communication to the primary and secondary H.323 Gatekeepers will never be lost.
- B. The Failsafe H.323 Gatekeeper within a gatekeeper zone takes over gatekeeper responsibilities for all of its peers within the zone.
- C. If communication is lost with the primary H.323 Gatekeeper, the secondary gatekeeper will become the primary and run in failsafe mode.
- D. If communication is lost to both gatekeepers, the H.323 Gateway running the failsafe gatekeeper services will continue to route calls in a best-effort fashion until communication is restored.

Answer: D

10. In the process of provisioning a CS 1000S RIs. 0 system, a customer wants to include a branch office into the configuration with 50 analog and 400 IP Phones. Each IP Phone carries 6 Centi-Call Seconds (CCS) each; 50% of the calls go to other IP Phones and 50% go to analog telephones. The Voice Gateway Media Cards (VGMCs) for the Enterprise Media Gateway 1000B have a call capacity of 794 CCS. How many VGMCs will be needed?

- A. one
- B. two
- C. three
- D. four

Answer: A

More [920-141 Braindumps](#) Information

Related 920-141 Exams

920-165	920-141	920-256	920-136	920-203
920-242	920-125	920-209	920-124	

Other Nortel Exams

920-124	920-442	920-569	920-171	920-443
920-260	920-209	920-195	920-552	922-057
920-128	922-041	920-177	920-263	920-136
922-091	922-080	920-174	920-160	922-110