



[Nortel 920-245](#)

Exam Name: Ethernet Switching

Q & A : 61 Q&As

[Pdf Demo](#)

Quality and Value for the 920-245 Exam

[Just4Exams Practice Exams](#) for Nortel NCSS 920-245 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

100% Guarantee to Pass Your 920-245 Exam

If you do not pass the NCSS 920-245 exam on your first attempt using our Just4Exams **920-245 testing engine and pdf study guide**, we will give you a FULL REFUND of your purchasing fee.

Downloadable, Interactive 920-245 Testing engines and PDF Version

Our Exam Preparation Material provides you everything you will need to take a [NCSS certification](#) examination. Details are researched and produced by [Nortel Certification](#) Experts who are constantly using industry experience to produce precise, and logical.

Free 920-245 Exams:

This is demo only, this pdf do not include the questions and answers picture

Exam : Nortel 920-245

Title : Ethernet Switching

1. Given the conditions:

Left LED - green

Right LED - flashing green

On an Ethernet Routing Switch 8648TXE/M 10/100 Ethernet I/O module, what is the status of a port that is displaying the LED conditions described above?

- A. Link speed is 10 Mbps and the port is disabled.
- B. Link speed is 100 Mbps and the port is disabled.
- C. Link speed is 10 Mbps and the port is passing traffic.
- D. Link speed is 100 Mbps and the port is passing traffic.

Answer: D

2. If one Multi Link Trunk is being used, how many fewer VLANs would be available on the Ethernet Routing Switch 8600?

- A. 1
- B. 4
- C. 8
- D. 16

Answer: C

3. You have installed a new Ethernet Switch 460-24T into a customer's network and are using the QoS Wizard to configure the QoS settings for various IP traffic flows. Which two IP applications can you directly choose in the QoS Wizard to prioritize inbound frames based on traffic type? (Choose two.)

- A. E-mail (SMTP)
- B. File Transfer (FTP)
- C. Multicasting (IGMP)
- D. Trivial File Transfer (TFTP)
- E. Network Management (SNMP)

Answer: AB

4. When can you obtain and load an image from an external TFTP server through one of the I/O ports?

- A. When you invoke the boot (ip address)/<file> command from the Device Manager.
- B. When you configure the Ethernet Routing Switch 8600 to boot from the network, then reset.
- C. When you invoke the boot (ip address):<file> command from the Command Line Interface (CLI).
- D. When you configure the Ethernet Routing Switch 8600 to boot from the network, then recycle power.

Answer: C

5. Click the exhibit button.

Given the following Ethernet Switch 325-24T configuration:

VLAN 10 is a port-based VLAN.

Port 1 is an untagged member of VLAN 10.

Port 5 is a tagged member of VLAN 10.

The device on Port 1 transmits an untagged frame to the device on Port 5.

How will an untagged frame be treated when it reaches Port 5 on this switch?

- A. It will be discarded when it is received.
- B. It will be placed in a hardware-based queue based on Priority 6. Then it will be tagged, and transmitted out Port 5 with Priority 2.
- C. It will be placed in a hardware-based queue based on Priority 6. Then it will be tagged, and transmitted out Port 5 with Priority 6.
- D. It will be placed in a hardware-based queue based on Priority 2. Then it will be tagged, and transmitted out Port 5 with Priority 2.

Answer: C

6. Which three switches support auto Media Dependent Interface Crossover (MDI/MDIX)? (Choose three.)

- A. Ethernet Switch 425
- B. Ethernet Switch 450
- C. Ethernet Switch 460
- D. Ethernet Switch 470
- E. Ethernet Routing Switch 5510

Answer: ADE

7. What is an advantage of using Independent VLAN Learning (IVL) mode over Shared VLAN Learning (SVL) mode on an Ethernet Switch 460-24T-PWR?

- A. The Spanning Tree Protocol (STP) can be disabled.
- B. More MAC addresses can be stored with unique forwarding databases.
- C. Duplicate MAC addresses can be handled if they are in different VLANs.
- D. The port forwarding rate will be greater with unique forwarding databases.

Answer: C

8. In the event of a network failure, a customer requires that an Open Shortest Path First (OSPF) interface detect the failure within 30 seconds. Which Ethernet Routing Switch 8600 Command Line Interface (CLI) command must be used to ensure a network failure is detected in the required amount of time?

- A. config vlan <vid> ip ospf metric 30
- B. config vlan <vid> ip ospf priority 30
- C. config vlan <vid> ip ospf hello-interval 30

D. config vlan <vid> ip ospf dead-interval 30

Answer: D

9. Which route type in the Ethernet Routing Switch 8600 routing table provides additional routes for faster convergence in case of network/link failures?

- A. best
- B. direct
- C. MPLS
- D. ECMP

Answer: D

10. An Ethernet Switch 450-24T will be added to an existing stack of two Ethernet Switch 470-24Ts. The software Release running on the Ethernet Switch 450-24T is compatible with the software Release running on the Ethernet Switch 470-24Ts. To complete the stack creation successfully, which two configuration changes are necessary? (Choose two.)

- A. Set the Unit Select switch on the Ethernet Switch 450-24T to the "Off" position.
- B. Set the Unit Select switch on the Ethernet Switch 450-24T to "Base" ("On" position).
- C. Set the Stack Mode for all Ethernet Switch 470-24Ts to Hybrid and then reset the stack.
- D. Cable the Ethernet Switch 450-24T into the stack, power off all units, and then power up the stack.
- E. Set the Stack Mode for the Base Ethernet Switch 470-24T to Hybrid and leave the other Ethernet Switch 470-24T as Pure.

Answer: AC

11. Which Ethernet Routing Switch QoS feature ensures that the lower six egress queues are serviced in a fair, yet weighted manner?

- A. WRR
- B. WFQ
- C. DSCP
- D. TCP/UDP

Answer: A

12. You need to add a new port on an Ethernet Routing Switch 5510 that will support a new server to an existing VLAN that is a member of an existing Spanning Tree Group (STG). Which action(s) should you perform to accomplish this task?

- A. Add the port to the VLAN.
- B. Add the port to the VLAN and then manually add the port to the STG.
- C. Disable the STG, add the port to the VLAN, and then enable the STG.
- D. Remove the VLAN from the STG, add the port to the VLAN, and then add the VLAN to the STG.

Answer: B

13. Which two statements are true regarding Virtual Router Redundancy Protocol (VRRP) Backup? (Choose two.)

- A. It must advertise its presence to the network.
- B. It must not accept packets addressed to the IP address(s) associated with the virtual router.
- C. It must discard packets with a destination Media Access Control (MAC) equal to the virtual router MAC.
- D. It must respond to Address Resolution Protocol (ARP) requests for address(s) associated with the virtual router.

Answer: BC

14. Which actions should be performed during a configuration of a QoS policy for a trusted interface?

- A. drop traffic to a port
- B. change of DSCP value
- C. modification of 802.1p value
- D. alteration of the drop precedence

Answer: A

15. A customer with an Ethernet Switch 470-24T wants to configure MAC address-based security. Given that they can create up to 10 MAC Destination Addresses (DA) to filter, how are all packets with specified DAs treated?

- A. All packets with specified DAs are dropped.
- B. All packets with specified DAs are dropped based on ingress port.
- C. All packets with specified DAs are dropped based on VLAN membership.
- D. All packets with specified DAs are dropped based on source address intrusion.

Answer: A

More [920-245 Braindumps](#) Information

920-803	922-097	920-250	922-096	920-322
922-093	922-095	920-215	920-331	920-326
920-330	920-481	920-460	920-138	920-160
920-118	920-172	920-251	920-332	920-245

920-332	922-095	920-174	920-254	920-434
920-256	920-340	922-102	922-101	922-093
920-471	920-330	920-344	920-242	922-094
920-146	922-021	920-241	920-260	920-443