



## [Nortel 920-249](#)

**Exam Name:** Nortel Application Switch Ris.23XConfig &Admin

**Q & A :** 68 Q&As

***Pdf Demo***

### **Quality and Value for the 920-249 Exam**

[Just4Exams Practice Exams](#) for Nortel NCSS 920-249 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

### **100% Guarantee to Pass Your 920-249 Exam**

If you do not pass the NCSS 920-249 exam on your first attempt using our Just4Exams **920-249 testing engine and pdf study guide**, we will give you a FULL REFUND of your purchasing fee.

### **Downloadable, Interactive 920-249 Testing engines and PDF Version**

Our Exam Preparation Material provides you everything you will need to take a [NCSS certification](#) examination. Details are researched and produced by [Nortel Certification](#) Experts who are constantly using industry experience to produce precise, and logical.

**Free 920-249 Exams:**

***This is demo only, this pdf do not include the questions and answers picture***

Exam : Nortel 920-249

Title : Nortel Application Switch Ris.23XConfig &Admin

1. Which three commands would be useful when troubleshooting an issue with WCR? (Choose three.)

- A. /cfg/slb/cur
- B. /stats/slb/cur
- C. /info/slb/dump
- D. /info/l3/vrrp/dump
- E. /info/slb/sess/dump

Answer: ACE

2. Which two components use Real Time Streaming Protocol (RTSP) as the delivery media? (Choose two.)

- A. SIP
- B. Real Server
- C. Microsoft Media
- D. QuickTime Server

Answer: BD

3. While performing URL-based load balancing, why might you see a session with a real IP of 0.0.0.0?

- A. The client is refreshing a page.
- B. The switch has been incorrectly configured.
- C. All real servers related to that VIP are down.
- D. The switch has not received sufficient information to make a load balancing decision.

Answer: D

4. Which is the minimum platform requirement for a system with 14 simultaneous fast Ethernet connections and a single fiber connection?

- A. 2208
- B. 2216
- C. 2424SSL
- D. 3408

Answer: B

5. What happens to a WCR filter when all real servers in the associated group fail?

- A. The filter becomes a deny filter.
- B. The filter becomes an allow filter.
- C. The filter is ignored and traffic will be dealt with by the next matching filter.
- D. The backup action specified in the advanced filter menu will be used instead of redirection.

Answer: B

6. For Layer 7 load balancing, where must the sub-string match "/profit" be located in the URL?

- A. inside the first 32 bits
- B. inside the first 64 bytes
- C. immediately following the FQDN
- D. slash not specified in a sub-string match

Answer: C

7. Which two components are required to configure port mirroring? (Choose two.)

- A. a sniffer
- B. a mirror port
- C. a monitor port
- D. a separate license

Answer: BC

8. Each switch filter can be set to only one of four possible choices: allow, deny, and redirect are three of them. Which is the fourth choice?

- A. cloak traffic
- B. stack traffic
- C. disable traffic
- D. translate traffic

Answer: D

9. Which two are valid characteristics of content identifiers, such as URLs. (Choose two.)

- A. They can be of varying lengths.
- B. They have to be of constant lengths.
- C. They can be terminated by VLAN tagging.
- D. They can appear at unpredictable locations within a request.

Answer: AD

10. Which two requirements are necessary for an application switch? (Choose two.)

- A. edge routing
- B. no clustering
- C. session-based traffic management
- D. single point of control for traffic to web components

Answer: CD

11. Which metric is supported in Intrusion Detection System load balancing?

- A. hash
- B. roundrobin
- C. leastconns
- D. response time

Answer: A

12. By default, how are non-GET requests handled in URL based WCR?

- A. dropped
- B. sent to a cache
- C. forwarded to the origin server
- D. load balanced across the cache server group

Answer: C

13. Why is delayed binding necessary when doing URL or content-based switching?

- A. Layer 7 information is not sent in the first packet.
- B. It prevents DOS attacks against web services.
- C. It creates the correct source IP for traffic returning from the realserver.
- D. It creates the correct destination IP for traffic returning from the realserver.

Answer: A

14. Which two settings must be enabled before configuring the Application Switch for Real Time Streaming Protocol (RTSP)? (Choose two.)

- A. proxy IP addressing
- B. Direct Access Mode (DAM)
- C. Virtual Matrix Architecture (VMA)
- D. port-based bandwidth management

Answer: BC

15. What does Virtual Matrix Architecture (VMA) do?

- A. VMA allows filtering to be configured on all physical ports.
- B. VMA allows the switch to process TCP traffic from telnet sessions.
- C. VMA takes individual resources from any back-up switch and utilizes them for load balancing.
- D. VMA makes use of any unused resources within a switch by distributing the workload to multiple processors.

Answer: D

More [920-249 Braindumps](#) Information

#### **Related 920-249 Exams**

|         |         |         |         |         |
|---------|---------|---------|---------|---------|
| 920-803 | 922-097 | 920-250 | 922-096 | 920-322 |
| 922-093 | 922-095 | 920-215 | 920-331 | 920-326 |
| 920-460 | 920-138 | 920-330 | 920-481 | 920-160 |
| 920-118 | 920-172 | 920-251 | 920-233 | 920-249 |

#### **Other Nortel Exams**

|         |         |         |         |         |
|---------|---------|---------|---------|---------|
| 920-462 | 920-362 | 920-173 | 922-058 | 922-090 |
| 920-461 | 920-452 | 920-110 | 920-181 | 920-193 |
| 920-533 | 920-433 | 922-053 | 920-226 | 920-120 |
| 922-100 | 920-537 | 922-021 | 920-330 | 920-449 |