



[Nortel 920-330](#)

Exam Name: Mommunication Server 1000 Ris.5.0 IP Networking Design

Q & A : 60 Q&As

Pdf Demo

Quality and Value for the 920-330 Exam

[Just4Exams Practice Exams](#) for Nortel NCSS 920-330 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

100% Guarantee to Pass Your 920-330 Exam

If you do not pass the NCSS 920-330 exam on your first attempt using our Just4Exams **920-330 testing engine and pdf study guide**, we will give you a FULL REFUND of your purchasing fee.

Downloadable, Interactive 920-330 Testing engines and PDF Version

Our Exam Preparation Material provides you everything you will need to take a [NCSS certification](#) examination. Details are researched and produced by [Nortel Certification](#) Experts who are constantly using industry experience to produce precise, and logical.

Free 920-330 Exams:

This is demo only, this pdf do not include the questions and answers picture

Exam : Nortel 920-330

Title : Mommunication Server 1000 Ris.5.0 IP Networking Design

1. A customer wants to take advantage of the flexibility that a Nortel Solution provides them. They currently have a Communication Server (CS) 1000 Ris. 4.5 network with eight PBX systems connected via IP Peer Networking and the H.323 Protocol. Which three options are valid when migrating the customer's network to SIP trunking between the sites? (Choose three.)

- A. Add SIP Access Port Licenses to each of the existing NRS platforms on the network.
- B. Add SIP Access Ports to each CS 1000 system on the network to enable SIP Trunking.
- C. Enable/configure SIP Redirect/Registrar Services on the existing NRS servers.
- D. Enable/configure the SIP Gateway Services on the CS 1000 Signaling Server system endpoints.
- E. Enable the SIP Proxy Service on each of the CS 1000 Signaling Server Gateways.

Answer: BCD

2. You have been asked to engineer an IP Peer networking solution for a Communication Server (CS) 1000 Rls. 5.0 network. The customer requirements include a centralized numbering plan arrangement using trunks with Transport Layer Security (TLS) enabled. Which components are required as part of this solution for the network? (Choose two.)

- A. SIP Proxy Server
- B. H.323 Gatekeeper
- C. Terminal Proxy Server
- D. Network Routing Service

Answer: AD

3. A customer is deploying a Communication Server 1000E system and has requested that the system be engineered as High Availability. What is required to consider the system High Availability? (Choose two.)

- A. Software package 405
- B. Software package 410
- C. Dual Signaling Servers
- D. Alternate Call Servers with automated database replication
- E. Dual Call Processors using a High Speed Pipe for database synchronization

Answer: BE

4. A company with a Communication Server (CS) 1000M Rls. 5.0 system has IP Peer Networking configured between two offices in the same region. Each office is equipped with one Call Server, one Signaling Server, one Media Gateway 1000, 100 IP Phones, and 20 digital phones. To complete a call from a digital telephone at site A to an IP Phone at site B, at which site will DSP resources be used?

- A. site A only
- B. site B only
- C. both site A and site B
- D. neither site, a Media Card is not required

Answer: A

5. Which statement most accurately describes the function of Element Manager (EM) in a Communication Server (CS) 1000E Rls. 5.0 system for a typical baseline network design?

- A. a telnet application that provides an extension of the OTM interface to support the administration of Branch Office Gateways
- B. a client application that provides an extension of the OTM interface to support the station administration within the Call Server
- C. a software application that provides a web interface to support the administration of system components, including Basic Client Configuration (BCC)
- D. a software application that provides a web interface to support the administration of system components, excluding Basic Client Configuration (BCC)

Answer: C

6. A customer is deploying a new single-site Communication Server (CS) 1000E Standard Availability equipped with a CP-PM Call Server and CP-PM Signaling Server. Which tool is contained in the standard (not optional) new system package?

- A. Element Manager
- B. Telephony Manager
- C. Optivity Telephony Manager
- D. Enterprise Common Manager

Answer: A

7. When considering which CODEC to select for a VoIP, which one is optimal for speech quality but uses the most bandwidth?

- A. G.711
- B. G.723.1
- C. G.729A
- D. G.729B

Answer: A

8. A customer is deploying a Communication Server (CS) 1000E Standard Availability (SA) Rls. 5.0 network. Which network device should you use to create routed VLANs for the VoIP traffic, management, and signaling data?

- A. Shared hub
- B. Layer 2 switch
- C. Layer 3 switch
- D. Signaling Server

Answer: C

9. Which two statements most accurately describe the functions of the Media Gateway Controller (MGC) card in a Communication Server (CS) 1000E RIs. 0 system?

- A. The MGC supports peripheral cards for TDM services.
- B. The MGC provides basic call processing functions for the CS 1000E.
- C. The MGC provides a gateway controller for IP media gateways in the CS 1000E.
- D. The MGC supports PRI/PRI2/DTI/DTI2 trunks, BRI trunks, D-channels and clock controllers.

Answer: CD

10. A customer is migrating from a Meridian 1 Option 61C system to a Communication Server (CS) 1000M SG RIs. 5.0 system. They want to continue to use some of the Meridian 1 digital telephones for existing staff and add IP Phones for new employees. They are concerned that the digital telephones will have difficulty communicating with the IP Phones. Why is this not a problem?

- A. The IP Phone translates voice into data packets for transport using Internet Protocol.
- B. CS 1000M RIs. 5.0 routes the Media Path from the IP Phone to the Terminal Proxy Server that performs the transcoding of the VoIP packets to TDM.
- C. CS 1000M RIs. 5.0 routes the Media Path from the IP Phone to an available port on a Media Card that performs the transcoding of the VoIP packets to TDM.
- D. CS 1000M RIs. 5.0 routes the Media Path through the Terminal Proxy Server to an IP Trunk Card that performs the transcoding of the VoIP packets to TDM.

Answer: C

11. You have been asked to engineer an IP Peer Networking solution for a Communication Server (CS) 1000 RIs. 5.0 network. The customer requirements include a centralized numbering plan arrangement, and they want to use SIP Trunking. What component is required as part of the centralized numbering plan for the network?

- A. Network Connect Service
- B. H.323 Gatekeeper
- C. Terminal Proxy Server
- D. Network Routing Service

Answer: D

12. Which statement most accurately describes the function of the Terminal Proxy Server (TPS) in a Communication Server (CS) 1000E RIs. 5.0 system deployment for a typical single system network design?

- A. The TPS provides web services access to the Call Server.
- B. The TPS provides signaling exchange between an IP Phone and the Signaling Server.
- C. The TPS provides a direct media path between users in the CS domain and users in the SIP domain.
- D. The TPS provides the function of virtual trunk allocation without a physical presence in the hardware.

Answer: B

13. A design engineer needs to assess the network connections for the installation of a Communication Server (CS) 1000E Standard Availability (SA) RIs. 5.0 system. One of the important aspects is having different network ports available for TLAN and ELAN connections. Which hardware component needs access to both a TLAN and an ELAN connection?

- A. Call Server
- B. Signaling Server
- C. Third-party H.323 Gateway
- D. Media Gateway 1000 Chassis

Answer: B

14. A customer is deploying a Communication Server 1000 RIs. 5.0 Standard Availability solution that includes a CP-PM Call Server, a CP-PM Signaling Server, a Media Gateway Controller (MGC), and Media Card. Which Communication Server 1000 RIs. 5.0 hardware component requires an ELAN IP address only?

- A. Media Card
- B. CP-PM Call Server
- C. CP-PM Signaling Server
- D. Media Gateway Controller

Answer: B

15. A company is planning to install a Communication Server 1000E RIs. 5.0 system and wants Web access to perform moves, adds and changes on the telephones. Which service and which platform/Operating System (OS) is required?

- A. Terminal Proxy Service on a CP-PM or COTS server with the VxWorks OS
- B. Enterprise Common Manager running on a COTS server with the LINUX OS
- C. Enterprise Common Manager running on a COTS server with the VxWorks OS
- D. Network Routing Service (NRS) on an ISP 1100 Signaling Server with the VxWorks OS

Answer: B

More [920-330 Braindumps](#) Information

Related 920-330 Exams

920-803	922-097	920-250	922-096	920-322
922-093	922-095	920-215	920-331	920-326
920-330	920-460	920-138	920-481	920-160
920-118	920-172	920-251	920-233	920-249

Other Nortel Exams

920-257	920-131	920-336	920-569	920-463
920-232	920-328	920-363	920-553	920-450
920-171	922-056	920-110	920-259	920-236
920-175	920-134	920-805	920-470	920-130