



[Nortel 920-462](#)

Exam Name: *ncse-ethernet switching (baystack/bps/8600) exam*

Q & A : 56 Q&As

Pdf Demo

Quality and Value for the 920-462 Exam

[Just4Exams Practice Exams](#) for Nortel Other Nortel Certification 920-462 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

100% Guarantee to Pass Your 920-462 Exam

If you do not pass the Other Nortel Certification 920-462 exam on your first attempt using our Just4Exams **920-462 testing engine and pdf study guide**, we will give you a FULL REFUND of your purchasing fee.

Downloadable, Interactive 920-462 Testing engines and PDF Version

Our Exam Preparation Material provides you everything you will need to take a [Other Nortel Certification certification](#) examination. Details are researched and produced by [Nortel Certification](#) Experts who are constantly using industry experience to produce precise, and logical.

Free 920-462 Exams:

This is demo only, this pdf do not include the questions and answers picture

Exam : Nortel 920-462

Title : NCSE-Ethernet Switching (baystack/bps/8600) Exam

1. A customer with a Passport 8300 switch is configuring Remote Access Dial-In User Services (RADIUS) to provide a high degree of security against unauthorized access to the switch. They configured ten RADIUS servers on the client (Passport 8300 switch). What will happen if an authentication request is rejected by the first of five RADIUS servers configured on the switch?

- A. Local authentication is made on the switch itself.
- B. No local authentication is made on the switch itself.
- C. If the first server is unavailable, the Passport 8300 tries the second and so on until it establishes a successful connection.
- D. If the first server rejects the authentication request, the Passport 8300 tries the second and so on until it establishes a successful connection. If all of them reject the request, local authentication is made on the switch itself.

Answer: B

2. You have created a global filter with the following commands: `config ip traffic-filter create source src-ip 10.1.1.1 dst-ip 45.5.1 id 3 config ip traffic-filter filter 3 action mode forward config ip traffic-filter set 303 create name estfilter?`

`FRQILJLSWUDILFILOWHUVHWFUHDWHQDPH ? HVWILOWHU config ip traffic-filter set 303 add-filter 3 config ethernet 1/2 enable-diffserv true config ethernet 1/2 ip traffic-filter create` Which command would be used to add the source filter to port 1/2?

- A. `config ethernet 1/2 ip traffic-filter add set 3`
- B. `config ethernet 1/2 ip traffic-filter add set 303`
- C. `config ethernet 1/2 ip traffic-filter enable set 3`
- D. `config ethernet 1/2 ip traffic-filter add set estfilter? FRQILJHWKHUQHWSWUDILFILOWHUDGGVHW ? HVWILOWHU`

Answer: B

3. Click on the exhibit button. In the exhibits shown, you are required to setup a filter configuration as follows. Forward all http traffic (TCP port 80) directly to the WEB servers using a forward-to-next hop of 10.1.1.1. Forward all VoIP traffic (UDP port 2300-2363) directly to the VoIP servers using a forward-to-next hop of 10.1.1.14. From the partial list of commands in the exhibit, will this configuration meet the requirements listed above?

- A. No, filter 3 is ranging the wrong UDP ports.
- B. No, filter 1 is forwarding to the wrong IP address.
- C. No, filter 2 is should be dropping traffic, not forwarding.
- D. Yes, this configuration matches the requirements listed above.

Answer: D

4. The following commands complete a configuration for traffic filtering on a Passport 8600. missing command `config ip traffic-filter global-set 1 add-filter 1 config ethernet 1/2 enable-diffserv true config ethernet 1/2 ip traffic-filter create config ethernet 1/2 ip traffic-filter add set 1 config ethernet 1/2 ip traffic-filter default-action forward config ethernet 1/2 ip traffic-filter enable` Step one is missing. Which is the missing command?

- A. `config ip traffic-filter filter 1 forward equal`
- B. `config ip traffic-filter traffic-profile 1 info`
- C. `config ip traffic-filter global-set 1 create name gfilter1`
- D. `config ip traffic-filter create global src-ip 10.1.1.2/30 dst-ip 172.1.1.29/30 id 1`

Answer: C

5. Click on the exhibit button. Which commands will configure the labeled Ethernet ports appropriately?

- A. `config ethernet 3/1 enable-diffserv true config ethernet 1/1 access-diffserv true`
- B. `config ethernet 3/1 enable-diffserv true config ethernet 1/1 access-diffserv false`
- C. `config ethernet 1/1,3/1 enable-diffserv true config ethernet 1/1 access-diffserv true`
- D. `config ethernet 1/1,3/1 enable-diffserv true config ethernet 3/1 access-diffserv true`

Answer: C

6. A stock trading firm has just installed a server for online trading. Once a customer requests a stock trade via the Internet, the server must interface with the Stock Exchange via their Passport network, using a protocol which supports authentication, encryption and integrity assurance. Which supported protocol is appropriate for the Passport configuration?

- A. RADIUS Client
- B. RADIUS Server
- C. Secure Shell (SSH) Client
- D. Secure Shell (SSH) Server

Answer: D

7. Click on the exhibit button. A customer wants to use IP Subnet VLANs to provide routing between VLAN 2 and VLAN 3 connected to the BayStack BPS switch, and configure the core port as a Brouter port with RIP. Assuming that this was done correctly, which portion of the PP8600A configuration file identifies the right Brouter configuration?

- A. `ethernet 2/7 ip create 10.1.1.1/255.255.255.252 2090 mac_offset 2 ethernet 2/7 ip rip enable ip rip enable`
- B. `ethernet 2/7 ip create 10.1.20.1/255.255.255.252 2090 mac_offset 2 ethernet 2/7 ip rip enable ip rip enable`
- C. `ethernet 1/48 ip create 10.1.1.1/255.255.255.252 2090 mac_offset 2 ethernet 1/48 ip rip enable ip rip enable`
- D. `ethernet 1/48 ip create 10.1.20.1/255.255.255.252 2090 mac_offset 2 ethernet 1/48 ip rip enable ip rip enable`

Answer: A

8. Click on the exhibit button. Instead of using IP policies and with no router attached to VLAN 2, the following command will enable RIP on PP8600A adding the local interface to the RTM for RIP: `config vlan 2 ip rip enable` Which series of commands will optimally complete this type of RIP configuration on PP8600A shown in the exhibit?

- A. `config vlan 2 ip rip listen enable`

- B. config vlan 2 ip rip supply enable
- C. config vlan 2 ip rip supply enable config vlan 2 ip rip listen enable
- D. config vlan 2 ip rip supply disable config vlan 2 ip rip listen disable

Answer: D

9. A customer wants to configure SNMPv3 on the Passport 8300 switch. SNMPv3 requires a loadable module for the encryption libraries. What does this module contain and how must you modify the config file to load this module?

- A. The module contains keycode and the string oad-module KEY/flash/<key_filename>?must be inserted in config file The module contains keycode and the string ?oad-module KEY/flash/<key_filename>?must be inserted in config file
- B. The module contains SSH algorithm and the string oad-module SSH/flash/<ssh_filename>?must be inserted in config file The module contains SSH algorithm and the string ?oad-module SSH/flash/<ssh_filename>?must be inserted in config file
- C. The module contains DES algorithm and the string oad-module DES/flash/<des_filename>?must be inserted in config file The module contains DES algorithm and the string ?oad-module DES/flash/<des_filename>?must be inserted in config file
- D. The module contains license algorithm and the string icense-module DES/flash/<des_filename>?must be inserted in config file The module contains license algorithm and the string ?icense-module DES/flash/<des_filename>?must be inserted in config file

Answer: C

10. Click on the exhibit button. For the network configuration exhibit provided, the customer has the following requirements: 1. For a source IP address of 10.1.1.1, set DSCP = CS7 (111000) 2. For all http flows (TCP port = 80), set DSCP = AF31 (011010) 3. For all other traffic, set DSCP = AF11 (001010) 4. Configure the ingress port 1-2 as untrusted 5. Configure the egress ports 1-5 and 1-31 as trusted Based on the customer's requirements and the exhibit, regardless of the ingress VLAN on port 1-2 of the Passport 8600, in what order will the DiffServ DSCP be remarked?

- A. AF 11 for all traffic AF31 for traffic from any flow with TCP port number 80 CS7 for traffic from host 10.1.1.1
- B. AF 11 for all traffic CS7 for traffic from host 10.1.1.1 AF31 for traffic from any flow with TCP port number 80
- C. AF31 for traffic from any flow with TCP port number 80 CS7 for traffic from host 10.1.1.1 AF 11 for other flows
- D. CS7 for traffic from host 10.1.1.1 AF31 for traffic from any flow with TCP port number 80 AF 11 for other flows

Answer: D

More [920-462 Braindumps](#) Information

Related 920-462 Exams

922-109	922-101	922-111	922-081	920-457
922-104	922-071	920-110	922-098	920-806
920-805	920-220	920-502	920-569	920-246
920-520	922-094	922-099	920-199	920-197

Other Nortel Exams

920-258	920-220	920-164	920-571	920-452
920-336	920-450	922-102	920-433	920-136
920-140	920-138	920-442	920-431	920-239
920-330	920-324	922-111	920-110	920-316