



Nortel 920-805

Exam Name: Nortel Data Networking Technology

Q & A : 63 Q&As

Pdf Demo

Quality and Value for the 920-805 Exam

[Just4Exams Practice Exams](#) for Nortel Other Nortel Certification 920-805 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

100% Guarantee to Pass Your 920-805 Exam

If you do not pass the Other Nortel Certification 920-805 exam on your first attempt using our Just4Exams **920-805 testing engine and pdf study guide**, we will give you a FULL REFUND of your purchasing fee.

Downloadable, Interactive 920-805 Testing engines and PDF Version

Our Exam Preparation Material provides you everything you will need to take a [Other Nortel Certification certification](#) examination. Details are researched and produced by [Nortel Certification](#) Experts who are constantly using industry experience to produce precise, and logical.

Free 920-805 Exams:

This is demo only, this pdf do not include the questions and answers picture

Exam : Nortel 920-805

Title : Nortel Data Networking Technology

1. Which statement about broadcast domains and collision domains is false?

- A. When a connection is Ethernet full-duplex, the collision domain only contains two devices.
- B. When a connection is Ethernet full-duplex, the broadcast domain only contains two devices.
- C. When a hub is used to connect devices, all ports are in the same collision domain but not in the same broadcast domain.
- D. When a switch with multiple VLANs is used to connect devices, all ports are in the same broadcast domain.

Answer: B

2. Equal Cost MultiPath (ECMP) provides the ability to load-balance Layer 3 links and also to provide redundancy. When ECMP is

enabled, which set of criteria initiates its use?

- A. OSPF and RIP have no overlapping network advertisements.
- B. OSPF or RIP have learned duplicate routes with the same cost or metric.
- C. OSPF and RIP have identical network advertisements with the same cost.
- D. OSPF and RIP are used in parallel with network advertisements with different costs.

Answer: B

3. Which function do Route policies on the Ethernet Routing Switch (ERS) perform?

- A. Route policies can flush and clear the IP routing table.
- B. OSPF redistribute function is used to propagate OSPF routes within a single area.
- C. RIP announce policies determine how RIP learned routes are represented in the routing table.
- D. BGP redistribute function may be used to advertise OSPF learned routes using BGP.

Answer: D

4. You are configuring a static route on an Ethernet Routing Switch (ERS). Which parameter must you specify? A.an IP address for device management purposes B.an interface IP address in the routing table for loop back C.an interface IP address of the next-hop router as a destination in the routing table D.an IP address for a network to be listed in the routing table by the network manager You are configuring a static route on an Ethernet Routing Switch (ERS). Which parameter must you specify?

- A. an IP address for device management purposes
- B. an interface IP address in the routing table for loop back
- C. an interface IP address of the next-hop router as a destination in the routing table
- D. an IP address for a network to be listed in the routing table by the network manager

Answer: D

5. A corporation has decided to save money and buy remanufactured IP telephones. They purchased Phase 1 (One) IP telephones that do not support Power-over-Ethernet (PoE). The Ethernet Switches they purchased do supply PoE per the IEEE 802.3af specifications. Which statement regarding the Phase 1 IP telephones is true?

- A. They must be plugged into AC power outlets to function.
- B. They can use a power splitter to receive both power and data from the Ethernet Switch.
- C. They can use a power splitter to receive both power and data from the Ethernet Switch, but must also be attached to an AC outlet to boot and acquire an IP address.
- D. They must be plugged into AC power outlets to boot and acquire an IP address. After the telephone is operating, it can operate off the Ethernet Switch only.

Answer: B

6. An Ethernet Routing Switch is building the routing table using default route precedence values. As it considers routes from various sources, which set of criteria does the routing table use to build its information?

- A. All sources are considered in a Weighted Round Robin order.
- B. RIP routes are considered at a higher precedence value than OSPF.
- C. OSPF routes have a lower precedence value than Static routes.
- D. BGP routes are always listed first and most important in the IP Routing Table.

Answer: B

7. A manufacturing company is building a new plant. The equipment in the plant has been known to cause interference with the network at other sites and they want to be sure that they choose a media that is resistant to electrical interference. Which type of cable should they use?

- A. thick coaxial cable
- B. fiber optic cable
- C. unshielded twisted pair
- D. plenum twisted pair

Answer: B

8. A department was moved from one floor to another. When the department was on the old floor, the users connected through a mixture of 10 Mb hubs and 10/100 Mb switches. When the department was moved all the hubs were replaced by 10/100 Mb switches.

Two of the users are reporting that the network is much slower on the new floor even though the hubs were replaced. You discover that the switch ports these users connect to were used to connect to the hubs and are manually configured for 10Mb half-duplex. The PCs were connected to the switch and were manually configured for 100 Mb full-duplex.

What could have been done to avoid this issue?

- A. Auto-negotiation only needed to be enabled on the switch.
- B. Auto-negotiation should have been enabled on the switch ports and on the PCs.
- C. Auto-sensing only needed to be enabled on the switch.

D. Auto-sensing should have been enabled on the switch ports and on the PCs.

Answer: B

9. You are designing a large network and are using Open Shortest Path First (OSPF) for its efficiency with convergence times and its amount of traffic control. Which statement describes how OSPF accomplishes this?

- A. The metric is dynamic for each link.
- B. The metric is independent of the link speed.
- C. The metric reflects the link speed.
- D. The metric is the same regardless of link speed.

Answer: C

10. Which order is correct for these components in the Ethernet frame?

- A. destination MAC address, source MAC address, length/type field, data, FCS
- B. destination MAC address, source MAC address, data, length/type field, FCS
- C. source MAC address, destination MAC address, length/type field, data, FCS
- D. source MAC address, destination MAC address, data, length/type field, FCS

Answer: A

More [920-805 Braindumps](#) Information

Related 920-805 Exams

922-109	922-101	922-111	922-081	920-457
922-104	922-071	920-110	922-098	920-806
920-805	920-220	920-502	920-569	920-246
920-520	922-094	922-099	920-199	920-197

Other Nortel Exams

920-806	922-041	922-109	922-054	920-316
920-322	920-448	920-234	920-341	922-060
920-255	920-355	920-196	920-453	922-102
922-081	922-100	920-247	920-107	920-533