



[Apple 9L0-005](#)

Exam Name: Apple Desktop Service Certification Exam

Q & A : 82 Q&As

Pdf Demo

Quality and Value for the 9L0-005 Exam

[Just4Exams Practice Exams](#) for Apple ACPT 9L0-005 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

100% Guarantee to Pass Your 9L0-005 Exam

If you do not pass the ACPT 9L0-005 exam on your first attempt using our Just4Exams **9L0-005 testing engine and pdf study guide**, we will give you a FULL REFUND of your purchasing fee.

Downloadable, Interactive 9L0-005 Testing engines and PDF Version

Our Exam Preparation Material provides you everything you will need to take a [ACPT certification](#) examination. Details are researched and produced by [Apple Certification](#) Experts who are constantly using industry experience to produce precise, and logical.

Free 9L0-005 Exams:

This is demo only, this pdf do not include the questions and answers picture

Exam : APPLE 9L0-005

Title : Apple Desktop Service Certification Exam

1. Where is the BEST place to look for information regarding special take-apart tools for an Apple product?

- A. Discussions
- B. Service News
- C. User's manual
- D. Service manual

Answer: D

2. Which of the following tools is required to open a Mac mini?

- A. Torque screwdriver

- B. 5 mm hex nut driver
- C. CRT discharge tool
- D. Torx T-15 screwdriver
- E. Sharpened putty knife

Answer: E

3. A Mac mini displays a flashing question mark at startup. Which step does Apple recommend you take FIRST?

- A. Replace the logic board.
- B. Try to start up from a bootable CD or DVD.
- C. Reinitialize the hard disk and reinstall the Mac OS.
- D. Replace the internal hard drive with a known-good hard drive.

Answer: B

4. According to Apple service manuals, what steps should you take before performing any take-apart steps when replacing a part in any Apple product?

- A. Disconnect and reconnect all internal cables.
- B. Lay the product on its side so it will not fall over.
- C. Discharge the CRT and establish an ongoing ground.
- D. Gather all necessary tools and perform all preliminary steps.
- E. Order all available service parts for the appropriate configuration of the product.

Answer: D

5. Examine the exhibit. Is this the correct tool to remove the bezel on the iMac (Early 2006)?

- A. Yes
- B. No

Answer: A

6. Which of the following can permanently damage an LCD display?

- A. Rubbing the display.
- B. Using a screen saver.
- C. Not using a screen saver.
- D. Turning brightness up too high.

Answer: A

7. ESD causes damage to circuits by _____.

- A. slowing the circuit down
- B. cooling the circuit too quickly
- C. blasting a hole in the circuit
- D. increasing the circuit's clock speed

Answer: C

8. Which of the following is NOT a good step to take when working onsite on a computer?

- A. Place parts on the floor.
- B. Use a grounded ESD mat.
- C. Wear a grounded ESD wrist strap.
- D. Check the polarity of the grounded power outlet.

Answer: A

9. You require additional information about a specific problem with a customer's Power Mac G5. Which one of the following resources is the Apple-recommended choice for researching the problem?

- A. Downloads
- B. Discussions
- C. User's manual
- D. Knowledge Base

Answer: D

10. A customer needs to transfer data from her eMac for use on her Power Mac G5, but the eMac fails to finish starting up due to a video issue. Which of the following would most easily accomplish the data transfer?

- A. Remove the hard drive from the eMac and install it into the Power Mac G5.
- B. The eMac will need to be repaired before any data can be recovered from it.
- C. Boot the eMac into Mac OS X Safe Mode and connect the eMac and Power Mac G5 with an Ethernet cable.

D. Boot the eMac into Target Disk Mode and connect the eMac and Power Mac G5 with a FireWire cable.

Answer: D

11. "In Apple Hardware Test, what does an error code of ""mem_X/X"" signify?

- A. It signifies that memory should be replaced.
- B. It signifies that all memory slots are occupied.
- C. It signifies that test results have been memorized.
- D. It signifies that Apple Hardware Test requires more memory.

Answer: A

12. Which section of the Power Mac G5 Service manual is the BEST place to look for instructions for replacing a processor?

- A. Views
- B. Basics
- C. Take Apart
- D. Troubleshooting

Answer: C

13. You have just completed replacing a logic board in an iMac (Flat Panel) and are reassembling the computer. Which of the following special tools is recommended during this reassembly?

- A. CRT discharge tool
- B. Torque screwdriver
- C. Spring tensioning tool
- D. Jumper adjustment tool

Answer: B

14. Which FOUR of the following actions helps reduce the risk of damage from ESD? SELECT FOUR

- A. Ground yourself and the equipment you are working on.
- B. Always place ESD-sensitive components on metal surfaces.
- C. Handle all ESD-sensitive boards by the connectors, not the edges.
- D. Use static-shielding storage bags for ESD-sensitive components.
- E. Do not touch anyone who is working on ESD-sensitive components.
- F. Do not bring plastic, vinyl, or foamed polystyrene near ESD-sensitive components.

Answer: ADEF

15. Which of the following is the format used to describe a version of Apple diagnostic software used with PowerPC Macs?

- A. 3S107
- B. 2.5.8

Answer: B

16. Which of the following is the format used to describe a version of Apple diagnostic software used with Intel Macs?

- A. 3S107
- B. 2.5.8

Answer: A

17. Which THREE of the following items are appropriate to use for ESD prevention? SELECT THREE

- A. Metal work surface
- B. CRT discharge tool
- C. Grounded work mat
- D. Wrist strap and cord
- E. Static-shielding bags

Answer: CDE

18. A customer asks about RAM speed requirements to upgrade his eMac (USB 2.0). What Apple resource should you refer this customer to?

- A. Downloads
- B. Discussions
- C. User's manual
- D. Service manual

Answer: C

19. The fans inside a customer's Power Mac G5 seem to constantly run at full speed after a repair involving logic board replacement. What

should be done FIRST to correct this problem?

- A. Replace the processor(s).
- B. Run Apple Service Diagnostic.
- C. Replace the fans inside the Power Mac G5.
- D. Replace the Power Mac G5 logic board again.

Answer: B

20. You are troubleshooting an eMac system that has Mac OS X. The icon of a connected external FireWire drive is not appearing on the Finder Desktop. Which of the following would be MOST useful in troubleshooting this issue?

- A. Terminal
- B. Network Utility
- C. Process Viewer
- D. System Profiler
- E. Apple Hardware Test

Answer: D

More [9L0-005 Braindumps](#) Information

Related 9L0-005 Exams

9L0-061	9L0-006	9L0-005	9L0-060	9L0-030
9L0-206	9L0-207	9L0-620	9L0-004	

Other Apple Exams

9L0-007	9L0-827	9L0-030	9L0-613	9L0-609
9L0-612	9L0-614	9L0-005	9L0-401	9L0-061
9L0-207	9L0-610	9L0-006	9L0-621	9L0-929
9L0-509	9L0-508	9L0-206	9L0-403	9L0-507