



EMC E20-520

Exam Name: *calriion solutions specialist exam*

Q & A : 497 Q&As

Pdf Demo

Quality and Value for the E20-520 Exam

[Just4Exams Practice Exams](#) for EMC Specialist E20-520 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

100% Guarantee to Pass Your E20-520 Exam

If you do not pass the Specialist E20-520 exam on your first attempt using our Just4Exams **E20-520 testing engine and pdf study guide**, we will give you a FULL REFUND of your purchasing fee.

Downloadable, Interactive E20-520 Testing engines and PDF Version

Our Exam Preparation Material provides you everything you will need to take a [Specialist certification](#) examination. Details are researched and produced by [EMC Certification](#) Experts who are constantly using industry experience to produce precise, and logical.

Free E20-520 Exams:

This is demo only, this pdf do not include the questions and answers picture

Exam : EMC E20-520

Title : CALRiiON Solutions Specialist Exam

1. On which two [2] devices can Navisphere Management Server be installed?

- A. A CX400 Array
- B. An FC4500 Array
- C. A Solaris Workstation
- D. A Windows Workstation

Answer: AD

2. Where is the user notification information for Event Monitor stored?

- A. agent.cfg

- B. event.cfg
- C. navimon.cfg
- D. agent.config

Answer: C

3. What is the communication link between the VisualSRM console and a managed node?

- A. FCIP
- B. HTTP
- C. ODBC
- D. TCP/IP

Answer: D

4. Which phrase describes Access Logix?

- A. Host masking via switch zoning
- B. LUN masking via switch zoning.
- C. LUN masking via storage groups
- D. Enabling host access to FC switch

Answer: C

5. What must occur before the write operation is acknowledged to the host in normal MirrorView operation?

- A. Link status must be checked
- B. Fracture Log must be updated
- C. Write is acknowledged on secondary array
- D. Write Intent Log must be enabled for the Primary LUN

Answer: C

6. What are three [3] types of MirrorView topologies?

- A. SAN Connect
- B. iSCSI Connect
- C. Direct Connect
- D. WAN Connect (MirrorView over IP)

Answer: ACD

7. In what way does the CX Series improve upon the FC Series arrays?

- A. Introduction of 2Gb front-end ports
- B. Can hold more disk drives in less space
- C. Native Support for Single Mode Fibre Cable
- D. Employs switched back-end for increased bandwidth

Answer: B

8. Which CLARiiON can have the most concurrent SAN Copy sessions activated?

- A. CX300
- B. CX400
- C. CX500
- D. CX700

Answer: D

9. What are two [2] characteristics of DMP and PowerPath?

- A. PowerPath must be deactivated using vxdiskadm.
- B. Suppression of DMP is a menu item within vxdiskadm.
- C. DMP needs special code to map CLARiiON's passive path.
- D. DMP and PowerPath must be running together on the same host.

Answer: BC

10. What are three [3] attributes of a Clone Private LUN?

- A. Contains Fracture Logs.
- B. Contains Write Intent Logs
- C. Must be 128MB, or greater, in size.
- D. Is assigned to one storage processor.
- E. Shared by both storage processors simultaneously.

Answer: ACD

11. A Windows host is connected to a CX500 array through a SAN. One HBA is zoned to SP A port 0 and SP B port 1. The other HBA is zoned to SP B port 0 and SP A port 1. How many entries for this host should appear in the Connectivity Status window in Navisphere Manager?

- A. 1
- B. 2
- C. 4
- D. 8

Answer: C

12. What three [3] activities does Navisphere Analyzer perform?

- A. Examine past data
- B. Examine real-time data
- C. Examine data on HDS arrays
- D. Find bottlenecks and hotspots
- E. Create future projection charts

Answer: ABD

13. What are three [3] characteristics of Event Monitor?

- A. Integrated with Navisphere manager
- B. Monitors for user-configurable events
- C. Loaded as a separately purchased NDU
- D. Event Monitor is part of Navisphere Agent
- E. Monitors only for Navisphere defined events

Answer: ABD

14. Which two [2] CLARiiON arrays do not support the installation of SAN Copy?

- A. CX200
- B. CX300
- C. CX400
- D. CX500
- E. CX600
- F. FC4700

Answer: AB

15. Which SAN Copy menu option is used to monitor the progress of a copy session?

- A. Status
- B. Resume
- C. Properties
- D. Ownership

Answer: A

16. When entering a Navisphere CLI command, which variable specifies the CX-Series Storage Processor that will accept the command?

- A. -h [hostname]
- B. -d [devicepath]
- C. -sp [storage processor]
- D. -ip [ip address of storage processor]

Answer: A

17. Which EMC product helps identify when storage capacity on a host will run out?

- A. VisualSAN
- B. VisualSRM
- C. Navisphere Manager
- D. Navisphere Analyzer

Answer: B

18. Before Snapshots can be created, one or more LUNs must be configured in which way?

- A. added to the private LUN storage group
- B. as a snapshot cache pool shared by both SPs
- C. for each SP which manages snapshot sessions
- D. added to the same storage group as the source LUN

Answer: C

19. The LUN alignment offset feature on the CLARiiON and the diskpar.exe in Windows are both useful for correctly partitioning Windows drives to accommodate the MBR. When would you not use the LUN alignment offset feature on the CLARiiON, and would use diskpar.exe instead?

- A. When formatting the Windows drive as NTFS, since the MBR is not a factor on NTFS drives.
- B. When using layered CLARiiON applications as they operate on the Raw LUN and as such would incur disk crossings.
- C. When directly attaching a Windows host to the CLARiiON, as the LUN alignment offset is only available in AccessLogix.
- D. When LUNs are configured on a RAID 1/0 group. The mirrored drive doesn't accommodate LUN Alignment Offset and requires diskpar.exe.

Answer: B

20. What three [3] ways can a SnapView Clone be used?

- A. Offload source LUN during a backup process.
- B. Restoration of data when source LUN is corrupted.
- C. Creating Clones of Snapshot LUN for report generation.
- D. Performance tuning by moving data to a LUN on another RAID Group.
- E. Allow multiple hosts to have read/write access to same data on the source LUN

Answer: ABD

21. How would you find the Navisphere Analyzer options in the Navisphere Manager GUI?

- A. Click File, then Options, then Analyzer.
- B. Expand the desired array and then expand the Analyzer tab.
- C. Right click the desired array and then select Analyzer from the menu.
- D. Enter Engineering Mode, then select Analyzer from the Engineering Mode menu.

Answer: C

22. What are three [3] best practices for configuring LUNs on a Solaris host?

- A. Zone only one SP per HBA.
- B. Use storage array based RAID.
- C. Leave element size as CLARiiON default.
- D. Use only DMP in single HBA environments.
- E. Base RAID type on access pattern and application.

Answer: BCE

23. Which statement describes The Copy-on-First-Write mechanism in SnapView?

- A. Utilized on SnapView Clone, enhances performance
- B. Utilized on SnapView Clone, decreases performance
- C. Utilized on SnapView Cache LUN, decreases performance
- D. Utilized on SnapView Cache LUN, it enhances performance

Answer: C

24. Which three [3] options can be configured in the Create RAID Group dialogue box?

- A. RAID Type
- B. RAID Group ID
- C. Expansion Rate
- D. Enable Write Cache
- E. Manual Disk Selection

Answer: BCE

25. Which task(s) can a VisualSRM "reporting" user perform?

- A. View exported reports
- B. Manually run and export reports
- C. Create and view custom reports
- D. Manually run and schedule reports

Answer: A

26. What two [2] functions are disabled when PowerPath is installed without a license key?

- A. Failover
- B. Multipathing
- C. Load balancing

D. Access to peer SP paths

Answer: BC

27. Where are the WWPN's of SPA's ports located in Navisphere Manager?

- A. Storage Tab, SP A, Port Item
- B. Storage Tab, right-click SP A, Properties, Port Name Tab
- C. Storage Tab, Physical Tree, Enclosure SPE Tree, SPs Tree, SP A, Port Item
- D. Storage Tab, Physical Tree, Enclosure DPE Tree, SPs Tree, SP A, Port Item

Answer: D

28. Where must read cache be enabled for optimal host I/O?

- A. In FLARE and on both Storage Processors
- B. On the LUN and on both Storage Processors
- C. On the LUN and on the CLARiiON vault drives
- D. In FLARE and on the Storage Processor that owns the LUN

Answer: B

29. What is the SAN Copy "Session Throttle" parameter used for?

- A. Enabling or disabling the rate of I/O transfers.
- B. Controlling the I/O rate for an active SAN Copy session.
- C. Setting the maximum blocksize of the SAN Copy transfers.
- D. Balancing the SAN Copy session between storage processors.

Answer: B

30. How is the MirrorView Fracture Log configured?

- A. Bind at least one unused LUN
- B. Make sure LUNs are at least 128MB
- C. The Fracture Log is automatically configured
- D. Allocate SP Memory in the Memory tab of the Primary Storage System

Answer: C

More [E20-520 Braindumps](#) Information

Related E20-520 Exams

E20-520	e20-522	E20-381	e20-532	e20-510
e20-530	e20-580	e20-320	E20-522	

Other EMC Exams

e20-360	E20-616	E20-340	e20-535	e20-870
E20-475	e20-670	E20-351	e20-597	E20-597
E20-501	e20-380	E20-517	E20-405	e20-012
e20-661	E20-331	e20-522	e20-330	E20-591