



[HP HP0-239](#)

Exam Name: *Supporting the Modular Array(MA) Storage Family*

Q & A : 68 Q&As

Pdf Demo

Quality and Value for the HP0-239 Exam

[Just4Exams Practice Exams](#) for HP Certification III HP0-239 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

100% Guarantee to Pass Your HP0-239 Exam

If you do not pass the Certification III HP0-239 exam on your first attempt using our Just4Exams ***HP0-239 testing engine and pdf study guide***, we will give you a FULL REFUND of your purchasing fee.

Downloadable, Interactive HP0-239 Testing engines and PDF Version

Our Exam Preparation Material provides you everything you will need to take a [Certification III certification](#) examination. Details are researched and produced by [HP Certification](#) Experts who are constantly using industry experience to produce precise, and logical.

Free HP0-239 Exams:

This is demo only, this pdf do not include the questions and answers picture

Exam : HP HP0-239

Title : Supporting the Modular Array(MA) Storage Family

1. Which utility is used to load a patch for the ACS firmware?

- A. CLCP
- B. FMU
- C. CLONE
- D. CONFIG

Answer: A

2. The RA8000 CLI command INITIALIZE initializes ____.

- A. metadata only

- B. metadata and user data areas
- C. user data areas only
- D. the NVRAM of the HSG80 controller

Answer: A

3. An MA8000 has been operating in a single controller configuration. You added a second HSG80 controller for redundancy and started a CLI session through the serial port of the new (lower) controller. Which command do you use to include the new controller into the existing configuration?

- A. SET FAILOVER COPY=THIS_CONTROLLER
- B. SET MULTIBUS_FAILOVER=THIS_CONTROLLER
- C. SET FAILOVER COPY=OTHER_CONTROLLER
- D. SET MULTIBUS_FAILOVER=OTHER_CONTROLLER

Answer: C

4. Which ACS Version is required to run DRM?

- A. 8.7D
- B. 8.7F
- C. 8.7P
- D. 8.7S

Answer: C

5. Which cache module does the bottom controller use?

- A. configurable
- B. always left
- C. left only if the right slot is empty
- D. always right

Answer: D

6. You want to remotely configure an HSG80 controller. Before the first remote connection can be established, you must establish a local connection and ____.

- A. create a CCL (command console LUN)
- B. configure the node ID
- C. set the correct time and date
- D. set the correct port topology

Answer: A

7. How many HSG controllers are supported in an M2200 enclosure?

- A. 2
- B. 4
- C. 6
- D. 22

Answer: A

8. In Transparent Failover mode, unit D102 with no preferred path is presented through port ____.

- A. 2 on the bottom controller
- B. 2 on both controllers
- C. 1 on both controllers
- D. 1 on the top controller

Answer: A

9. A model 4300 drive enclosure with a single power supply contains ____ blowers.

- A. 1
- B. 2
- C. 3
- D. 4

Answer: B

10. Which command is used to view the available utilities offered by the ACS firmware?

- A. LIST
- B. DIRECTORY
- C. VIEW UTILITIES

D. SHOW UTILITIES

Answer: B

11. You have connected port 1 of the upper HSG80 controller to an FC switch and opened a terminal session through the serial port of the same controller. Which CLI command do you use to establish the correct topology on port 1?

- A. SET PORT_1 TOPOLOGY=LOOP
- B. SET THIS_CONTROLLER PORT_1_TOPOLOGY=FABRIC
- C. SET PORT_1_TOPOLOGY=FABRIC
- D. SET THIS_CONTROLLER TOPOLOGY=1

Answer: B

12. What do you enter at the CLI prompt to configure a CCL (command console LUN) on your HSG80 controller which will be fixed to LUN 0?

- A. SET THIS_CONTROLLER SCSI_VERSION=SCSI-2
- B. SET SCSI_VERSION=SCSI-2
- C. SET D0 SCSI_VERSION=SCSI-3
- D. SET THIS_CONTROLLER SCSI_VERSION=SCSI-3

Answer: D

13. When the CONFIG utility is used after a physical disk was moved from one drive bay to another, the moved disk will be ____.

- A. rediscovered and added to the spareset
- B. rediscovered and reassigned to the storageset
- C. added to the controller configuration with a new name and deleted with the old name
- D. added to the controller configuration with a new name and the old name will not be removed from the controller configuration

Answer: D

14. Which SWCC menu selection sequence is likely to cause customer data loss?

- A. Storage, Controller Configuration, Open
- B. Storage, Controller Configuration, Save
- C. Storage, Controller Configuration, Load
- D. Storage, Controller Configuration, Restart

Answer: C

15. Which ACS versions support cloning?

- A. 8.7G, 8.7F, 8.7S, 8.7L and 8.7P only
- B. 8.7G, 8.7F and 8.7S only
- C. 8.7G and 8.7F only
- D. 8.7G and 8.7L only

Answer: A

More [HP0-239 Braindumps](#) Information

Related HP0-239 Exams

HP0-S16	HP0-D04	HP0-J26	HP0-P13	HP0-M23
HP0-918	HP0-M28	HP0-S14	HP0-920	HP0-265
HP0-263	HP0-239	HP0-084	HP0-266	HP0-085
HP0-205	HP0-071	HP0-080	HP0-286	HP0-207

Other HP Exams

HP2-896	HP0-045	HP0-083	HP0-302	HP0-093
HP0-773	HP0-782	HP0-S11	HP2-K14	HP0-064
HP0-J20	HP0-727	HP0-J18	HP0-509	HP0-725
HP0-053	HP0-815	HP0-S16	HP0-648	HP0-245