



HP HP0-633

Exam Name: NNM II(7.x) Customization

Q & A : 78 Q&As

Pdf Demo

Quality and Value for the HP0-633 Exam

[Just4Exams Practice Exams](#) for HP Certification II HP0-633 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

100% Guarantee to Pass Your HP0-633 Exam

If you do not pass the Certification II HP0-633 exam on your first attempt using our Just4Exams **HP0-633 testing engine and pdf study guide**, we will give you a FULL REFUND of your purchasing fee.

Downloadable, Interactive HP0-633 Testing engines and PDF Version

Our Exam Preparation Material provides you everything you will need to take a [Certification II certification](#) examination. Details are researched and produced by [HP Certification](#) Experts who are constantly using industry experience to produce precise, and logical.

Free HP0-633 Exams:

This is demo only, this pdf do not include the questions and answers picture

Exam : HP HP0-633

Title : NNM II (7.x) Customization

1. Which event should you configure to be forwarded from a collection station to a management station?

- A. threshold events from data collection
- B. node status events from netmon
- C. connectorDown events created by ECS
- D. node added and deleted events from netmon

Answer: A

2. What are the steps to manage distributed data collection files so you can view a single report from the management station?

- A. copy the raw files to the management station, export them to the data warehouse using ovcultosql

- B. export the data to the data warehouse on the collection station using ovcoltosql, replicate to the management station
- C. from the management station, run odwtrend -export pointing to the files on the collection station
- D. run odwtrend -export on the collection station pointing to the data warehouse on the management station

Answer: A

3. You want to do trend analysis in your distributed management environment and always be able to see the most recent six months of data from your management station. What is the architecture of your data collection?

- A. Configure each collection station to monitor the data, store the data, and send reports to the management station?
- B. Configure each collection station to monitor the data, upload the data to the management station, and create reports at the management station.
- C. Configure collection at the collection station and have NNM automatically synchronize data back to the management station for reporting.
- D. Configure collection at the management station and it automatically partitions collection and assigns it to the nearest collection station.

Answer: B

4. To enable a Problem Diagnosis probe to report to multiple servers, you can _____.

- A. configure the probe in the configuration file of each server
- B. configure the probe to monitor the path to each server
- C. initiate a trek using the probe to add it to servers automatically
- D. configure all the server names in the probe configuration file

Answer: A

5. What are the best items to place in a failover filter? Select TWO.

- A. critical servers
- B. desktop workstations
- C. remote collection stations
- D. local collection stations
- E. connector devices
- F. DHCP devices

Answer: AE

6. During normal processing, you have automatic failover configured on a management station for a collection station. Which overlap mode is most efficient?

- A. AllowOverlap keeps active copies of all objects at the management station so failover takes the least processing.
- B. UnmanageSecondary holds a space for each object so failover takes less time.
- C. DeleteSecondary frees the most space and processing time on the management station, and failover handles the rare occurrence where the collection station goes down.
- D. NoOverlap allows the management station to discontinue monitoring the objects.

Answer: C

7. Which function does a topology filter perform?

- A. It directly eliminates topology objects from a map.
- B. It prevents topology objects from being locally discovered.
- C. It affects the topology view exported by a collection station.
- D. It dictates a particular topology object be resident on a particular map.

Answer: C

8. Your management station manages a domain of its own in addition to receiving information from a remote collection station. You just got a large bill from your WAN provider for last month when your remote collection station went down. How can you avoid that in the future? Select TWO.

- A. Configure overlapping domains so the management station will not have to resynchronize everything.
- B. Configure a failover filter to minimize management station polling.
- C. Add a backup collection station at the remote location to manage the remote domain redundantly.
- D. Configure the -nosynchronize option to allow natural updating of the management station when a collection station returns to normal operation.

Answer: BC

9. How long does a management station take to recognize that a collection station is down and to initiate failover polling?

- A. 5 minutes
- B. 20 minutes
- C. 4 polling cycles

D. One failed poll

Answer: C

10. What must be true for a management station to implement failover of a collection station?

- A. The collection station must have a failover filter in place.
- B. The management station must have access to the monitored objects.
- C. At least two collection stations must have been reporting on the objects.
- D. The management station must have its overlap mode set to DeleteSecondary.

Answer: B

11. You have configured a topology filter on a collection station so only connector devices are uploaded to the management station. You have also configured threshold events to be forwarded to the management station. When a server violates a threshold, what appears in the Alarm Browser on the management station?

- A. the server threshold alarm from the collection station
- B. no alarm appears
- C. a warning from the collection station that a threshold has been violated on an un-replicated node
- D. the server threshold alarm generated by the management station

Answer: A

12. The difference between an NNM Advanced Edition collection station and an NNM Advanced Edition management station is that on the collection station _____.

- A. only the collecting software is installed
- B. only the collecting processes are running
- C. the replication process is running
- D. the replication process is not running

Answer: D

13. By default, how does data get from Problem Diagnosis probes to the server?

- A. they maintain a TCP connection with a heartbeat
- B. through an HTTP upload
- C. the probe stores data until the server sends a request
- D. the probe packs the data in an OV event

Answer: B

14. To improve bandwidth utilization in DIM, you could _____.

- A. force a complete synchronization every morning using nmdemandpoll so data is more accurate for the rest of the day
- B. stop and restart the collection station on a regular schedule to re-establish a clean link
- C. avoid restarting the management station
- D. configure ovtopmd.lrf with the -minTopo parameter so less data is uploaded

Answer: C

15. How do you unlink a Problem Diagnosis server from a remote probe?

- A. From Problem Diagnosis view, select the probe from the list and [Delete].
- B. Edit pdconfig.xml and remove the <Probe> block.
- C. Execute pdconfig.ovpl -unlink on the server.
- D. Edit nprobe.conf and remove the server name.

Answer: B

More [HP0-633 Braindumps](#) Information

Related HP0-633 Exams

HP0-461	HP0-704	HP0-727	HP0-634	HP0-655
HP0-664	HP0-661	HP0-517	HP0-662	HP0-698
HP0-719	HP0-449	HP0-703	HP0-702	HP0-671
HP0-660	HP0-601	HP0-633	HP0-656	HP0-460

Other HP Exams

HP0-238	HP0-P22	HP0-922	HP2-B11	HP0-891
HP0-782	HP0-633	HP0-919	HP0-J24	HP0-P12
HP0-092	HP0-J17	HP0-J27	HP0-S17	HP0-273
HP0-S12	HP0-710	HP0-J32	HP0-791	HP0-D01