



HP HP0-648

Exam Name: Adaptive EDGE Fundamentals

Q & A : 71 Q&As

Pdf Demo

Quality and Value for the HP0-648 Exam

[Just4Exams Practice Exams](#) for HP HP AIS Certification II HP0-648 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

100% Guarantee to Pass Your HP0-648 Exam

If you do not pass the HP AIS Certification II HP0-648 exam on your first attempt using our Just4Exams **HP0-648 testing engine and pdf study guide**, we will give you a FULL REFUND of your purchasing fee.

Downloadable, Interactive HP0-648 Testing engines and PDF Version

Our Exam Preparation Material provides you everything you will need to take a [HP AIS certification Certification II certification](#) examination. Details are researched and produced by [HP Certification](#) Experts who are constantly using industry experience to produce precise, and logical.

Free HP0-648 Exams:

This is demo only, this pdf do not include the questions and answers picture

Exam : HP HP0-648

Title : ProCurve Adaptive Edge Fundamentals

1. While troubleshooting a network outage, you decide to examine the Event log of an HP ProCurve Switch 5348xl. Identify the command that filters reports of normal behavior from the console display.

- A. console events -n
- B. console events critical
- C. console events not-info
- D. console events -c

Answer: C

2. How does an IP host determine which destination addresses are local and which are remote?
- A. The host derives a range of local addresses by applying its configured subnet mask to its own IP address.
 - B. The host broadcasts an ICMP request to its local router and requests a hop-by-hop path.
 - C. The host broadcasts an ICMP request to all routers in the enterprise and requests a hop-by-hop path.
 - D. The host creates and maintains a table that lists remote address ranges and the next hop router for each range.

Answer: A

3. You have configured port a1 on an HP ProCurve switch as an untagged member of VLAN 20. The port is not a member of any other VLANs. Which statement describes an action the switch takes when forwarding a frame through port a1?
- A. The switch adds a tag that will be interpreted by the device connected to that port.
 - B. The switch strips any tag that may have been included with the frame when it was received.
 - C. HP switches require tagged status on all ports.
 - D. The switch changes the VLAN ID of any tag to 20.

Answer: B

4. A network administrator asks you about the differences in the discovery features of HP ProCurve Manager and HP ProCurve Manager Plus. Which statement describes these differences?
- A. There is no difference between the discovery processes used by the two applications.
 - B. HP ProCurve Manager Plus enables the scheduling of auto-discovery. HP ProCurve Manager requires users to initiate discovery manually.
 - C. HP ProCurve Manager Plus will discover devices from manufacturers other than HP. HP ProCurve Manager will discover only ProCurve devices.
 - D. HP ProCurve Manager Plus supports discovery based on CDP and FDP. HP ProCurve Manager does not support discovery based on FDP.

Answer: A

5. You are installing a new HP ProCurve switch at a customer site. Which statements describe procedures for configuring the switch's IP addressing information? Select TWO.
- A. Connect to the switch using the serial console interface, enter the global configuration level, enable DHCP, and assign an address scope.
 - B. Connect to the switch using the serial console interface, enter the global configuration level, and assign a box-wide IP address and mask.
 - C. Connect to the switch using the serial console interface, enter the global configuration level, and assign an IP address and mask within the VLAN 1 context configuration level.
 - D. Leave the switch at its default settings and allow it to acquire a reserved IP address, mask, and default gateway from a DHCP server.
 - E. Connect to the switch using the Telnet interface, enter the global configuration level, and assign a box-wide IP address.

Answer: CD

6. You have just finished configuring Multiple Spanning Tree (MST) on HP ProCurve 5348xl switches at a customer site. While checking your configuration, you notice that two switches have declared themselves to be the Root in one MST instance. How can you correct this configuration error? Reconfigure the _____.
- A. bridge priority on one of the switches
 - B. switches so that they have the same configuration name and revision number
 - C. VLAN assignments on the switches
 - D. port priorities on the links between the switches

Answer: B

7. You need to configure VLANs on an HP ProCurve 5300xl switch that is currently set to factory defaults. You issue the CLI command `no vlan 1 untagged a1-a4`

What will the result of this command be?

- A. Ports a1-a4 will be removed from VLAN 1.
- B. You will receive an error saying you cannot remove the ports from VLAN 1.
- C. The ports will become tagged members of VLAN 1.
- D. You will receive a prompt asking which VLAN the ports should be assigned to.

Answer: B

8. You are configuring an HP ProCurve 5300xl switch that will act as a default gateway for devices in VLAN 70. What configuration steps are necessary to enable the switch to perform this function? Select TWO.
- A. Add the switch's uplink ports to VLAN 70.
 - B. Assign an IP address to the switch's VLAN 70 interface.
 - C. Enable IP routing.

- D. Configure all ports that are members of VLAN 70 as tagged.
- E. Configure the switch with a default gateway.

Answer: BC

9. You are assigned to a team that is designing a new HP ProCurve solution. The team soon will begin work on diagramming the network's physical connectivity. What is the appropriate phase of the design process for this activity?

- A. assess customer needs
- B. develop and propose a solution
- C. implement and document the solution
- D. it can be done in any phase

Answer: B

10. You have been sent to install and configure HP ProCurve switches on a network that already includes switches manufactured by Cisco Systems, Inc. During planning meetings, the network administrator often refers to "trunk ports." What does the administrator mean?

- A. ports that connect the distribution and core layers
- B. ports that are configured for gigabit connectivity
- C. ports that are aggregated into a single logical port
- D. ports that carry multiple VLANs

Answer: D

11. You have been asked to install and configure HP ProCurve switches in a network that includes switches manufactured by Cisco Systems, Inc. During a planning session, the network's administrator repeatedly refers to the "access ports" on the Cisco switches. What is an equivalent term or feature on HP ProCurve switches?

- A. edge ports
- B. untagged ports
- C. uplink ports
- D. trunk ports

Answer: B

12. You are assigned to configure HP ProCurve switches at a customer site for in-band management. Which of the following are in-band management methods? Select TWO.

- A. SNMP
- B. XMODEM
- C. serial console
- D. Telnet
- E. menu interface

Answer: AD

13. You are going to install and configure HP ProCurve switches in a network that includes a core switch manufactured by Cisco Systems, Inc. What VLAN configuration step is necessary to ensure compatibility with the native VLAN on the Cisco switch?

- A. Configure the VLAN for untagged status on the HP ProCurve switches.
- B. Configure the VLAN as the default VLAN on the HP ProCurve switches.
- C. Configure GARP VLAN Registration Protocol on the HP ProCurve switches.
- D. Configure the VLAN for management access to the HP ProCurve switches.

Answer: A

14. A network administrator at a customer site asks about the impact of classifying some high-priority traffic for an 802.1p value of 7 and other traffic for an 802.1p value of 6. What will the effect of this configuration be? The change in 802.1p value _____.

- A. is not possible because the 802.1p field does not support a value of 7
- B. will introduce network latency by making forwarding more complicated
- C. will provide more granular control over forwarding priority
- D. will make no difference in actual forwarding because both priorities are placed in the same physical queue on switches before forwarding

Answer: D

15. You have been asked to configure IGMP on an HP ProCurve Switch 5348xl at a customer site. While planning the configuration, you determine that the network does not currently include an IGMP Querier. To act as IGMP Querier, the switch must be configured with _____.

- A. an IP address for each VLAN that will support multicasting
- B. a Class D IP address
- C. 802.1p prioritization settings for each VLAN that will support multicasting
- D. a box-wide default gateway

Answer: A

More [HP0-648 Braindumps](#) Information

Related HP0-648 Exams

HP0-S20	HP2-T11	HP0-216	HP0-J25	HP0-648
HP0-683	HP0-S23	HP0-402	HP0-553	HP0-M30
HP2-Z05				

Other HP Exams

HP0-S19	HP0-M16	HP0-J27	HP0-072	HP0-644
HP0-263	HP0-512	HP0-070	HP0-756	HP0-P18
HP0-207	HP0-656	HP0-750	HP3-C15	HP0-791
HP2-Q01	HP0-S24	HP0-447	HP0-460	HP0-P11