



[HP HP0-J25](#)

Exam Name: HP StorageWorks AIS 2008 Delta Exam

Q & A : 70 Q&As

[Pdf Demo](#)

Quality and Value for the HP0-J25 Exam

[Just4Exams Practice Exams](#) for HP HP AIS HP0-J25 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

100% Guarantee to Pass Your HP0-J25 Exam

If you do not pass the HP AIS HP0-J25 exam on your first attempt using our Just4Exams ***HP0-J25 testing engine and pdf study guide***, we will give you a FULL REFUND of your purchasing fee.

Downloadable, Interactive HP0-J25 Testing engines and PDF Version

Our Exam Preparation Material provides you everything you will need to take a [HP AIS certification](#) examination. Details are researched and produced by [HP Certification](#) Experts who are constantly using industry experience to produce precise, and logical.

Free HP0-J25 Exams:

This is demo only, this pdf do not include the questions and answers picture

Exam : HP HP0-J25

Title : HP StorageWorks AIS 2008 Delta Exam

1. What are ways to access the MSA2000 Event Logs? (Select two.)

- A. Select Monitor > Status > view Event Log.
- B. Present and mount the maintenance LUN.
- C. Click the Event Log icon in the system panel.
- D. Browse to https://<MSA_name>:2381/EventLog.
- E. Dump the Event Log through the serial adapter cable.

Answer: AC

2. Which controller components of an EVA4400 are customer replaceable?

- A. only cache batteries
- B. the entire shelf as one unit
- C. all components that are available as spare parts
- D. all components you can replace without opening the shelf

Answer: C

3. On an EVA, which event log file is used to log disk shelf events?

- A. Controller Event log file
- B. Hardware Event log file
- C. Storage Cell Event log file
- D. Management Event log file

Answer: A

4. What can you use to display performance data provided by the EVA?

- A. SIM
- B. SSSU.exe
- C. Command View EVA
- D. performance monitor of the Microsoft Windows operating system

Answer: D

5. What is the status of the battery LED when the HSV300 controller cache is powered by the batteries?

- A. solid green
- B. solid amber
- C. flashing amber
- D. fast flashing green

Answer: C

6. When you add disks to a disk group on an EVA4400, what is a best practice to maintain redundancy to multiple disk failures?

- A. multiples of 2
- B. multiples of 6
- C. multiples of 8
- D. multiples of the number of disk shelves

Answer: C

7. Which critical events does the Device Specific Module (DSM) impact? (Select three.)

- A. error handling
- B. bus initialization
- C. request handling
- D. device initialization
- E. OS kernel interface
- F. plug and play interface

Answer: ACD

8. How do you acquire management access to fabric switches?

- A. through the FCIP link
- B. by using SmartStart EVA
- C. by using a Telnet connection
- D. through Command View EVA

Answer: C

9. On an EVA4400, how many mirrorclones of a demand-allocated snapshot can be created?

- A. 0
- B. 1
- C. 4
- D. 7

Answer: A

10. On an EVA4400, what is a requirement for a fully allocated snapshot in relation to its source?

- A. It must be located in the same disk group.
- B. It must be located in a different disk group.
- C. It must be assigned to a higher redundancy level.

D. It must be assigned to the same redundancy level.

Answer: A

11. What must be considered when creating virtual disks in an MSA2000?

- A. the cache settings for the virtual disk
- B. the desired LUN ID for the virtual disk
- C. the operating system of the associated hosts
- D. the availability of enough disk drives of the same type for the desired RAID level

Answer: D

12. On an EVA4400, where can you specify the algorithm used to distribute the load across the storage controller host ports?

- A. MPIO manager
- B. device manager
- C. host property page
- D. MPIO Device Specific Module (DSM)

Answer: A

13. You are starting Command View EVA by using the SmartStart EVA CD to manage a storage system. Which statement is correct?

- A. You must enable the Advanced mode in SmartStart EVA and right-click on the storage system icon.
- B. You must specify the IP address of the management server and select the storage system to manage within Command View EVA.
- C. You must specify only the name of the storage system; SmartStart EVA will automatically locate and start Command View EVA for this system.
- D. You must start Command View EVA from the SmartStart EVA CD without installation and select the storage system to manage within Command View EVA.

Answer: B

14. Which MSA2000 feature disables cache mirroring in active-active mode and might improve the I/O performance?

- A. write-back cache mode (WBCM)
- B. write-through cache mode (WTCM)
- C. super-sequential cache mode (SSCM)
- D. independent cache performance mode (ICPM)

Answer: D

15. Which types of spares are available in an MSA2000? (Select three.)

- A. vdisk spare
- B. array spare
- C. global spare
- D. default spare
- E. dynamic spare
- F. dedicated spare

Answer: ACE

More [HP0-J25 Braindumps](#) Information

Related HP0-J25 Exams

HP0-S20	HP2-T11	HP0-216	HP0-J25	HP0-648
HP0-683	HP0-S23	HP0-402	HP0-553	HP0-M30
HP2-Z05				

Other HP Exams

HP0-656	HP0-710	HP0-787	HP0-M29	HP0-J15
HP0-M86	HP0-065	HP0-240	HP0-064	HP0-401
HP0-P16	HP2-027	HP0-G12	HP2-T13	HP0-914
HP0-J34	HP3-C15	HP0-919	HP0-S20	HP2-K10