



[HP HP0-Y20](#)

Exam Name: ProCurve Adaptive EDGE Fundamentals

Q & A : 60 Q&As

Pdf Demo

Quality and Value for the HP0-Y20 Exam

[Just4Exams Practice Exams](#) for HP Certification I HP0-Y20 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

100% Guarantee to Pass Your HP0-Y20 Exam

If you do not pass the Certification I HP0-Y20 exam on your first attempt using our Just4Exams **HP0-Y20 testing engine and pdf study guide**, we will give you a FULL REFUND of your purchasing fee.

Downloadable, Interactive HP0-Y20 Testing engines and PDF Version

Our Exam Preparation Material provides you everything you will need to take a [Certification I certification](#) examination. Details are researched and produced by [HP Certification](#) Experts who are constantly using industry experience to produce precise, and logical.

Free HP0-Y20 Exams:

This is demo only, this pdf do not include the questions and answers picture

Exam : HP HP0-Y20

Title : ProCurve Adaptive EDGE Fundamentals

1. After monitoring switch status, a ProCurve University IT manager determines that the parameters associated with the Multiple Spanning Tree Protocol must be modified. In order to do this, the manager needs to move from the Operator level to the Manager level. Which command is used to accomplish this?

- A. enable
- B. configure
- C. manager
- D. write

Answer: A

2. Which configuration parameter is necessary to ensure that a ProCurve University management station with an IP address of 10.1.1.51/24 can manage a switch with an IP address of 10.1.1.6.1/24?

- A. default gateway
- B. default password
- C. default management profile
- D. default VLAN

Answer: A

3. Which configuration/monitoring interfaces are available for an IT consultant to remotely manage a customer's ProCurve switch using Telnet? (Select two.)

- A. web interface
- B. boot monitor interface
- C. ProCurve Manager
- D. command line interface
- E. menu interface

Answer: DE

4. You access a ProCurve switch using Telnet and see the following prompt after a successful login:

Switch_1A#

Which privilege level have you entered?

- A. Manager level
- B. Help Desk level
- C. Global Configuration level
- D. User level

Answer: A

5. Which 10 Gigabit Ethernet technology uses multimode fiber and supports a maximum distance up to 300 meters?

- A. 10-GbE ER
- B. 10-GbE LR
- C. 10-GbE SR
- D. 10-GbE X2-CX4

Answer: C

6. How long is the free trial period for ProCurve Manager Plus?

- A. 15 days
- B. 30 days
- C. 60 days
- D. 180 days

Answer: B

7. Which configuration step is necessary to enable remote management access to a ProCurve Switch 5348xl installed behind a firewall with only TCP port 80 unblocked?

- A. Enable the switch's web server at the CLI.
- B. Generate an SSL encryption key and store it in the firewall.
- C. Configure the switch with a web proxy server address.
- D. Assign an IP address and grant that IP address access in the firewall's allow list.

Answer: D

8. Which information can be found in the Link Layer Discovery Protocol (LLDP) neighbors table on a ProCurve 3500yl switch? (Select two.)

- A. system name
- B. MAC address of neighbors
- C. link status for each uplink port
- D. maximum hop counts in the topology
- E. ports Blocked state by Spanning Tree Protocol

Answer: AB

9. Which in-band management methods are available in a production environment using ProCurve switches? (Select two.)

- A. Telnet
- B. SNMP
- C. WBEM
- D. CIMON

E. IPMI

Answer: AB

10. A customer inquires about configuring the IP address on a new ProCurve 3500yl switch. What can you do to configure this information on the switch? (Select two.)

- A. Connect to the switch using the Telnet interface, enter the global configuration level, and assign a box-wide IP address.
- B. Leave the switch at its factory default settings and allow it to acquire an IP address, mask, and default gateway from a DHCP server.
- C. Connect to the switch using the serial console interface, enter the global configuration level, and assign a box-wide IP address and mask.
- D. Connect to the switch using the serial console interface, enter the global configuration level, enable DHCP, and assign an address scope.
- E. Connect to the switch using the serial console interface, enter the global configuration level, and assign an IP address and mask within the context of the VLAN used for management access .

Answer: BE

More [HP0-Y20 Braindumps](#) Information

Related HP0-Y20 Exams

HP0-M15	HP0-S18	HP0-M16	HP0-A01	HP0-M18
HP0-M19	HP0-S19	HP0-Y20	HP0-Y19	HP0-J24
HP0-J15	HP0-X02	HP0-063	HP0-J22	HP0-S17
HP0-M22	HP0-Y21	HP0-Y11	HP0-P10	HP0-P17

Other HP Exams

HP0-J23	HP0-742	HP0-450	HP0-704	HP0-242
HP0-A03	HP0-638	HP0-719	HP0-M12	HP0-512
HP0-M16	HP0-S12	HP0-241	HP0-210	HP0-A13
HP2-027	HP0-092	HP0-310	HP0-A21	HP2-990