

Exam : [HP HP0-Y23](#)

Title : **Deploying HP ProCurve
Products**

Version : **Demo**

1. What can be used as a destination when backing up the configuration on an HP ProCurve 3500yl switch?

(Select two.)

- A. TFTP server
- B. compact flash
- C. neighboring switch
- D. USB flash drive
- E. FTP server

Answer: AD

2. You must configure an HP ProCurve 3500yl switch for installation in a network that uses RSTP to form a single-instance Spanning Tree. What must you do to ensure that the 3500yl will participate in this Spanning Tree?

- A. Enter spanning-tree in the global configuration context.
- B. Enter spanning-tree rstp in the configuration context for every VLAN the switch shares with another switch.
- C. Enter spanning-tree protocol-version rstp in the Spanning Tree configuration context.
- D. Enter spanning-tree autodetect in the configuration context of every port where the switch will hear Spanning Tree BPDUs.

Answer: A

3. Which options are available at the following prompt in the CLI of an HP ProCurve 3500yl switch? (Select three.)

3500yl-24G#

- A. enable IP routing
- B. update switch software
- C. disable ports
- D. erase startup configuration
- E. define management passwords
- F. restart the switch
- G. assign IP address to VLAN interface

Answer: BDF

4. Which privilege level is indicated by the following prompt at the CLI of an HP ProCurve switch?

3500yl-24G>

- A. operator
- B. interface
- C. global configuration
- D. manager

Answer: A

5. You must configure an IP interface for VLAN 22 on an HP ProCurve switch. Besides the IP address, which parameter is required?

- A. subnet mask
- B. DNS server
- C. default gateway
- D. port members

Answer: A