



[Network Appliance NS0-501](#)

Exam Name: Network Appliance Implementation Engineer-SAN

Q & A : 99 Q&As

Pdf Demo

Quality and Value for the NS0-501 Exam

[Just4Exams Practice Exams](#) for Network Appliance NAC-NIE NS0-501 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

100% Guarantee to Pass Your NS0-501 Exam

If you do not pass the NAC-NIE NS0-501 exam on your first attempt using our Just4Exams **NS0-501 testing engine and pdf study guide**, we will give you a FULL REFUND of your purchasing fee.

Downloadable, Interactive NS0-501 Testing engines and PDF Version

Our Exam Preparation Material provides you everything you will need to take a [NAC-NIE certification](#) examination. Details are researched and produced by [Network Appliance Certification](#) Experts who are constantly using industry experience to produce precise, and logical.

Free NS0-501 Exams:

This is demo only, this pdf do not include the questions and answers picture

Exam : Network Appliance NS0-501

Title : Network Appliance Implementation Engineer-SAN

1. An organization currently has a NetApp Fibre Channel block-based solution. With limited budget and resources, they want to create a new disaster recovery site that utilizes a NetApp solution.

What would the optimal solution include?

- A. SnapMover and Fibre Channel at the disaster recovery site for all hosts
- B. SnapMirror and iSCSI at the disaster recovery site for all hosts
- C. Fibre Channel at both locations using ftp to replicate storage
- D. MetroCluster and NAS

Answer: B

2. Which utility on Solaris 10 can be used to collect information about firmware and driver versions for an Emulex LP1xxxx/LPe1xxxx HBA?

- A. EMutil
- B. SANutil
- C. hbainfo
- D. SANsurfer
- E. HBAnywhere

Answer: E

3. Which utility on Windows 2003 and Windows 2008 can be used to collect information about firmware and driver versions for an Emulex LP1xxxx/LPe1xxx HBA?

- A. EMutil
- B. SANutil
- C. fcp config
- D. SANsurfer
- E. HBAnywhere

Answer: E

4. Click the Exhibit button.

A Solaris 10 host with VERITAS Storage Foundation 4.1 is FCP attached to a FAS3140 high availability storage system running single image cfmode.

Using the diagram shown, which ports will be considered active by VERITAS DMP using the NetApp ASL to a LUN on controller 1 mapped to host 1?

- A. Port 0b on controller 1 only
- B. Port 0d on controller 1 only
- C. Port 0b and 0d on controller 1 only
- D. Ports 0b and 0d on both controller 1 and controller 2

Answer: C

5. Click the Exhibit button.

Given the information provided in the diagram, what is the appropriate FC topology?

- A. point-to-point
- B. switched fabric
- C. arbitrated loop
- D. ring

Answer: B

6. A company has a Fibre Channel environment and wants to connect a new host in a remote data center using 50/125um OM2 multi-mode fiber cable and needs to support 2 Gb speeds.

What is the maximum distance of the cable run supported in this situation?

- A. 50/125um OM2 multi-mode fiber cable supports up to 500 meters at 2 Gb.
- B. 50/125um OM2 multi-mode fiber cable supports up to 10000 meters at 2 Gb.
- C. 50/125um OM2 multi-mode fiber cable supports up to 150 meters at 2 Gb.
- D. 50/125um OM2 multi-mode fiber cable supports up to 300 meters at 2 Gb.

Answer: D

7. Which utility on Solaris 10 can be used to collect information about firmware and driver versions for a Qlogic QLAXxx/QLExxxx HBA?

- A. EMutil
- B. SANutil
- C. cfgadmin
- D. SANsurfer
- E. HBAnywhere

Answer: D

8. A company has deployed a NetApp dual controller FAS3100 series with iSCSI. Currently, there are five Windows servers and three Novell NetWare servers connected to the IP SAN. The customer wants to connect an HP-UX server to the IP SAN.

Which cfmodes allow all operating systems to co-exist in the IP SAN?

- A. single_image
- B. standby
- C. cfmodes not applicable
- D. dual_fabric

Answer: C

9. For which four operations would you use igroup throttles on a NetApp storage solution? (Choose four.)

- A. to assign a specific percentage of the queue resources on each physical port to the igroup
- B. to manage pathing to the LUNs
- C. to reserve a minimum percentage of queue resources for a specific igroup
- D. to limit the number of concurrent I/O requests an initiator can send to the storage system
- E. to restrict an igroup to a maximum percentage of use
- F. to manage space reclamation

Answer: ACDE

10. Which command do you use to see the rate of change between two successive Snapshot copies in a flexible volume in Data ONTAP?

- A. snap diff
- B. snap calculate
- C. snap delta
- D. snap space

Answer: C

More [NS0-501 Braindumps](#) Information

Related NS0-501 Exams

NS0-501	NS0-920	NS0-910
---------	---------	---------

Other Network Appliance Exams

NS0-201	NS0-121	NS0-501	NS0-510	NS0-131
NS0-301	NS0-163	NS0-210	NS0-120	NS0-330
NS0-151	NS0-170	NS0-130	NS0-530	NS0-102
NS0-310	NS0-111	NS0-101	NS0-153	NS0-320