



EMC e20-532

Exam Name: *networked storage-san specialist exam for storage admins*

Q & A : 113 Q&As

Pdf Demo

Quality and Value for the e20-532 Exam

[Just4Exams Practice Exams](#) for EMC Specialist e20-532 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

100% Guarantee to Pass Your e20-532 Exam

If you do not pass the Specialist e20-532 exam on your first attempt using our Just4Exams **e20-532 testing engine and pdf study guide**, we will give you a FULL REFUND of your purchasing fee.

Downloadable, Interactive e20-532 Testing engines and PDF Version

Our Exam Preparation Material provides you everything you will need to take a [Specialist certification](#) examination. Details are researched and produced by [EMC Certification](#) Experts who are constantly using industry experience to produce precise, and logical.

Free e20-532 Exams:

This is demo only, this pdf do not include the questions and answers picture

Exam : EMC E20-532

Title : Storage Area Network (SAN) Specialist for Storage Admins

1. Which Cisco tool is used to monitor, configure and manage multiple MDS switches?

- A. Device Tools
- B. SAN Manager
- C. Fabric Manager
- D. Connectrix Manager

Answer: C

2. Click the Exhibit button.

In this implementation, gateways are used to connect existing Fibre Channel devices to an IP network, and as such will include physical

interfaces for which two [2] networks?

- A. IP
- B. ATM
- C. Sonet
- D. Fibre Channel

Answer: AD

3. How many buffer-to-buffer (BB) credits can be allocated to a port on a Brocade DS16-B2 (Brocade 3x00) series switch?

- A. 27
- B. 54
- C. 64
- D. 108

Answer: D

4. Which three (3) are valid types of persistent bindings?

- A. S_ID
- B. D_ID
- C. WWNN
- D. WWPN

Answer: BCD

5. Which version of HBA firmware must be used with PowerPath?

- A. Current HBA firmware
- B. Firmware shipped with HBA
- C. Latest HBA Firmware from vendor
- D. Current approved EMC HBA firmware

Answer: D

6. Which view of Workload Analyzer will provide the aggregate utilization of all FA ports in the Symmetrix?

- A. Performance view
- B. Link utilization view
- C. Data collection view
- D. Performance traffic view

Answer: A

7. HBA has been replaced on a host in a customer environment. After rebooting the host, you notice that the host still sees all storage devices on all paths. Why?

- A. There is no LUN masking deployed on the storage array
- B. Zoning has been disabled on the switch or hardware/port zoning is in effect
- C. The WWPN of the host has not changed and hence there is no need for any changes to the SAN
- D. The old HBA has the same WWPN as the new one

Answer: AB

8. How many bits does a WWN contain?

- A. 16
- B. 24
- C. 32
- D. 64

Answer: D

9. Which native command on a B-series switch will provide data for EMC Customer Service?

- A. showtech
- B. supportshow
- C. supportlogs
- D. switchsupport

Answer: B

10. The PowerPath command, powermt, has reported a number of devices as dead. Which commands are used to remove the dead devices?

- A. powercf check; powermt restore; powermt config
- B. powermt check; powermt restore; powermt config

- C. powermt restore; powermt check; powermt config
- D. powercf restore; powermt restore; powermt config

Answer: C

11. What is the recommended minimum amount of memory in a management station for an EMC VisualSAN 4.0 installation in a mid-sized SAN?

- A. 256 MB
- B. 512 MB
- C. 1 GB
- D. 2 GB

Answer: C

12. Which option is used to prevent mirroring at the host level if the device is already mirrored at the storage level in a PowerPath Volume Manager 4.x environment?

- A. HW_MIRRORS_ON_REDUNDANT_SW_POLICY
- B. NO_MIRRORS_ON_REDUNDANT_HW_POLICY
- C. SW_MIRRORS_ON_REDUNDANT_HW_POLICY
- D. DISABLE_MIRRORS_ON_REDUNDANT_HW_POLICY

Answer: C

13. What is the difference between the native long-wave Fibre Channel distance that EMC supports vs. what Brocade supports?

- A. EMC: 10 km, Brocade: 35 km
- B. EMC: 20 km, Brocade: 10 km
- C. EMC: 35 km, Brocade: 15 km
- D. EMC: 35 km, Brocade: 80 km

Answer: D

14. Which command is used to backup the configuration of a Brocade switch?

- A. backupConfig
- B. configUpload
- C. configDownload
- D. firmwareDownload

Answer: B

15. A customer has plugged a new host into his SAN but cannot see the HBA WWNs appear in the Topology. What are two [2] ways to resolve?

- A. Reset the switch
- B. Rediscover the switch
- C. Enable SNMP on the switches
- D. Install the Host Agent and wait for the host to be discovered

Answer: BD

16. How many DS-32M2 switches can be mounted in a single EC-1200 cabinet?

- A. 10
- B. 12
- C. 14
- D. 16

Answer: B

17. A new HBA is added to a Sun Solaris host. After a reconfiguration reboot, the new HBA is logged into the FA port on the Symmetrix, but it cannot see any devices. Which two [2] must be verified?

- A. Correct HBA WWN and FA association exists in the VCMDDB
- B. LUN number conversion from hexadecimal to decimal in the sd.conf file
- C. LUN number conversion from decimal to hexadecimal in the sd.conf file
- D. LUN number conversion from hexadecimal to decimal in HBA driver configuration file on the host

Answer: AB

18. In the OSI 7-layer Network Model, which layer describes the cabling used to create Fibre Channel SANs?

- A. Layer 1, Physical
- B. Layer 2, Data Link
- C. Layer 3, Network

D. Layer 6, Presentation

Answer: A

19. Which statement about the MDS 9000 32-port switch module is correct?

- A. Can support 16 ISLs
- B. Has a non-blocking architecture
- C. Shares 2Gb bandwidth among four ports
- D. Has more bandwidth than the 16 port module

Answer: C

20. Which MDS-9000 director/switch is capable of supporting the emerging 10Gb bandwidth?

- A. 9140
- B. 9216
- C. 9509
- D. 9549

Answer: C

21. Click the Exhibit button.

How many total ports are used for ISLs (not available for host or storage connections) in this core/edge example?

- A. 3
- B. 6
- C. 9
- D. 12

Answer: D

22. Which EMC VisualSAN 4.0 component provides switch zoning capabilities?

- A. Zone Manager
- B. SAN Assistant
- C. Network Manager
- D. Configuration Manager

Answer: C

23. From Connectrix Manager, which two [2] levels of user rights can be assigned to specific users?

- A. Fabric Administrator
- B. System Administrator
- C. Product Administrator
- D. Configuration Administrator

Answer: BC

24. Click the Exhibit button.

What is represented by data flow in the picture?

- A. FCIP representation of remote DR
- B. ISCSI representation of remote DR
- C. FCIP representation of remote backup
- D. ISCSI representation of remote backup

Answer: A

25. Which two [2] components are required to use SAN Manager?

- A. NAS Agent
- B. FCC Agent
- C. SDM Agent
- D. SAN Manager license

Answer: CD

26. How many switching modules (line cards) can be inserted into the MDS-9509 Director?

- A. 5
- B. 6
- C. 7
- D. 8

Answer: C

27. Which two [2] management tools have SAN zoning capabilities in a McDATA environment?

- A. Connectrix Manager
- B. Fabric Control Watch
- C. Embedded Web Server
- D. Storage Virtualization Control

Answer: AC

28. Which database service needs to be verified if EMC VisualSAN 4.0 displays errors on program start?

- A. Oracle 8i
- B. Informix 9
- C. Sybase 11
- D. SQL Server 2000

Answer: D

29. How many buffer-to-buffer (BB) credits can be used on ports 4-23 in a DS-24M2 switch?

- A. 5
- B. 12
- C. 24
- D. 60

Answer: A

30. What does EMC VisualSAN 4.0 use to gather Brocade Switch information?

- A. SNMP
- B. Webtools
- C. SCSI INQ
- D. Navisphere CLI

Answer: A

More [e20-532 Braindumps](#) Information

Related e20-532 Exams

E20-520	e20-522	E20-381	e20-532	e20-510
e20-530	e20-580	e20-320	E20-522	

Other EMC Exams

E20-361	e20-825	E20-500	e20-651	E20-590
e20-822	E20-322	E20-830	e20-537	e20-855
e20-661	E20-351	E20-616	E20-455	E22-310
E20-120	e20-533	E20-616	E20-381	E20-840